

**Explosion Proof Network IP Camera - 4.0MP Resolution - 20FPS - Built-in Infrared - IP66 Rated - N4X**

Part #: [EXPCMR-IP-POEP-4MP-IR-1XLE3](#)



The EXPCMR-IP-POEP-4MP-IR-1XLE3 Network Explosion Proof Camera w/ Built-in Infrared Light from Larson Electronics is a remote inspection camera specifically designed for observation in hazardous locations. This explosion proof, dust/ignition proof, weather proof and tamper resistant camera provides the operator with a live feed from inside tanks, reactors, vessels or other hazardous locations. Operated remotely from a centralized control room, this remote inspection camera saves both time and money as well as contributing to workplace safety.

**Camera Features:** The EXPCMR-IP-POEP-4MP-IR-1XLE3 Network Explosion Proof Camera features a built-in 1/3" progressive-scan CMOS image sensor that delivers up to 4.0MP resolution at 20 fps. The wide angle fixed lens with 83° field of view is designed to cover large areas and work spaces. This explosion proof camera provides a crisp and clear image for everything within the 83° focal area. Total distance is dependent on mounting height and angle.

The 17-watt unit comes with built-in infrared lights to support image capturing in low-light conditions and after sunset. This component is available in two lighting configurations: spot and flood. Four Edison Edixeon® three watt LEDs producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. The spot configuration features a 10° beam that measures 120' L x 60' W. The flood configuration throws a 35° beam that measures 80' L x 80' W. The infrared light is powered with the camera, over POE.

**PoE+:** The explosion proof camera is compatible with PoE+ devices (IEEE 802.3at Type 2), 4PPoE devices (IEEE 802.3bt Type 3) and IEEE 802.3bt Type 4 devices. As a high-powered PoE device, the system draws a maximum of 17 watts. This unit is not compatible with IEEE 802.3af Type 1 PoE devices, as it exceeds the power limitations of the standard @ 15.4 watts maximum.

This remote inspection camera utilizes 120dB true Wide Dynamic Range, 3D Digital Noise Reduction and a true day/night IR-Cut Filter Removal to produce clear images in variable and low light conditions. The camera automatically switches from full color to IR mode when visible light falls below a certain level.

**Wiring:** Link-up with the camera is achieved via a customer provided RJ45 Ethernet cable which is ran back to the customer provided DVR system mounted outside the hazardous location. Camera power is delivered via the same Ethernet cable using Power over Ethernet (PoE+) technology. This not only increases flexibility in deployment, but also provides time and cost savings as well.

**Recording:** To record the stream from this camera, a NVR (network video recorder) is required. Larson Electronics provides a line of explosion proof, hazardous location, and non-classified NVR's to work in conjunction with this explosion proof camera. This camera is live-view capable without any NVR system via remote access to the camera. Three streams are available, one main stream for recording and two sub streams for live viewing or additional resources. Each stream can be configured to different resolutions and frame rates.

**Mounting:** The EXPCMR-IP-POEP-4MP-IR-1XLE3 Network Explosion Proof Camera features an ATEX/IECEx certified copper-free aluminum alloy body for durability. The camera and infrared light includes an adjustable rear-mounted polished stainless steel mounting bracket/handle. Additional accessory pole mounts and magnetic mounts are available separately.

**Applications:** Vessel, tank and reactor monitoring, remote observation of external facilities, monitoring of cleaning, spray patterns, mixing, foaming, reaction, and level.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

**Specifications / Additional Information****EXPCMR-IP-POEP-4MP-IR-1XLE3 Network Explosion Proof****Camera****Listing:** United States and Canada**Dimensions:** -**Camera Weight:** -**Total Watts:** 17W (Max)**Power Source:** PoE+ (IEEE 802.3at Type 2), 4PPoE (IEEE 802.3bt Type 3) and IEEE 802.3bt Type 4**Image Sensor:** 1/3" Progressive Scan CMOS sensor**Signal System:** NTSC**Video Resolution:** 4.0MP (2688\*1520)**Frame Rate:** Up to 20fps @ 2688\*1520 resolution**Compression Type:** H.264, H.264 OVC, MJPEG**Bit Rate:** 32Kbps - 16Mbps**Focal Length:** 4mm**Max Field of View:** 83°**Shutter Speed:** 1/3s to 1/10,000s**Min. Illumination:** 0.01 lux (Color) / 0 lux (w/ Built-in IR)**Infrared Wavelength Options:** 750 nm, 850 nm or 940 nm**Infrared Beam Pattern:** Flood or Spot**IR Spot Beam:** 120`L x 60`W**IR Flood Beam:** 80`L x 80`W**Day/Night:** True D/N w/Mechanical Cut Filter**Digital Noise Reduction:** 3D DNR**Ethernet Interface:** RJ45**Ethernet Speed:** 10/100**Protocols:** TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more**Remote Configuration:** Yes**Ambient Temperature Range:** -22°F to +140°F**Housing Materials:** Copper-free Aluminum Alloy**Lens Material:** 3/8" Thick Tempered Glass**Mounting:** Adjustable rear-mounted handle/bracket**Wiring Hub:** (2) 3/4" NPT**Quick Summary**

Class I, Divisions 1 &amp; 2, Groups B, C, D

Class I, Zones 1 &amp; 2, Groups IIB+H2, IIA

Class II, Divisions 1 &amp; 2, Groups E, F, G

Class III, Divisions 1 &amp; 2

Ex db IIC Gb

Ex tb IIC Gb Db IP66

NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

Main stream and two sub streams

Capable of programming unique settings per stream

ONVIF Profile S Certified

WDR (wide dynamic range) for auto adjusting

High Powered POE Device

**Special Orders/Requirements**

Contact us for special requirements

**Phone:** 1-903-498-3363**Toll Free:** 1-800-369-6671**Fax:** 1-903-498-3364**E-mail:** sales@larsonelectronics.com[Scroll Down to Purchase-](#)

This product does not qualify for free shipping.

Part #: EXPCMR-IP-POEP-4MP-IR-1XLE3 (223005)

Options:

EXPCMR-IP-POEP-4MP-IR-1XLE3- BEAM CONFIG - IR WAVELENGTH

Example: EXPCMR-IP-POEP-4MP-IR-1XLE3-FLD-750NM

BEAM CONFIG		IR WAVELENGTH	
Flood	-FLD	750 nm	-750NM
Spot	-SPT	850 nm	-850NM
		940 nm	-940NM

Links (Click on the below items to view):

- [Hi-Res Image 1 - Explosion Proof Network IP Camera](#)