

EPCS-1X3PS.HOA-24V-PTM.2K

Explosion Proof VFD Remote Control Station - C1D1/C2D1 - 2K Ohms - (3) PS - Hand, Off, Auto Switch

Product ID: 223033

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPCS-1X3PS.HOA-24V-PTM.2K Explosion Proof VFD Control Station

Unit Type: Variable Frequency Drive Remote Control Station

Dimensions: -

Weight: -

Selector Switch: Three Position (Hand, Off, Auto)

Rotary Dial: 0-10 V Input - Speed Control

Speed Control: 2K Ohm Potentiometer, 0.5 W

Materials: Non-Sparking Aluminum

Mounting: Surface Mount

Hubs: (1) 3/4" or 1/2" NPT

Ratings

Class I, Divisions 1 & 2 Groups C,D

Class II, Divisions 1 & 2 Groups E,F,G

Class III

NEMA 7 (C,D); 9 (E,F,G)

Certified to USA/Canadian Standards

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EPCS-1X3PS.HOA-24V-PTM.2K from Larson Electronics is an Explosion Proof Variable Frequency Drive Remote Control Station for Class I, II and III rated work sites. This explosion proof unit features a three position selector switch for activation and a rotary dial for speed control of the connected VFD. Constructed from non-sparking aluminum, this remote control station contains one 3/4" or 1/2" NPT hub for completing input/output connections.

The EPCS-1X3PS.HOA-24V-PTM.2K is designed to facilitate remote control for

variable frequency drives in flammable environments. This explosion proof unit contains a three-position (hand/off/auto), maintained selector switch. Operators may also access a rotary dial for speed control, which features 0-10V input. Speed control is provided by a 2K Ohm potentiometer. This explosion proof remote control box requires connection to the start, stop and speed control signals of the VFD.

Constructed of non-sparking aluminum, the NEMA-rated unit is weatherproof. The EPCS-1X3PS.HOA-24V-PTM.2K offers superior corrosion resistance and is suitable for Class I, II and III rated combustible sites.

Wiring/Mounting: Operators can completing wiring connections and mounting on surfaces, walls or conduits via a 1/2" or 3/4" NPT hub.

Suggested Applications: Hazardous locations, oil and gas sites, agricultural operations, grain storage, woodshops, motor control and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

EPCS-1X3PS.HOA-24V-PTM.2K

Product ID: 223033

Export Control Classification Number (ECCN): EAR99

Options:

EPCS-1X3PS.HOA-24V-PTM.2K-**Hub Config**-**Termination**

Example: EPCS-1X3PS.HOA-24V-PTM.2K-**0.5IN**-**DE**

Hub Config	
1/2 INCH	-0.5IN
3/4 INCH	-0.75IN

Termination	
DEAD END	-DE
FEED THRU	-FT

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)