Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

SPLED-IND-PED-WS-24.24-DF-MS

Pedestrian LED Crossing Sign - 24"x24" - Class I LED Beacon - Motion Detector - Solar/Double Face

Product ID: 223116

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

SPLED-IND-PED-WS-24.24-DF-MS Pedestrian LED Crosswalk Sign

Listing: -
Lamp Type: LED
Dimensions: 24" x 24" (Sign Only)
Weight: 4 lbs (Strobe Light Only)
Operation: 100% Remote Solar Power
Wattage: 14.4W
Lumens: 1,440 lms
Luminous Efficiency: 100 Lumens per Watt
LED Lamp Life Expectancy: 50,000+ Hours
Strobe Color Options: Green, Amber, Red, White or Blue
Color Rendering Index: -
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Beam Angle (Strobe): Full, 360°
Lighting Configuration (Strobe): Strobing Flash
Sign Configuration: Double Faced
Power Efficiency: -
Power Factor: -

Ratings/Features

SAEJ845, Class 1- Brightest Rating
Motion Sensor
Multi-Strobe Pattern Options
Waterproof
25` Minimum Motion Sensing Range
100% Remote Operation
Double Sided Sign

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Ambient Temp: -45°C to +55°C

Materials: Polycarbonate

Mount: Surface

Battery Type: Sealed Lead Acid

Wiring: 10` of 16/2 SOOW Cord b/w Solar Panel and Top of Sign

Sign Color: Yellow/ Black

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics SPLED-IND-PED-WS-24.24-DF-MS Pedestrian LED Crossing Sign enhances pedestrian safety and is ideal for parking lots and sidewalks. The double-sided crosswalk sign measures 24"x24" and leverages a Class I rated LED strobe with an adjustable motion sensor for illuminative notifications, when movement is detected. This unit is a 100% remote system powered by a solar panel. Color choices for the LED beacon include green, amber, red, white or blue.

The SPLED-IND-PED-WS-24.24-DF-MS offers illuminated safety for pedestrians. Reflective material on the double-faced yellow/black sign ensures visibility, when viewed from different angles. Measuring 24"x24", the unit features a Class I rated LED beacon located above the sign. The LED strobe light is activated when movement is detected by the adjustable motion sensor, which supports a minimum sensing range of 25`. The motion sensor can be pointed in different directions, allowing the sign to face traffic, while the sensor faces the direction of crosswalk traffic. The light will stay on for 15 seconds after motion is detected and the sensitivity of the sensor can be adjusted to meet each application.

The powerful LED beacon is equipped with 30 flash patterns, including four simulated rotating patterns. This beacon has a black powder coated die cast base that contains a fully potted circuit board. A clear polycarbonate lens protects the LED assembly; and the housing is waterproof, shock resistant and built for reliable operations. The strobe light is equipped with auxiliary LEDs on top, helping to make this a Class I rated beacon.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Power/Wiring: This unit is 100% remote, powered by a solar panel. The 30 watt solar panel recharges the battery in 5 hours with direct sunlight. As with all solar powered

equipment, charging time is affected by the amount of available ambient light. When ambient light levels drop below a certain level, such as on very cloudy days, the unit will not recharge.

A sealed lead acid battery pack is contained within the solar panel, not the crosswalk sign. The mounting apparatus is designed to allow a variety of mounting options including flat surfaces such as a wall and square or round pole mounting. The crosswalk sign is connected to the panel by a 10 foot 16/2 SOOW cord that provides flexibility for positioning of the solar panel and sign into their respective optimum locations independently of each other.

Mount: The solar panel is weatherproof and designed to catch the maximum amount of sunlight possible when properly mounted. The motion sensor will activate the light upon detecting movement within range of the panel and keep the light on for 15 seconds after detection.

For best results and to ensure clarity, the double-faced pedestrian sign should be mounted in a way that both sides are visible.

Applications: Sidewalks, parking garages, busy industrial facilities, delivery bays, high-activity locations and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

SPLED-IND-PED-WS-24.24-DF-MS

Product ID: 223116

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

SPLED-IND-PED-WS-24.24-DF-MS-Color

Example: SPLED-IND-PED-WS-24.24-DF-MS-GR

Color	
GREEN	-GR
AMBER	-AMB
RED	-RED
WHITE	-WHT
BLUE	-BLU

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **Video1**
- **Video2**
- **Video3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**