

C1D2 LED Pivoting Light - 4 Ft 2 Lamp - Offshore LED Rig Light - Meets USCG Specs -Day/Night Sensor

[HAL-48-2L-LED-BMSW-DNS](#)



HAL-48-2L-LED-BMSW-DNS Hazardous Area

NRTL Listed for United States & Canada

Dimensions: 51.1"-L x 7.09"-W x 8.65"-H

Weight: 22.2 Lbs

Total Watts: 56 watts

Total Lumens: 6720

Voltage: 120V AC, 208-277V AC or 24V DC.

LED Lamp Life Expectancy: 50,000 Hours

Luminous Efficiency: 120 Lumens per Watt

Operating Temp Range: T4A rated -40°C to +65°C

Beam Angle: 150°

Color Temp: 5600K or 4500K - Color Rendering Index-75

Mounting: Back Mount Swivel Bracket

Wiring Hub: 1/2" or 3/4" threaded

Materials: Sheet aluminum housing, acrylic lens

Warranty: **YES**- 5 Years*

Ratings/Approvals

Class 1 Division 2, Groups A, B, C & D

NRTL Certified to UL 844

NRTL Certified to UL 1598A Marine Type

Listed for Canada

T4 Temperature Rating

Meets USCG Specs

California Title 24 Compliant

Day/Night Sensor

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-498-3363

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HAL-48-2L-LED-BMSW-DNS Hazardous Area LED Light Fixture with Day/Night Sensor is NRTL Listed for United States and Canada Class 1 Division 2 Groups A, B, C and D - NRTL Certified to UL 1598A listed, has a T4A temperature rating and ideal for hazardous locations where flammable chemical/petrochemical vapors may be occasionally encountered. The built-in day/night photocell sensor allows this fixture to operate automatically depending on the ambient light levels detected near the fixture. This hazardous location LED light carries a United States Coast Guard approval, making it ideal for applications such as oil rigs, ships, offshore applications, petrochemical, manufacturing, chemical storage, and water treatment centers.

This four foot long, two lamp LED fixture is ideal for operators seeking a top quality hazardous location light that will reduce operating costs, improve lighting quality and reduce downtime incurred from frequent servicing intervals. The HAL-48-2L-LED-BMSW-DNS fixture is a 4 foot long, 2 lamp, Class 1 Division 2 Groups A, B, C and D hazardous area LED light that takes the reliability and efficiency of a fluorescent fixture and adds even longer lamp life and efficiency with high

output LEDs. This fixture is T4A temperature rated and comes standard with our high power 28 watt LED lamps. The lamps are protected by a powder coated aluminum frame and shatter and heat resistant clear acrylic lens secured with ten zinc coated steel draw latches.

We now offer our second generation LED tube lamps with this fixture which have increased this hazardous location light's performance. This two lamp HAZLOC LED linear fixture is lighter in weight and produces more light than hazardous location fluorescent fixtures. The four foot long LED tube design bulbs included with this unit are rated at 50,000 hours of service life, which is over twice as long as standard T8 bulbs.

This fixture carries a T4A temperature rating and is NRTL Certified to U.L. 595 and UL 1598A Marine Type approved for use marine environments. The fixture is constructed of copper free sheet aluminum and powder coated. The lamp reflector is corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. The HAL-48-2L-LED-BMSW-DNS is weatherproof and provides operators in hazardous locations with a highly efficient, reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present. [Click here to read the NEC description for explosion proof and hazardous locations.](#)



[Click Image to Enlarge](#)



[Click Image to Enlarge](#)



[Click Image to Enlarge](#)



We have eliminated the ballast box normally associated with fluorescent fixtures which reduces overall weight and creates a slimmer unit profile. There is no ballast in this unit and the included [LEDT8-28W-V1](#) LED lamps have a 50,000+ hour service life, both of which result in extreme efficiency and greatly reduced maintenance costs. The solid state design of the LED lamps give this fixture superior resistance to damage from vibration, extremes in temperature and a lamp service life over twice that of standard fluorescent bulbs.

Unlike the glass tube design of traditional fluorescent lamps, these LED T-Style lamps have no filaments or fragile housings to break during operation. Instead of using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. The LED assembly is mounted to the "tube" constructed from extruded aluminum, with a polycarbonate lens protecting the LEDs. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than fluorescent lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional fluorescent lighting.

Day/Night Sensor:The HAL-48-2L-LED-BMSW-DNS features an integrated day/night photocell that allows for automatic operation of the light when ambient

light levels drop below a certain amount such as in low light conditions or at night. This automatic operation of the light adds an additional layer of convenience to this LED light fixture. Operators can adjust the photocell sensor to turn the light on at different ambient light levels to accommodate the specific needs of the location where the light is installed. This feature adds even more versatility to this unit.

The 28 watt LED lamps produce 30% more illumination than standard T8 bulbs while offering lower amp draw and increased reliability. Each lamp produces 3360 lumens at 120 lumens per watt, for a combined 6720 total lumen light output. A HAL-48-2L-T8 hazardous location fluorescent light, with a combined total of 64 watts, draws 0.54 amps at 120 volts AC. This LED version of the same light, with a total of 56 watts, draws only 0.47 amps at 120 volts AC. The HAL-48-2L-LED-BMSW-DNS is universal voltage, not multi-tap, and operates on 120V AC, 208-277V AC or 24V DC.

Energy Consumption Comparison

	T5HO	T8	LED
Wattage	108 watts	64 watts	56 watts
Amp Draw @ 120V AC	0.90 amps	0.54 amps	0.47 amps
Amp Draw @ 220V AC	0.49 amps	0.29 amps	0.25 amps
Amp Draw @ 240V AC	0.45 amps	0.27 amps	0.23 amps
Amp Draw @ 277V AC	0.39 amps	0.24 amps	0.20 amps
Amp Draw @ 12V DC	9 amps	5.34 amps	4.67 amps
Amp Draw @ 24V DC	4.5 amps	2.67 amps	2.34 amps
Lamp Life Expectancy	20,000 hours	24,000 hours	50,000 hours
Color Temperature	5000K / 4100K	4100K	5600K
Operation cost per year (12hs/day @ 12c/kWh)	\$56.77	\$33.64	\$29.43

Mounting Options:

Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.

Standard Surface Mount Brackets:

Each L bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two bolts on either side of the bracket. The bolts act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be pivoted by loosening the that hold the bracket to the mounting peg. This fixture allows 45° of pivot from the 90° point.

Suggested Applications: Aircraft maintenance, oil drilling rigs, refineries, marine and salt water environments, ships, tankers, offshore, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed streamlined ribbed corrosion-resistant, copper free sheet aluminum body for better heat dissipation and extended ballast life.
4. Aluminum lens frame for greater strength
5. Re-lamping done via 10 draw latches, which enable the

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable



- operator to unlatch the lens and access the lamps.
- 6. Heavy gauge aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
- 7. 1/2" or 3/4", threaded access hole for wiring conduit.
- 8. Units can be wired end to end in series.

- business certifications.
- 9. Bright, even light maintains consistent color over time.
- 10. Instant on/off – No flickering, delays or buzzing.
- 11. Very good color rendering.
- 12. Vibration/impact resistant.
- 13. Significantly cooler operation.
- 14. Less frequent outages, higher output improves workplace safety.



Options:

HAL-48-2L-LED-BMSW-DNS-Voltage-Color Temp-Hub Config

Example: HAL-48-2L-LED-BMSW-DNS-120VAC-120VAC-0.5IN

Voltage	
120V AC	-120VAC
208-277V AC	-277VAC
24VDC	-24VDC

Color Temp	
5600K	-120VAC
4500K	-277VAC
3000K	-24VDC

Hub Config	
1/2IN	-0.5IN
3/4IN	-0.75IN

Links (Click on the below items to view):

- [Addpic4large](#)
- [Class 1 Division 2 LED Light Fixture - Rotating brackets allowing 90 degrees of rotation](#)
- [large](#)
- [medium](#)
- [Snelson light fixture alternative](#)
- [SpecSheet](#)
- [Surface mount adjustable LED Hazardous Area Linear Light Fixture](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)