

**Explosion Proof Non Fused Disconnect Switch - 200 Amp - C1D1&2 - 3-Pole - (2) 2" NPT Hubs**

Part #: EPNFDS-200A-3P-2X2NS

**Made in the USA**

The Larson Electronics EPNFDS-200A-3P-2X2NS explosion proof 200 amp non-fused disconnect switch provides operators with a Class I and II, Divisions 1 and 2 cast aluminum enclosure that provides overcurrent and short circuit protection of service entrance, feeder or branch circuits, lighting, heating, appliance and motor circuits. This explosion proof disconnect switch features an EHD frame and has a 3-Pole configuration. The EPNFDS-200A-3P-2X2NS operates on a maximum of 600V AC and features one cast 2" conduit hub on the top and one cast 2" conduit hub on the bottom.

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES\***

The EPNFDS-200A-3P-2X2NS explosion proof disconnect switch is made of cast aluminum and features a rectangular bolted cover design for uniform and attractive installations. The cover bolts and hinges are made from stainless steel. The external on/off lever can be locked into the "off" position with room for up to three padlocks for superior security. The internal circuit breaker handle mechanism is a sliding plate type mounted to the cover. The circuit breaker is trip free of the external handle mechanism.

**Applications:** Petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

**Specifications / Additional Information****EPNFDS-200A-3P-2X2NS Explosion Proof Disconnect Switch / Breaker****Dimensions:** 28.28"L x 16.28"W x 12.63"H**Weight:** 70 lbs**Configuration:** 3-Pole**Voltage Rating:** 600V AC Max**Amps:** 200**Fusible:** No**Materials:** Cast Aluminum**Hardware Materials:** Stainless Steel**Mounting:** Surface Mount**Hub Sizes:** (2) 2" NPT (one top one bottom)**Hub Qty:** 2**Hub Locations:** One on Both Top and Bottom**Conduit:** Operator Provided

\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

[Scroll Down to Purchase](#)

[This product does not qualify for free shipping.](#)

[Part #: EPNFDS-200A-3P-2X2NS \(223632\)](#)

**Features/Ratings**

Class I Division 1 &amp; 2 Groups B, C &amp; D

Class I Zones 1 &amp; 2 Groups IIB+ H2 &amp; IIA

Class II Division 1 &amp; 2 Groups E, F &amp; G

Class III

NEMA 3, 4, 4X, 7(B,C,D) 9(E,F,G)

**Special Orders- Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com

Links (Click on the below items to view):

- [Hi-Res Image 1](#)