Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227

4.0MP Explosion Proof Network IP Camera for Cannabis Extraction - 120-240V AC - TCP/IP - BHO/THC/CBD

Product ID: 223651

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227 Network Explosion Proof Camera for Cannabis Extraction

Listing: United States, Canada, European Union, International
Dimensions: -
Weight: -
Camera Watts: 5W (Max)
Infrared Light Watts: 12W
Camera Power Source: PoE (802.3af)
Infrared Light Voltage: 120-240V AC
Image Sensor: 1/3" Progressive Scan CMOS Sensor
Signal System: NTSC
Video Resolution: 4.0MP (2688*1520)
Frame Rate: Up to 20fps @ 2688*1520 Resolution
Compression Type: H.264, H.264 OVC, MJPEG
Bit Rate: 32Kbps - 16Mbps
Focal Length: 4mm
Max Field of View: 83°
Shutter Speed: 1/3s to 1/10,000s
Min. Illumination: 0.01 lux (Color) / 0 lux (w/ Built-in IR)
Infrared Wavelength Options: 750 nm, 850 nm or 940 nm
Infrared Beam Pattern: Flood or Spot
IR Spot Beam: 120`L x 60`W
IR Flood Beam: 80`L x 80`W
Day/Night: True D/N w/Mechanical Cut Filter
Digital Noise Reduction: 3D DNR
Ethernet Interface: RJ45

Quick Summary

Listed for United States & Canada
Class I, Divisions 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Divisions 1 & 2, Groups E, F, G
Class III, Divisions 1 & 2
NEMA 3R, 4, 7 (B, C, D), 9 (E, F, G)
NRTL Listed to UL 508A
NRTL Listed to UL 1203
NRTL Listed to CSA C22.2 No 14, 25, 30
Main stream and two sub streams
Capable of programming unique settings per stream
ONVIF Profile S Certified
WDR (wide dynamic range) for auto adjusting
TCP/IP Infrared Light Control

Ethernet Speed: 10/100
Protocols: TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Infrared Light Control: Modbus TCP/IP Network Programmable (On/Off, Scheduling and Network Functions)
Remote Configuration: Yes
Ambient Temperature Range: -22°F to +140°F
Housing Materials: Copper-free Aluminum Alloy
Lens Material: 3/8" Thick Tempered Glass
Mounting: Adjustable rear-mounted handle/bracket
Wiring Hub: (2) 3/4" NPT

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227 Network Explosion Proof Camera w/ Built-in Infrared Light from Larson Electronics is a remote inspection camera specifically designed for observation in butane THC extraction rooms and hemp processing facilities. This explosion proof, dust/ignition proof, weather proof and tamper resistant camera provides the operator with a live feed inside mobile extraction labs, as well as indoor cannabis growing and processing sites. Operated remotely from a centralized control room, this remote inspection camera saves both time and money as well as contributing to workplace safety.

Camera Features: The EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227 Network Explosion Proof Camera is a powerful solution for cannabis extraction facilities requiring real-time monitoring and cutting-edge security. This compact unit features a built-in 1/3" progressive-scan CMOS image sensor that delivers up to 4.0MP resolution at 20 fps. The wide angle fixed lens with 83° field of view is designed to cover large areas, including mobile labs and temporary extraction rooms. This explosion proof camera provides a crisp and clear image for everything within the 83° focal area, allowing businesses and persons with access (local/state officials, operation managers, inspectors, etc.) to view the workplace in real-time. Total distance is dependent on mounting height and angle.

The monitoring device comes with built-in infrared lights to support image capturing in low-light conditions and after sunset. This component is available in two lighting configurations: spot and flood. Four Edison Edixeon® three watt LEDs producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. The spot configuration features a 10° beam that measures 120`L x 60`W. The flood configuration throws a 35° beam that measures 80`L x 80`W. The explosion proof infrared light is powered using a customer-provided 120-240V AC power source, while the explosion proof camera is powered by PoE.

This remote inspection camera utilizes 120dB true Wide Dynamic Range, 3D Digital Noise Reduction and a true day/night IR-Cut Filter Removal to produce clear images in variable and low light conditions. The camera automatically switches from full color to IR mode when visible light falls below a certain level.

Modbus TCP/IP (Infrared Light): On/off, scheduling and network features for the explosion proof infrared light are facilitated via Modbus TCP/IP protocol. This remote setup enables operators to apply custom schedules and configurations for the infrared light, such as operation during after hours, integration with a day/night photocell and more.

Wiring: Link-up with the camera is achieved via a customer provided RJ45 Ethernet cable which is ran back to the customer provided DVR system mounted outside the hazardous location. Camera power is delivered via the same Ethernet cable using Power over Ethernet (PoE) technology. This not only increases flexibility in deployment, but also provides time and cost savings as well.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 – 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance

cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 – 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Recording: To record the stream from this camera, a NVR (network video recorder) is required. Larson Electronics provides a line of explosion proof, hazardous location and non-classified NVRs for BHO/THC/CBD extraction facilities, which work in conjunction with this explosion proof camera. This camera is live-view capable without any NVR system via remote access to the camera. Three streams are available, one main stream for recording and two sub streams for live viewing or additional resources. Each stream can be configured to different resolutions and frame rates.

Mounting: The EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227 Network Explosion Proof Camera features an ATEX/IECEx certified copper-free aluminum alloy body and weighs a total of 12 pounds. The camera and infrared light includes an adjustable rear-mounted polished stainless steel mounting bracket/handle. Additional accessory pole mounts and magnetic mounts are available separately.

Applications: Hemp processing, cannabis extraction rooms, legal cannabis grow rooms, hemp greenhouses, butane-based extraction facilities, THC, BHO, CBD, medicinal cannabis compliance, security, monitoring, labs, research and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227

Product ID: 223651

Export Control Classification Number (ECCN): EAR99

Options:

EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227-Beam Config-Wavelength

Example: EXPCMR-CER-IP-POE-4MP-IR-ANC-1XLE3-1227-FL-750NM

Beam Config	
FLOOD	-FL
SPOT	-SP

Wavelength	
750 NM	-750NM
850 NM	-850NM
940 NM	-940NM

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- ATEX Certificate (European Explosion Proof)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- Certificate 4, Misc
- IEC Ex Certificate (International Explosion Proof)
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- Video1
- Video2
- Video3
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map