Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ

45 kVA Isolation Transformer - 400V Delta Primary - 240Y/136 Wye-N Secondary - NEMA 3R - 60Hz

Product ID: 223845

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

1**MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ Isolation Transformer**

1**Phase:**1 Three Phase
1**Frequency:**1 60 Hz
1**kVA:**1 45
1**Primary Voltage:**1 400 V Delta
1**Primary Connection:**1 Delta
1**Secondary Voltage:**1 240Y/136 V
1**Secondary Connection:**1 Wye-N
1**Taps:**1 2 - 2.5% FCAN; 4 - 2.5%
14 1**Winding Material:**1 Aluminum
14 1**Primary Termination (Std):**1 -
14 1**Secondary Termination (Std):**1 -
14 1**Mounting:**1 Floor or Wall
14 1**Insulation:**1 220°C
14 1**Temperature Rise:**1 150°C
14 1**Sound Level:**1 Meets NEMA ST-20 Standards
14 1**Enclosure Material:**1 NEMA Type 3R Heavy Duty Ventilated - Steel
14 1**Finish:**1 ANSI 61 Grey, UL50 Finish
14 1**Dimensions:**1 28.00"H x 25.00"W x 23.50"D
14 1**Weight:**1 415 lb

1**Approvals/Ratings**

1Listing: UL Listed
1CSA Certified
1Isolation Transformer

1**Special Orders - Special Requirements**

1Contact us for special requirements

1Toll Free: 11-800-369-6671
1**Intl:**1 1-903-270-1187
1**E-mail:** 1sales@larsonelectronics.com

110

The MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ 400 V Delta 3 Phase Energy Efficient 60 Hz Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 45 kVA, the MT-ATX-3P-480D-45KVA-400Y.321-N3R-50HZ isolation transformer is a three phase unit with a primary voltage of 400 V Delta. It also provides a secondary voltage of 240Y/136 V Wye-N. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be either floor or wall mounted. The unit also features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


DANGER PELIGRO




M



MT-DOE16-3P-400D-45KVA-240Y.136-N3R-60HZ

Product ID: 223845

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Operations Manual**
- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**