

## **EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1**

### **Solar Powered Explosion Proof LED Strobe Light - C1D1 - Wireless Remote - 80' Cord - C1D2 Panel**

**Product ID: 223941**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

#### **EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 Explosion Proof Solar Powered LED Strobe Lamp**

**Listing: United States & Canada**

**Lamp Type: Solar LED**

**Lamp Dimensions: 7.25" -W x 15" -H**

**Solar Panel Dimensions: 11-3/8"L x 15-3/4"D**

**Weight: 9 lbs (Strobe Only)**

**Voltage: 12V DC**

**Battery: (4) 18aH Sealed Lead Acid Batteries**

**Runtime: -**

**Charging Time: 5 Hours**

**Total Watts: 7W**

**Candela: 1,235**

**Light Color Options: Red, Green, Blue, Amber or White**

**LED Lamp Life Expectancy: 50,000+ Hours**

**Beam Angle: 360°**

**Lighting Configuration: Strobing Flash**

**Strobe Count: 4 per Second**

**Wireless Remote Switch: Push Button, On/Off**

**Wireless Signal Receiver: Included**

**Operating Temp Rating: T3C**

**Housing Material: Cast Aluminum**

**Finish: Polyester Powder Coating**

#### **Ratings/Approvals**

Class I, Division 1&2 Groups C,D

Class II, Division 1&2 Groups E,F

Class III

UL 844

UL 1598 Marine Type

UL 595 Outdoor Marine Type (Saltwater)

UL Certified - U.S./Canadian Safety Standards

IP67 Strobe

NEMA 4X

#### **Special Orders - Special Requirements**

Contact us for special requirements

**Intl: 1-903-270-1187**

**Toll Free: 1-800-369-6671**

Mounting: Inverted Pendant Mount

Wiring: 80' 10/2 SOOW Cord

Fax: 1-903-498-3364

E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

### Made in Texas

**The EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 Solar Powered Explosion Proof LED Strobe Light from Larson Electronics is a reliable lighting solution for remote areas and standalone applications where connection to external power is either impractical or unavailable. Equipped with a wireless remote and signal receiver, this 7-watt strobe lamp offers 360 degrees of illumination and is protected by a cage guard. Charged by a Class I, Division 2 solar panel, four 12V AC 18aH sealed lead acid batteries provide constant, reliable power to the LED strobe light.**

The EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 is a sustainable LED strobe lighting solution for hazardous locations and remote sites. This explosion proof 7-watt lamp operates on 12V DC and features a strobing flash lighting configuration, at a rate of 4 strobe counts per second. Charged by the Class I, Division 2 rated solar panel, four 12V AC 18aH sealed lead acid batteries provide constant, reliable power. The batteries, 24V Class I, Division 2 charge controller and battery disconnect are contained within a NEMA 4X remote enclosure and must be installed within a Class I, Division 2 environment. A 20' photovoltaic cable between the enclosure and light fixture allows for easy mounting of the panel and control box.

This solar-powered LED strobe light is constructed of cast aluminum with a polyester powder coated finish. The IP67-rated unit comes with a T3C temperature rating. Designed for extreme work sites, the LED strobe lamp is UL tested to withstand 1,490 lbs.

[Click Photo to Enlarge](#)

**Wireless Remote/Signal Receiver:** The EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 is equipped with an explosion proof wireless remote and wireless signal receiver for remote On/Off functionality. To activate the LED strobe light, operators press a black push button on the wireless remote, which transmits a signal to the wireless receiver and triggers a dry contact relay. This cutting-edge feature enables freedom of movement, increased safety and flexibility at the work site.

**LED Benefits:** Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. Solid state LED lighting is also safer for the environment as LEDs are 100% recyclable. And recycling simultaneously reduces operating costs by eliminating the need for the expensive special disposal services required with traditional gas burning and arc type lamps.

**Power/Wiring:** This EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 is powered by four 12V AC 18aH sealed lead acid batteries that are recharged by the solar panel. These rechargeable batteries provide a continuous supply of steady, reliable power. The lead acid battery pack is contained within the solar panel, not the light. This fixture ships with 80 feet of 10/2 SOOW cord that connects the explosion proof strobe light to the solar panel. Custom lengths are available upon request. Please contact us for special requirements.

Charging time for the battery bank is 5 hours when exposed to direct sunlight. As with all solar powered equipment, charging time is affected by the amount of available ambient light. Indirect sunlight and low ambient light levels, such as on cloudy days, will extend the charge time.

**Mounting:** The EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1 features an inverted pendant mount for compatible surfaces, walls or ceilings. This mounting configuration ensures maximum visibility of the explosion proof LED strobe fixture.

**NOTE:** *Larson Electronics has further upgraded the options available with this light. We expect the light to be mounted separately from the panel. This means the solar panel can be mounted in direct sunlight (not in the hazardous area) while the light is mounted in a hazardous area workspace. Standard installation for explosion proof lighting, including threaded rigid pipe to the LED light fixture and appropriate seal-offs, etc. are required.*

**Suggested Applications:** Paint spray booths, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, gas processing plants, chemical manufacturing, waste treatment plants, remote locations and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.



---

## Frequently Asked Questions (FAQ)



**EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1**

**Product ID: 223941**

**Harmonized System (HS) Code:** 9405.41.84.10

**Export Control Classification Number (ECCN):** EAR99

**Options:**

**EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1-Light Color-Light Mount**

**Example:** EPSLED-80-SOL-80C-C1D2-20C-WR-MOD1-RED-CLG

| Light Color |      |
|-------------|------|
| RED         | -RED |
| GREEN       | -GRN |
| BLUE        | -BLU |
| AMBER       | -AMB |
| WHITE       | -WHT |

| Light Mount      |          |
|------------------|----------|
| CEILING          | -CLG     |
| WALL             | -WLM     |
| PENDANT          | -PND     |
| 25°<br>STANCHION | -STNCH25 |

Links (Click on the below items to view):

- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)