Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPFDS-80A-3P-3X80A.600V-FA

80A Explosion Proof Fused Disconnect - 600V Rated - Fast Acting Fuse - (3) 80A Fuses (2) NPT Hubs

Product ID: 224039

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPFDS-80A-3P-3X80A.600V-FA Explosion Proof Disconnect Switch/Breaker

Unit Type: Explosion Proof Fused Disconnect
Dimensions: 12" x 18" x 8"
Weight: 130 lbs
Rated Voltage: 600V AC
Configuration: 3-Pole
Amps: 80A (Maximum)
Fuses: Included
Fuse Type: Fast Acting Fuse
Fuse Qty: (3) 80A 3P [600V]
Materials: Copper-free Aluminum
Hardware Materials: Stainless Steel
Finish: Aluminum Lacquer Paint Finish
Mounting: Wall/Surface Mount
Wire Size: #14-2/0
Hub Qty: 2
Hub Sizes/Locations: (1) 2" NPT @ Top, (1) 0.5" NPT @ Bottom
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Features/Ratings

Class I, Division 1&2 Groups B,C,D
Class I, Zones 1&2 Groups IIB+ H2,IIA
Class II Division 1&2 Groups E,F,G
Class III
NEMA 3,4,4X,7(B,C,D),9(E,F,G)
CENELEC/ATEX/IEC Ex
Ex d IIB + H2 T5 or T6
Ex tD A21 IP66

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The Larson Electronics EPFDS-80A-3P-3X80A.600V-FA Explosion Proof Disconnect Switch is designed for use in Class I, II and III environments. Equipped with fast-acting fuses, this 3-pole unit contains three 80-amp

600V fuses and two NPT hubs. The explosion proof disconnect offers instant response to surges and electrical spikes, making it ideal for resistive circuits in flammable work sites.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES

The EPFDS-80A-3P-3X80A.600V-FA ensures active protection of electrical systems in combustible facilities. Rated at 600V AC, this fused unit contains three 80-amp 3-pole 600V fast-acting fuses. These explosion proof disconnects are sensitive to electrical pulses, which provide peace of mind for operators working with sensitive equipment, such as laptops and electronics. Choosing between a time-delay fuse and a fast-acting fuse highly depends on the type of system or device requiring protection, as both protective methods are effective (one is not superior over the other).

Operators are provided access to a copper-free aluminum handle, which can be padlocked in the ON or OFF position. The ATEX-rated explosion proof disconnect is constructed of copper-free aluminum, with stainless steel hardware. For durability, the unit is finished in aluminum lacquer paint and features a NEMA-rated enclosure.

Hubs: For completing electrical connections, two NPT hubs are provided on the enclosure. One 2" NPT hub at the top; and one 0.5" NPT hub at the bottom are available during installation.

Mounting: Operators can mount the explosion proof disconnect on walls or flat surfaces.

Applications: Sensitive equipment, electronics, LED lighting systems, computers, petroleum refineries, chemical and petrochemical plants, storage areas, and other processing facilities where hazardous substances are handled or stored.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

EPFDS-80A-3P-3X80A.600V-FA

Product ID: 224039

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**