

MGP-480V.3P-800A-2x400A.CL-2X60A.CL-1X200A.CL-N3R

Temporary Power Distribution - 480V, 3PH - 800A MCB - Cam-lock Input/Output - N3R

Product ID: 235837

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MGP-480V.3P-800A-2x400A.CL-2X60A.CL-1X200A.CL-N3R -Temporary Power Distribution

Line In: (2 Sets) 45°, 400A 600V Rated 16 Series Male Cam-locks [Brown, Orange, Yellow, Green]

Voltage: 480V AC, 3PH

Panel: 800A 480V 3PH MCB N3R

Breakers: (1) 200A [480V], (2) 60A [480V]

Line Out: (2 Sets) 45°, 150A 600V Rated 15 Series Female Cam-locks [Brown, Orange, Yellow, Green], (1 Set) 45°, 400A 600V Rated 16 Series Female Cam-locks [Brown, Orange, Yellow, Green]

Protection: N3R Flip Covers (Cam-locks), Circuit Breakers

Form Factor: Powder Coated Steel Dolly Cart w/ (4) Casters - Front (2) Casters Swivel

Dimensions: W-40" X D-40" X H-48"

Weight: 350 lbs

Max Primary OCP: 800A @ 480V

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Ratings

UL 1640 Portable Power-Distribution Equipment

NEMA 3R Indoor or Outdoor Use

Made in the USA

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The Larson Electronics MGP-480V.3P-800A-2x400A.CL-2X60A.CL-

1X200A.CL-N3R temporary power distribution system provides operators with a primary and secondary three-phase voltage of 480V AC. This unit provides operators the ability to safely tap into and distribute 480V AC power from a variety of sources including generators and direct grid power.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Portable Power Distribution Purpose and Use: The MGP-480V.3P-800A-2x400A.CL-2X60A.CL-1X200A.CL-N3R portable power distribution system gives operators the ability to power their 480 volt equipment from a single system. On the primary side, operators connect 480V AC using two sets of male cam-locks (brown, orange, yellow and green). On the secondary side, operators are provided access to two sets of 150-amp and one set of 400-amp female cam-locks for line-out devices. All cam-locks are equipped with NEMA 3R protective flip covers.

Operation: One set of 45°, 400-amp 600V rated 16 series male cam-locks (brown, orange, yellow and green) brings three-phase 480V power to the NEMA 3R 800-amp, three-phase 480V main circuit breaker panel. The panel contains one, 200-amp 480V and two, 60-amp 480V breakers. Line-out from the main circuit breaker panel is provided by two sets of 45°, 150-amp 600V rated 15 series female cam-locks (brown, orange, yellow and green) and one set of 45°, 400-amp 600V rated 16 series female cam-locks (brown, orange, yellow and green).



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

Protective Construction: The portable panel and load center/distribution assembly is mounted to a powder coated steel, dolly cart style frame, resulting in an extremely stable, durable, and mobile power distribution platform. Four casters (front two casters swivel) and a dolly cart style mounting platform provides easier substation mobility, and a center point lift point allows easy lifting with cable or chain hooks.

This temporary power distribution solution can be modified to meet the needs of job-site receptacle requirements. Units are available up to 150 KVA,] and can be equipped with skids or trailer mounted.

Certification: Larson Electronics is a UL 1640 panel shop and certified to build portable power distribution systems. All units are built in accordance to NFPA 70 (National Electric Code) and certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.

~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is NEMA 3R rated and ideal for indoor/outdoor use and applications including but not limited to; construction sites, plant maintenance, plant turnarounds, shows, exhibits and shipyard operations.

Larson Electronics is a manufacturer and as such can build portable transformer systems to your specifications. Although we carry several models of power distribution transformers, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)









MGP-480V.3P-800A-2x400A.CL-2X60A.CL-1X200A.CL-N3R
Product ID: 235837

Harmonized System (HS) Code: 8504.21.0040
Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [ANSI Certificate 1](#)
- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [Catalog Page - Product Series](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 5, Misc](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)