Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ATEX-HLP-125A-4P5W-240.415V

125A Explosion Proof Plug - 690V Rated - ATEX/IECEx -Z1/Z2, Z21/Z22 - Red

Product ID: 236036

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-HLP-125A-4P5W-240.415V Flameproof Plug

Listing: International, European Union
Unit Type: Explosion Proof Plug
Dimensions: 11.73" L x 4.76" OD
Weight: 2.86 lbs
Voltage Rating: 690V AC, 50/60Hz
Amps: 125A
Configuration: 4-pole, 5-wire
Mate (Flameproof Outlet): ATEX-HLO-125A-SW-4P5W-240.415V
Ambient Operating Temp: -40°C - +45°C
Materials: Polyamide
Mount: -
Cable Entry: 2.16" OD (55mm)
Connection: Terminals (35mm2)
Color: Red

Ratings/Approvals

ATEX/IECEx Rated
Certified for Zone 1, Zone 2
Certified for Zone 21, Zone 22
Ex 2GD Ex de C T5 Gb
Ex tD A21 T95 Ta45
IP66

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The Larson Electronics ATEX-HLP-125A-4P5W-240.415V Explosion Proof Plug is recommended for use in ATEX/IECEx flammable work sites. This 125-amp rated accessory comes in a 4-pole, 5-wire configuration. Constructed of polyamide, the flameproof plug features IP66 rated protection.

The ATEX-HLP-125A-4P5W-240.415V is designed for secure electrical connections in hazardous locations. This 4-pole, 5-wire plug is rated at 125 amps and up to 690V AC. Equipped with terminals for connections, the IP66 rated device features polyamide

construction. Specially designed color coding and pin configuration reduces the possibility of making incorrect power connections.
This flameproof accessory can be used in ATEX/IECEx rated, Zone 1/Zone 2 and Zone 21/Zone 22 sites. Designed to mate with the ATEX-HLO-125A-SW-4P5W-240.415V flameproof outlet, the plug accepts 2.16" OD cable entries.
Applications: Manufacturing, industrial, warehouse, lighting, motor-generator sets, compressors, wet areas or locations where combustible dusts, fibers or flying are present or where explosive gases or vapors may be present.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

ATEX-HLP-125A-4P5W-240.415V

Product ID: 236036

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**