

IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1

**Non-Fused Disconnect Switch - Isolator Switch - Three Pole - 125A - 415V Rated - (1) Open
Auxillary Contact - Carbon Steel**

Product ID: 236406

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 Weatherproof Non-Fused Disconnect / Isolator Switch

Unit Type: Weatherproof Non-Fused Disconnect / Isolator Switch

Dimensions: -

Weight: -

Rated Voltage: Max to 400 V

Rated Current: Max to 125 Amps

Utilization Category: AC-23, AC-3

Rated Insulation Voltage (Ui): 800 V

Rated Withstand Impulse Voltage (Uimp): 6 kV

Rated Short-Time Withstand Current (Icw): 10 kA

Rated Short-Time Marking Capacity (Icm): 17 kA

Short-Circuit Protection of Fuse: 500 V / 125 A

Protection Characteristic of Fuse: gG(Conformity to IEC/EN60269-1)

Ambient Temperature: -55°C to + 55°C

Selector Switch: (1) 3-Pole, 2-Position Selector Switch Labeled "ON", "OFF"

Selector Switch Safety: Lockout/Tag Out Lock

Auxillary Contact: (1) Normally Open

Terminals: (1) 50/70 mm Terminal w/ Internal Wiring

Materials: Carbon Steel - Powder Coated - Gray

Cable Entry: (2) Cable Entries - Each w/ M63 Plastic Cable Glands

Mount: Surface

Cable Diameter: Can Accomodate 1.06" to 1.89" (27-48 mm) Cable

Ratings/Details:

IP66

Carbon Steel Construction

Powder Coated

WF2 Corrosion-Proof Mark

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 from Larson Electronics is a Weatherproof Non-Fused Disconnect / Isolator Switch that is rated for 415 V, 50 Hz and is also rated IP66 for use in areas where exposure to dust or powerful water jets is possible. This weatherproof non-fused disconnect / isolator switch prevents all ingress of dust and immune to water sprayed from powerful jets. The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 features a two position selector switch and one normally open auxillary contact. The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 is constructed from carbon steel and is powder coated gray for durability and corrosion resistance.

The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 is a durable weatherproof non-fused disconnect / isolator switch designed for areas that encounter dusty or wet conditions. Featuring an voltage rating of 415 V, 50 Hz, this unit features one normally open auxillary contact in addition to the two-position selector switch. This isolator switch is equipped with two M63 moulded plastic cable glands with a diameter of 27-48 mm.

The two position selector switch on the IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 is labeled "ON" and "OFF". The switch is key lockable for lock out or tag out.

Voltage: The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 has a voltage rating of 415 V, 50 Hz.

Wiring/Mounting: The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 features two cable entries. Each entry is equipped with a M40 plastic cable gland and can accommodate cables with a diameter of between 1.06" to 1.89" (27-48 mm). The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 has one 50/70 mm terminal with internal wiring on the inside.

Materials: The IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1 is built from carbon steel and is finished in a gray powder coating for durability and corrosion resistance.

Applications: Situations requiring a weatherproof non-fused disconnect / isolator switch.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

IND-WPCS-CS-NFDS-415V-3P-125A-AUX.1-R1

Product ID: 236406

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)