Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-LI-EMG-48-2X50LED

100W Low Profile Explosion Proof LED Light - 2x4 Lay-In Mount - Class 1 Div 1 - Paint Spray Booth - Emergency Battery Backup

Product ID: 236514

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-LI-EMG-48-2X50LED HAZLOC Lay-In Mount Light w/ Emergency Battery Backup	Ratings/Approvals
Listing: United States - Canada	Listed for United States and Canada
Lamp Type: Cree LED	Class I, Divisions 1 & 2, Groups C and D
Dimensions: 47.5"L x 23.5"W x 8"D	Class II, Divisions 1 & 2, Groups E,F,G
Weight: 75 lb	Class III, Divisions 1 & 2
Voltage: 100-277 Volts AC, 50/60Hz or 11-25 Volts AC/DC	Certified to UL 844 Ed. 13
Total Watts: 100 W	Certified to UL 1598
Total Lumens: 14,000	Certified to C22.2 No. 137 Rev 2009
Luminous Efficacy: 140 Lm/W	Certified to C22.2 No. 250.0
Lamp Life: 60,000+ Hours	Certified to C22.2 No. 30-M-1986 Rev 2012
Color Temp: 5600 K, 4500 K, 3000 K	T5 Temperature Rating
Color Rendering Index: >75 CRI	Paint Spray Booth Approved
Beam Angle: 60° or 125°	IEC 60529 Tested
Lighting Configuration: Flood Pattern	IP67 Rated Waterproof
Power Efficiency: >95%	LEL Approved
Power Factor: 0.992	Multiple Driver Banks
Ambient Operating Temp Range: -50°C to +65°C	80% Lumen Retention after 60,000 Hours
Operating Temp Rating: T5	Factory Sealed Light Fixture
Emergency Runtime: 90 Minutes	3.5kV Surge Protection (NTC Circuit)
Emergency Power Draw: 15 Watts	Suitable for Locations with Paint Deposits
Emergency Lumen Output: 2100	90 Minute Emergency Runtime
Housing Material: Copper Free Cast Aluminum	Made in the USA
Housing Finish: Epoxy Powder Coated - Grey	**Special Orders- Requirements**
Lens Material: Hardened Borosilicate Glass	Contact us for special requirements

Gasket Material: Silicone

Mounting: Recessed Lay-In Mounting

Wiring Hub: 3/4" NPT

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in Texas

The HAL-LI-EMG-48-2X50LED from Larson Electronics is a Hazardous Area LED Lay-In Light Fixture that is designed to provide operators with a powerful and energy efficient alternative to traditional hazardous location luminaries. This LED lay-in mount fixture is ETL listed Class I Divisions 1 & 2, Class II Divisions 1 & 2, and is approved for use within paint spray booths. Cree LED technology and compact design makes this lamp an excellent replacement upgrade option for paint booths and hazardous locations where flammable chemical/petrochemical vapors are present. The HAL-LI-EMG-48-2X50LED features an emergency battery backup. In emergency mode, the LED lamp will operate at 15 watts of power and continue to operate at a lower light intensity level for 90 minutes via a battery.

******PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE******

The HAL-LI-EMG-48-2X50LED Explosion Proof fixture is a 2x4 Class I Divisions 1 & 2 hazardous location lay-in LED light fixture and is ideal for use in paint spray booths and hazardous environments where space for lighting fixtures is limited. This fixture is T5 temperature rated and is a fully integrated LED unit. The LED assembly is protected by a front access aluminum framed, hinged, 3/16" thick polycarbonate door that provides direct front access to the internal components. The lamp housing is designed for recessed mounting, and is constructed of non-sparking aluminum coated with a powder coated white finish.

This Class I Divisions 1 & 2, Class II Divisions 1 & 2 explosion proof light fixture provides 14,000 lumens of high quality light while drawing only 100 watts. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. Special heat dissipating design in conjunction with LED technology helps this fixture to achieve an excellent 60,000 hour rated lifespan with 80% lumen retention. Light weight and a low profile make this unit an attractive alternative to larger and heavier older fixtures and requires less hardware to install.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

The integrated LED assembly in this unit features multiple LED drivers which helps to increase the operational life of the fixture. With traditional LED lights, in the event an LED array or driver fails, the entire fixture no longer illuminates. This new series of LED lamps contains twenty-four individual LED boards configured in a series of banks. Each bank contains two LED boards with an individual driver. In the event of a driver failure, only one bank of LEDs will be effected while the other banks will continue to operate. In the event that of an LED failure, the mating LED will continue to operate.

This light is universal voltage capable and can be operated with 100-277 V AC, 50/60 Hz without any need for a special ballast. The aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LED luminaries. The LED lamp produces 14,000 lumens with a color temperature of 5000 K, 4000 K, or 3000 K and a color rendering index of 75 which produces colors and details much more accurately than high pressure sodium or mercury vapor luminaries.

Emergency Battery Backup: The emergency LED light works, mounts and is wired like our HAL-LI-48-2X50LED LED light fixtures. The main difference is that we add a battery backup unit that adds emergency light functionality to the fixture. This emergency LED light will run at the standard UL suggested 90 minutes after power is lost while drawing 15 watts of power and operating at a lower light intensity. The light recharges the battery once electrical power is restored. Standard configuration includes a single emergency battery backup that is automatically recharged and kept in a ready state.

Mounting: This fixture features a troffer lay-in mounting design housing that measures only 8" in thickness and 2` wide by 4` long, resulting in a very low profile fixture that is deal for flush mounting in ceilings that utilize standard sized ceiling tiles. This fixture is designed for recessed mounting and requires a mounting hole to be made in booth panels capable of accommodating the fixture housing in order to provide the maximum amount of space in paint spray booth enclosures. Once mounted, this fixture`s door frame will extend 3/8" into the spray booth.

Applications: Paint spray booths and enclosed spaces where flammable chemical/petrochemical vapors are present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-LI-EMG-48-2X50LED

Product ID: 236514

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

HAL-LI-EMG-48-2X50LED-Voltage-Color Temp-Beam Config

Example: HAL-LI-EMG-48-2X50LED-1227-50K-60B

Voltage	
120-277V AC	-1227
11-25V AC/DC	-1224

Color Temp	
5000K	-50K
4000K	-40K
3000K	-30K

Beam Config	
60°	-60B
125°	-125B
140°	-140B

Links (Click on the below items to view):

- **HigResPic1**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**