

IND-PB20-MS

Non-Metallic Weatherproof Momentary Switch - Single Push Button - Outdoor Rated

Product ID: 236880

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: IND-PB20-MS

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-PB20-MS Non-Metallic Momentary Switch

Type: Momentary Switch

Dimensions: 3.95"W x 4.21"H x 4.16"D

Voltage Rating: 690V AC, 20A, 50-60Hz

Horsepower Rating: 2 HP

Ambient Operating Temp Range: -50°C to +60°C

UV Protection: f1

Housing Materials: Non-Metallic Glass Reinforced Impact Resistant Antistatic Material

Housing Color: Black

Button Color: Green

Flame Retardant Rating: V-0

Gasket Material: Silicone

Mounting: Din Rail Mount

Wiring Hub: (1) 1/2" NPT Hub

Ratings/Approvals

Weatherproof

Outdoor Rated

NEMA 3, 4, 4X, 12, 13

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The IND-PB20-MS from Larson Electronics is a non-metallic momentary switch that is weatherproof and outdoor rated. This single push button switch has a din rail mount design and is constructed of an impact resistant glass reinforced non-metallic material

with silicone gaskets. The IND-PB20-MS has a black housing color with a green button and boasts a compact size for convenient mounting and use.

This weatherproof and outdoor rated non-metallic momentary switch is designed for din rail mounting. The IND-PB20-MS has contact blocks that are rated for voltages up to 690 V AC, is capable of handling 20 amps for switching duty and has a horsepower rating of 2 HP. This switch also features silver alloy contacts with gold flashing. This non-metallic momentary switch has an ambient operating temperature of -50°C to +60°C and can be used in conjunction with motor starters or contactors for remote operation of motors.

The IND-PB20-MS C1D2 non-metallic single push button momentary switch features a non-metallic housing that is constructed of a PA6 glass reinforced antistatic material that is impact resistant, f1 UV resistant and has a flame retardant rating of V-0. The housing on this switch is black and the button itself is green which offers plenty of contrast for easy visibility of the button. This switch has a 1/2" NPT hub and features silicone gasketing throughout.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Image: IND-PB20-MS



Image: IND-PB20-MS



Image: IND-PB20-MS



Image: IND-PB20-MS



Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/236880.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/236880.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/236880.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/236880.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/236880.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)