

EXC-100-TW-4.4-100A-DS100M-DS60F

100' 4/4 Type-W Twist Lock Extension Power Cord - DS100 to DS60 - 480V - 100 Amp Rated Continual

Product ID: 239631

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXC-100-TW-4.4-100A-DS100M-DS60F - 100' 4/4 Type-W 100 A Extension Cord

Male Cord Cap: DS100 480 V AC 100 A 3P+G Pin/Sleeve Plug with Handle

Female Cord Cap: DS60 480 V AC 100 A 3P+G Pin & Sleeve Receptacle with Handle

Voltage Rating: 480 V

Max Amp Rating: 100 A

Cable Type: 4/4 Type-W

Cable Length: 100'

Weight 160 lb

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The EXC-100-TW-4.4-100A-DS100M-DS60F from Larson Electronics is a 100 Foot 4/4 Type-W Twist Lock Extension Power Cord that is designed for 480 V 3-phase indoor and outdoor applications. This rugged extension cord is constructed of 4-gauge 4-conductor wire, equipped with a DS100 480 V AC 100 A 3P+G Pin/Sleeve Plug with Handle on the primary side and a DS60 480 V AC 100 A 3P+G Pin & Sleeve Receptacle with Handle and allows operators to extend power to equipment when stationary outlets are not readily available.

The EXC-100-TW-4.4-100A-DS100M-DS60F twist lock extension cord provides a safe and effective way for operators to extend 480 V and power a variety of

devices for plant maintenance, power generators, transformers, power distribution substations, construction and other temporary applications. 100 feet of chemical and abrasion resistant flexible Type-W cord 4/4 Type-W cable is terminated in male DS100 480 V AC 100 A 3P+G Pin/Sleeve Plug with Handle. The opposite end is terminated in a DS60 480 V AC 100 A 3P+G Pin & Sleeve Receptacle with Handle.

****Please note, this extension cord is rated for a maximum of 100-amps of continual service. Devices plugged into this cord must operate at 100 amps or below on 480 V.****

Applications: This twist lock extension cord is ideal for indoor or outdoor use and applications including but not limited to, generators, construction sites, plant maintenance, plant turnarounds, shows, exhibits, industrial equipment, uninterruptible power supplies (UPS battery backups), stage equipment, and shipyard operations. These industrial extension cords are popularly used in applications where external power sources are often necessary. We also offer class rated extension cords for use within explosion proof and hazardous location environments.

Larson Electronics is a manufacturer and as such can build extension cords and portable transformer systems to your specifications. Although we carry several models of power distribution transformers, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)

EXC-100-TW-4.4-100A-DS100M-DS60F

Product ID: 239631

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)