Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXHL-SL-4-LE1-X15-25C-1227-E2E

48W Explosion Proof LED String Light - (4) Lamps - C1D1/C2D1 - 120-277V AC - Daisy Chain - Mounting Holes

Product ID: 240626

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXHL-SL-4-LE1-X15-25C-1227-E2E Explosion Proof LED String Light

Listing: United States, Canada, Europe, Asia
Lamp Technology: LED
Lamp Qty: (4)
Single-Lamp Dimensions: 6"L x 6.25"W x 7.75"H
Weight: -
Voltage: 120-277V AC
Total Watts: 48W
Single-lamp Watts: 12W
Total Lumens: 5280 lms
Single-lamp Lumens: 1320 lms
Luminous Efficacy: 110 Lm/W
LED Life Expectancy: 50,000+ Hours
LED Light Color: 6000K - White
Color Rendering Index: -
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Lighting Configuration: 10° Spot or 40° Flood
Spot Beam: 800`L x 140`W

Ratings/Approvals

Class I, Divisions 1 & 2, Groups B, C, D
Class I, Zones 1 & 2, Groups IIB+H2, IIA
Class II, Divisions 1 & 2, Groups E, F ,G
Class III
NEMA Type 3, 4, 4X, 7 (B,C,D), 9 (E,F,G)
ATEX Ex II 2 G / D
IECEx db IIC Gb
IECEx tb IIC Db IP66
Daisy Chain

Flood Beam: 300`L x 225`W
Ambient Operating Temp Range: -40°C to +60°C
Housing Material: Aluminum
Light Housing Color: Powder Coated - Grey
Lens Material: Polycarbonate

Mounting: (2) Mounting Holes per Lamp

Wiring: 80' SOOW Cord - 25' Line-in SOOW Cord, 15' SOOW Cord Between Each Lamp (Total 45'), 10' SOOW Cord Output to Receptacle
Cord Cap: 5-15P (125V), 5-20P (125V) or 6-20P (250V)

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EXHL-SL-4-LE1-X15-25C-1227-E2E

Product ID: 240626

Export Control Classification Number (ECCN): EAR99

Options:

EXHL-SL-4-LE1-X15-25C-1227-E2E-Beam Config-Cord Cap

Example: EXHL-SL-4-LE1-X15-25C-1227-E2E-SP-1523

Beam Config	
SPOT	-SP
FLOOD	-FL

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Links (Click on the below items to view):

- **HigResPic1**
- **Video1**
- **Video2**
- **Video3**
- **Video4**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**