Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## HULBLT-18W-LED-R2-30

# 18 Watt Handheld LED Spotlight for Industrial Lighting -Articulating Head- Polycarbonate Handle IP65

**Product ID: 242840**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**HULBLT-18W-LED-R2-30**

**Lamp Type: CREE LED**
**Dimensions:** 4.75"L x 2.3" Diameter
**Weight:** 2 lbs.
**Voltage:** Universal- 100-277VAC, 50/60Hz
**Total Watts:** 18W

**Total Lumens:** 1,530

**Luminous Efficacy:** 85 Lm/W

**LED Lamp Life Expectancy:** 50,000+
**Color Temp:**5000K
**Color Rendering Index:** 85
**Beam Type:** 25° Spot or 60° Flood
**Power Efficiency:** >90%

**Power Factor:** 0.9

**Operating Temperature Range:** -40°C to +85°C
**Typical Case Temperature:** -20°C above ambient temp.
**Housing Material:** Aluminum
**Housing Color:** Black, Bronze or White
**Lens Material:** Polycarbonate

**Mounting:** Handheld use

**Wiring:** 30` 16/3 SOOW Continuous Cable

**Ratings**

NRTL Listed for use in United States and Canada.
Waterproof / Vapor proof
IP65 Ingress Protection
Impact/Vibration Resistant Construction
50,000 Hour LED life

**Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187

**Cord Cap:** 5-15, 6-15, 5-20, 6-20, L5-15, L6-15, L5-20, L6-20, BS1363, Schuko, or Pigtail **E-mail:** sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**HULBLT-18W-LED-R2-30**

**Product ID: 242840**

**Harmonized System (HS) Code:** 9405.41.84.10

**Export Control Classification Number (ECCN):** EAR99

**Options:**

**HULBLT-18W-LED-R2-30-Finish-Beam Config-Cord Cap**

**Example: HULBLT-18W-LED-R2-30-BLK-SP-5.15**

| Finish | |
|---|---|
| BLACK | -BLK |
| BRONZE | -BRZ |
| WHITE | -WHT |

| Beam Config | |
|---|---|
| 25° SPOT | -SP |
| 60° FLOOD | -FL |

| Cord Cap | |
|---|---|
| 5-15 STRAIGHT | -5.15 |
| 6-15 STRAIGHT | -6.15 |
| L5-15 TWIST | -L5.15 |
| L6-15 TWIST | -L6.15 |
| UK BS1363 | -BS1363 |
| INTL SCHUKO | -Schuko |
| PIGTAIL | -Pigtail |

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**