Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-HB-80W-RD2-LED-TRC-SDPM

80W Explosion Proof High Bay AC LED Fixture - C1D1 - C2D1 - Group B + ATEX/IECEX - DIN 32676 Clamp Mount

Product ID: 243392

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLX-HB-80W-RD2-LED-TRC-SDPM Explosion Proof High Bay AC LED

Lamp Type: AC LED
Listing: United States, Canada, Europe
Dimensions: 4.24"H x 9.21"OD
Weight: 12.1 lbs
Voltage: 120V AC, 208V AC, 220V AC, 240V AC, 277V AC
Total Watts: 80W
Lumens: 8,400 (5000K) or 7,600 (3000K)
Luminous Efficacy: 105 Lm/W (5000K)or 95 Lm/W (3000K)
Lamp Life: 60,000+ Hours
Color Temp: 5000K cool white, 3000K warm white
Color Rendering Index: >70 CRI
Beam Angle: 110°
Lighting Configuration: Wide Flood Beam
Power Efficiency: >85%
Power Factor: >0.9
Amperage: 0.66A@120V AC, 0.38A@208V AC, 0.36A@220V AC, 0.33A@240V AC, 0.28A@277V AC
Ambient Operating Temp Range: -60°C to +100°C
Operating Temp Rating: T6
Housing Material: Aluminum Alloy
Lens Material: Tempered Glass
Mounting: DIN Clamp Mount 20, 25, 50, 65 or 80
Wiring: 10` SOOW Cord w/ Flying Leads

Ratings/Approvals

Class I, Division 1, Groups B, C, D
Class I, Division 2, Groups A, B, C, D
Class II, Divisions 1 & 2, Groups E, F, G
Class III, Divisions 1 & 2
Class I, Zone 1 & 2, AEx d IIB+H2
Class I, Zone 21 & 22, AEx td IIC
IEC Ex d IIB+H2 T5...T4 Gb
IEC Ex tb IIIC T110° Db
ATEX II 2G Ex d IIB+H2 T5...T4 Gb
ATEX II 2D Ex tb IIIC T110° Db
IP67 Waterproof
NEMA 6/6P
Certified to UL 844
Certified to UL 1598
Certified to UL 60079
Certified to CSA C22.2 No. 137-M1981
Certified to IEC 60079 & EN 60079
Compatible With Lutron C.L. Series Dimmers
Factory Sealed Light Fixture
ABS Type Approval

Special Orders- Requirements

Contact us for special requirements

The EPLX-HB-80W-RD2-LED-TRC-SDPM Explosion Proof High Bay AC LED light fixture from Larson Electronics is a compact powerhouse built to withstand demanding conditions. This LED high bay light features state-of-the-art AC LEDs paired with specially designed heat sinks for improved efficiency, thermal management, and durability, and includes a DIN 32676 clamp mount. Available in 5000K cool white and 3000K warm white options, a 110° flood beam provides crisp, and bright illumination with broad coverage. This heavy duty Class I Division 1 and Class II Division 1 LED lamp is suitable for oil refineries, petrochemical plants, painting facilities, offshore rigs, marinas, docks, warehouses, garages, and commercial buildings.

Light Features: The 80 watt EPLX-HB-80W-RD2-LED-TRC-SDPM High Bay AC LED light fixture delivers brilliant illumination and robust performance in a convenient space-saving form. A 110° wide flood beam provides crisp, bright light with broad coverage. The include single pin DIN fitting is T304 stainless steel clamp. DIN mount options include 20, 25, 50, 65 and 80.

This explosion proof high bay light fixture utilizes AC LEDs paired with a heavy-duty housing and an advanced heat sink that allows for improved efficiency and thermal performance. By eliminating the drivers associated with DC LEDs, space is freed up for more connective surface, accelerating heat dissipation and increasing durability. The specially designed heat sink allows for greater surface area contact with the air as well as a stronger airflow rate. Because this fixture is created for maximum thermal efficiency, it is ideal for applications in which the ambient operating temperature falls into extreme ranges, especially high heat applications. Furthermore, fewer sub-components also means fewer chances for secondary component failure. The simplified circuit system used within AC LEDs creates greater stability and enhances luminaire lifespan.

The EPLX-HB-80W-RD2-LED-TRC-SDPM is designed to endure the daily wear and tear inflicted by harsh outdoor conditions such as sun, wind, rain, snow and sleet. as well as to withstand the corrosive effects of saltwater spray in marine environments. Durable IP67 rated construction provides protection against the ingress of dust, dirt and humidity and allows this light to withstand the corrosive elements found within marine environments including saltwater spray. The copper free, non-sparking die-cast aluminum alloy housing and tempered glass lens are vibration and impact resistant, and the housing is treated with a coating that rejects dust and buildup.

The EPLX-HB-80W-RD2-LED-TRC-SDPM is listed for use in the United States and Canada and carries IEC Ex and ATEX certifications.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. Solid state LED lighting is also safer for the environment as LEDs are 100% recyclable. And recycling simultaneously reduces operating costs by eliminating the need for the expensive special disposal services required with traditional gas burning and arc type lamps.

Dimming: The EPLX-HB-80W-RD3-LED-TRC-SDPM can be wired with a dimmer

switch for dimming capabilities. This gives operators the ability to manually adjust the brightness of the LED lamp quickly and easily. When using an electronic dimmer switche, the EPLX-HB-80W-RD3-LED-TRC-SDPM will dim from 0% up to 100% via the user provided dimming switch. This explosion proof LED light fixture is compatible with Lutron C.L. series dimmer switches. Compatible dimmers in that series include the following: Diva® C•L® dimmer, Ariadni®/Toggler® C•L® dimmer, Luméa® C•L® dimmer, Maestro® C•L® dimmer and Skylark® C•L® Dimmer.

PLEASE NOTE THAT ANY DIMMER INSTALLED ON THIS FIXTURE MUST BE LOCATED OUTSIDE OF THE HAZARDOUS AREA

Mounting: The EPLX-HB-80W-RD2-LED-SDPM high bay fixture comes with a DIN 32676 sanitary clamp mount. Clamp sizes include: 20, 25, 50, 65 and 80. Please choose a size when ordering.

Power/Wiring: The EPLX-HB-80W-RD2-LED-TRC is available in the following voltages: 120V AC, 208V AC, 220V AC, 240V AC, and 277V AC.

Applications: Industrial grade construction, compact design, and versatile positioning options make this Class I Division 1 Groups B, C, & D, Class II Divsion 1 Groups E, F & G fixture and ideal lighting solution for oil refineries, petrochemical plants, painting facilities, offshore rigs, marinas, docks, warehouses, garages, and commercial buildings.

High Quality Features

1. Each unit dialectically tested.
2. Low power consumption.
3. Instant on/off operation.
4. Fixture constructed of die-cast,corrosion resistant, copper free aluminum alloy.
5. No ballast box. No ballast to replace.
6. Superior color rendering compared to HPS, LPS, MH.
7. Retains 80% lumen output after 60,000 operating hours.
8.Exterior coating rejects dust and buildup.
9. Available in voltages: 120V AC, 208V AC, 220V AC, 240V AC, and 277V AC
10. Highly efficient thermal dissipation.
11. Fewer secondary components adds durability and longevity
12. Lighter weight, slimmer, brighter alternative to fluorescent configurations.
13. Explosion Proof / Flame Proof US, CAN, ATEX, IECEx; Rated for use in the United States and Canada.
14. Can be wired with a dimmer switch.
15. Compatible with Lutron C.L. series dimming switches.

Superior LED Benefits

1. 60,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


LUMINAIRE FOR HAZARDOUS LOCATIONS
Class I, Div. 1, Groups B, C, D
Class II, Div. 1, Groups E, F, G
Hz : 50/60 Hz
V : 120 Vac
W : 100 W
A : 0.88 A



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-HB-80W-RD2-LED-TRC-SDPM
Product ID: 243392

Warranty: 60 Months

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
EPLX-HB-80W-RD2-LED-TRC-SDPM-Voltage-Color Temp-Size
Example: EPLX-HB-80W-RD2-LED-TRC-SDPM-120V-50K-DN20

Voltage	
120V	-120V
208V	-208V
220V	-220V
240V	-240V
277V	-277V

Color Temp	
5000K	-50K
3000K	-30K

Size	
DIN 20	-DN20
DIN 25	DN25
DIN 50	DN50
DIN 65	DN65
DIN 80	DN80

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map