Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HLSW-PB20-ES-LCK-M1

Non-Metallic Explosion Proof Emergency Stop Push Button with Lockout Device - Mushroom Head - C1D2 - C2D2 - C3D1&2

Product ID: 257453

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLSW-PB20-ES-LCK-M1 Non-Metallic Mushroom Head Emergency Stop Switch w/ Lockout Device

Type: Mushroom Head Emergency Stop Switch
Dimensions: 3.95"W x 4.21"H x 4.16"D
Voltage Rating: 690V AC 50/60Hz
Amperage Rating: 20A
Horsepower Rating: 2 HP
Ambient Operating Temp Range: -50°C to +60°C
UV Protection: f1
Housing Materials: Non-Metallic Glass Reinforced Impact Resistant Antistatic Material
Housing Color: Black
Button Color: Red
Lockout Device: Yes - Aluminum Lockout Device w/ "E-STOP" Label
Flame Retardant Rating: V-0
Gasket Material: Silicone
Mounting: Din Rail Mount
Wiring Hub: (1) 1/2" NPT Hub or (1) M20 Clearance Hole Hub
Configuration: Pull Release or Twist Release

Ratings/Approvals

Class I, Division 2, Groups A, B, C, D
Class I, Zone 1, AEx de IIC T4/T5/T6 Gb
Class II, Division 2, Groups E, F, G
Class II, Zone 2, Aex tb IIIC T4/T5/T6 Db IP66
Class III, Divisions 1 & 2
II 2 G Ex de IIC T4/T5/T6 Gb
II 2 D Ex tb IIIC T4/T5/T6 Db IP66

NEMA 3, 4, 4X, 12, 13

Aluminum Lockout Device w/ "E-STOP" Label

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The HLSW-PB20-ES-LCK-M1 from Larson Electronics is a non-metallic mushroom head emergency stop push button with lockout device that is

rated for Class I Division 2 Groups A, B, C & D, Class II, Division 2, Groups E, F & G and Class III, Divisions 1 & 2 hazardous environments. This ATEX certified single mushroom head emergency stop push button switch has a din rail mount design and is constructed of an impact resistant glass reinforced non-metallic material with silicone gaskets. The HLSW-PB20-ES-LCK-M1 has a black housing color with a red button and boasts a compact size for convenient mounting and use. The HLSW-PB20-ES-LCK-M1 is equipped with an emergency stop shroud and lockout device. The device is constructed from aluminum and protects the button from being pushed or activated accidentally. The emergency stop shroud is also equipped with a through-hole that allows a lockout pin to be used and a label with the message "E-STOP".

This Class I Division 2 Groups A, B, C & D rated non-metallic mushroom head emergency stop push button switch is designed for din rail mounting. It is ideal for mounting and use in petroleum refineries, chemical plants, petrochemcial plants and other facilities where similar conditions exist. The HLSW-PB20-ES-LCK-M1 has explosion protected contact blocks that are rated for voltages up to 690V AC, is capable of handling 20 amps for switching duty and has a horsepower rating of 2 HP. This switch also features silver alloy contacts with gold flashing. This non-metallic mushroom head emergency stop push button switch has an ambient operating temperature of -50°C to +60°C and can be used in conjunction with motor starters or contactors for remote operation of motors.

The HLSW-PB20-ES-LCK-M1 C1D2 non-metallic single push button mushroom head emergency stop switch features a non-metallic housing that is constructed of a PA6 glass reinforced antistatic material that is impact resistant, f1 UV resistant and has a flame retardant rating of V-0. The housing on this switch is black and the button itself is red which offers plenty of contrast for easy visibility of the button. The HLSW-PB20-ES-LCK-M1 features silicone gasketing throughout. This switch is available in either a 1/2" NPT hub or a M20 clearance hole hub. This switch is also available in a pull release or twist release configuration. Please make your selections when ordering below.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


E-STOP
STOP
LARSON
ELECTRONICS


E-STOP
STOP
A31
LARSON
ELECTRONICS

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364




83mm
3 1/2 inch
104mm
4 1/2 inch
6mm
Ø240

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HLSW-PB20-ES-LCK-M1

Product ID: 257453

Export Control Classification Number (ECCN): EAR99

Options:

HLSW-PB20-ES-LCK-M1-Release-Hub Config-Contacts

Example: HLSW-PB20-ES-LCK-M1-PULL-0.5IN-NO

Release	
PULL	-PULL
TWIST	-TWST

Hub Config	
1/2 IN	-0.5IN
3/4 IN	-0.75IN
M20	-M20

Contacts	
NORMALLY OPEN	-NO
NORMALLY CLOSED	-NC

Links (Click on the below items to view):

- ATEX Certificate (European Explosion Proof)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- IEC Ex Certificate (International Explosion Proof)
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map