Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HLX-AE.EX-TX-220V-200VA-4X-24V-5C

200VA Explosion Proof Transformer - 220V to 24V AC - (4) Receptacles - 5' Cord - ATEX/IECEx Rated

Product ID: 257483

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLX-AE.EX-TX-220V-200VA-4X-24V-5C Hazardous Location Transformer

Listing: NRTL Listed to ATEX/IECEx Standards
Line-in Cord: 5' 16/3 SOOW Cord
Line-in Cord Cap: 16A IEC Ex 60309, 2P+E Clock Hour 6, Blue [220V]
Primary Voltage: 220V AC
Primary Breakers: -
Primary Receptacle: -
Primary Protection: -
Transformer: 200VA 220V to 24V AC - Encapsulated, Ex Rated
Maximum Wattage: 200W
Secondary Voltage: 24V AC
Secondary Breakers: -
Secondary Receptacles: (4) Extra Low Voltage IEC Ex 60309, 2P, Purple [24V AC]
Secondary Protection: Weatherproof Covers
Materials: Non-sparking
Mount: Portable w/ Top-mounted Handle
Dimensions: -
Weight: -

Ratings/Approvals

Approved for Zone 1 & Zone 2
Approved for Zone 21 & Zone 22
IEC Ex - Ex ed T5 Gb Ex tD
ATEX - Ex II 2GD Ex ed II T5 Gb Ex tD
Temp Rating -40Ta45
IP66 Weatherproof
NRTL Certified to IEC 60079
NRTL Certified to EN 60079
CE Certified

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The Larson Electronics HLX-AE.EX-TX-220V-200VA-4X-24V-5C Portable

Explosion Proof Transformer converts 220V AC electrical current into 24V AC for use in ATEX/IECEx rated facilities. This 200VA unit is equipped with four 24V AC receptacles and a top-mounted carrying handle for seamless mobility.

The HLX-AE.EX-TX-220V-200VA-4X-24V-5C portable transformer gives operators the ability to power their 24V AC equipment in ATEX/IECEx rated combustible sites from a single system. On the primary side, operators connect 220 volt line-in power via a 5-foot 16/3 SOOW cord with a 16-amp 220V IEC Ex 60309 blue cord cap (2P+E, clock hour 6). On the secondary side, four extra low voltage IEC Ex 60309 receptacles are available for 24V AC equipment. The receptacles contain weatherproof covers.

Operation: A 5-foot 16/3 SOOW cord with a 16-amp 220V IEC Ex 60309 blue cord cap (2P+E, clock hour 6) brings 220V power to the 200VA encapsulated Ex rated transformer, which converts 220V AC to 24V AC and passes the current to the secondary side. The secondary side is equipped with four 24V AC extra low voltage IEC Ex 60309, 2-pole purple receptacles (200W maximum).

Protective Construction: The HLX-AE.EX-TX-220V-200VA-4X-24V-5C is protected by a heavy-duty flameproof enclosure. An accessible top-mounted handle enables operators to carry the unit around the work site. This weatherproof power distribution unit is IP66 rated and approved for Zone 1/2 and Zone 21/22 locations.

Applications: Chemical processing facilities, food processing plants, oil refineries, agricultural sites, grain storage facilities, metal processing and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

HLX-AE.EX-TX-220V-200VA-4X-24V-5C

Product ID: 257483

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- ATEX Certificate (European Explosion Proof)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- IEC Ex Certificate (International Explosion Proof)
- INMETRO Certificate (Brazil)
- MSDS (Material Safety Data Sheet
- RoHS Certificate (Restriction of Hazardous Substances)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map