

HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1

Flameproof Double Push Button - 250V AC/110V DC - Momentary - Lockout Green - ATEX/IECEX
Product ID: 257564

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1 Flameproof Double Push Button

Listing: NRTL Listed for ATEX/IECEX Locations

Unit Type: Explosion Proof Double Push Button w/ Lockout

Dimensions: 3.03" x 4.13" x 1.73" (77mm x 105mm x 44mm)

Weight: -

Rated Voltage: 250V AC or 110V DC

Rated Frequency: -

Amperage Rating: 16A (250V AC), 1A (110V DC)

Mechanical Life: 100,000+ Operations

Push Button Type: Double Momentary, Non-illuminated

Push Button Colors: Red/Green

Contact Configuration: (1) NO, (1) NC

Lockout Type: Lockable Metal Hinge Plate for Single Push Button - Padlock, (2) Keys

Lockout Designation: Green Push Button Only

Operating Temp: -40°C to +50°C

Materials: Non-sparking

Mounting: Panel

Terminals: 2.5mm

Cable Entry OD: 5.5mm-13mm

Color: Black

Ratings

Approved for Zone 1 and 2

Approved for Zone 21 and 22

ATEX EX II 2 GD

IEC Ex d e IIC T6/T5 Gb

IEC Ex t IIIC T80°C Db/T90°C Db

Temp Rating -40Ta40/55

NRTL Certified to IEC 60079

NRTL Certified to EN 60079

CE Certified

Conforms to CE 0575

IP66 Weatherproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

PLEASE NOTE: The HLSW-AE.EX series of explosion proof switches, operators, buttons, lights, and dials are certified to European Union (ATEX) and International (IEC Ex) standards and are approved for installing in these locations. This unit IS NOT certified to United States (NEC) or Canadian (CEC) standards for hazardous location. This unit DOES NOT carry UL or CSA ratings. Please contact Larson Electronics for NEC/CEC equivalent version of this product if you intend to install the product in United States, Canada, or any country that followed NEC or CEC electrical standards.

The Larson Electronics HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1 Explosion Proof Double Push Button with Lockout is a compact solution for controlling industrial machinery or equipment in flammable environments. This device is compatible with 250V AC/110V DC and contains NO and NC contacts. The IP66-rated double push button is protected by a non-sparking housing.

PLEASE NOTE: The HLSW-AE.EX series of explosion proof switches, operators, buttons, lights, and dials are certified to European Union (ATEX) and International (IEC Ex) standards and are approved for installing in these locations. This unit IS NOT certified to United States (NEC) or Canadian (CEC) standards for hazardous location. This unit DOES NOT carry UL or CSA ratings. Please contact Larson Electronics for NEC/CEC equivalent version of this product if you intend to install the product in United States, Canada, or any country that followed NEC or CEC electrical standards.

The HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1 is designed for use in Zones 1/2 and Zones 21/22 rated combustible locations. This double-push button unit is rated for 250V AC at 16 amps and 110V DC at 1 amp. Featuring more than 100,000 operating cycles, the device operates with momentary action for both red and green push buttons (maintained action is available at an additional cost). This push button can be added to custom control station builds that contain pilot lights, other push buttons, emergency stop, selector switches, sensors and more. The weatherproof unit contains (1) normally open and (1) normally closed contacts.

A sturdy lockout component for a single push button deters tampering. This component consists of a metal hinged plate, which covers the green push button, and a padlock (two keys included). With this lockout configuration, only operators holding keys can provide approval or start the connected device. The red push button is always exposed, allowing any individual in the facility to stop the connected machine (for example, during emergency situations or presence of abnormal conditions).

This explosion proof push button is constructed of non-sparking materials. The IP66-rated device is suitable for ATEX/IECEx rated work sites with operating temperatures ranging between -40°C and +50°C. There are no labels or marking on this push button. We offer both custom labels (upon request) and the following selection of markings at an additional cost: On, Off, Start, Stop, I, O, Forward, Reverse and directional arrows.

Wiring: This non-illuminated device is equipped with 2.5mm terminals for wiring connections. Maximum outer cable diameter range for the hub is 5.5mm to 13mm.

Mounting: The HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1 is compatible with panel mounting applications.

Applications: Petroleum refineries, chemical and petrochemical plants, paint spray booths, food manufacturing buildings, agricultural operations, grain storage centers, industrial equipment and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)





HLSW-AE.EX-PMU-PB-16A-MS-2X.RG-C3-R-W1-G1

Product ID: 257564

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [IEC Ex Certificate \(International Explosion Proof\)](#)
- [MSDS \(Material Safety Data Sheet](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)