Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDXUL-32E-1227

96W LED Light Bar - Submersible Underwater Light - 1100'L X 200'W Spot - 120-240VAC - 5760 Lumens

Product ID: 257611

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDXUL-32E-1227 LED Light Bar

Lamp Type: 32 Edixeon® 3 Watt LEDs
Dimensions: 18.25"L x 3"H x 3.56"D
Total Watts:96
Voltage: 120-240V AC (208V, 220V, 230V)
Amps: 8A @ 12V DC, 4A @ 24V DC
Lumens: 5760
Beam Configuration: 10° Spot or 35° Flood
Spot Beam: 1100`L x 160`W
Flood Beam: 350`L x 340`W
LED Light Color: White
Color Temperature: 6000K, 5600K, 5000K, 4500K, 4000K, 3500K, 3000K, 2700K
Lux at Lens: 199,600
Lux at 1 Meter: 39,400
LED Life Expectancy: 50,000+ hours
Ambient Operating Temp Range: -40°C to +80°C
Optics Efficiency: 90%
Housing Material: Heavy Duty Billet Aluminum CNC Machined Housing
Mounting/Hardware Material: Stainless Steel
Lens Material: Shatter Resistant Polycarbonate Lens, One-piece Front Lens Cover
Lens Gasket: O-ring
Wiring: Deutsch IPD / LADD DT04-2P Connector, Potted Power Connector
Housing Color: Black or White
Weight: 7 lbs

Ratings/Approvals

CE Certified
RoHS Compliant
70% Lumen Retention @ 65,000 hours
Submersible to 3 Meters
Fresh and Saltwater Applications
Usable Above Water
IP68 Waterproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Buy American Compliant

The LEDXUL-32E-1227 from Larson Electronics is an LED Light Bar that offers high-intensity LED light output and extreme durability combined with versatile mounting and power options. This heavy-duty LED light bar, which is submersible up to 3 meters, produces a bright, 5,760 lumen LED light beam that can reach up to 1100` away from the operator. This high voltage light provides an extremely rugged lighting solution that is ideal for use in commercial and industrial security applications, as well as military environments.

The LEDXUL-32E-1227 LED light bar from Larson Electronics produces 5760 lumens of white light at a color temperature of 6000K. 32 Edison Edixeon® 3 watt LEDs producing 180 lumens each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam 1,110` long by 160` wide with limited spread or light spillage. We offer optional floodlight versions of this light that have 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. Other color temperature options include 5600K, 5000K, 4500K, 4000K, 3500K, 3000K and 2700K. Please choose an option when ordering.

This 96-watt unit, operates on 120-240V AC (including 208V, 220V and 230V) and may be used both underwater and above water. When used underwater, the luminary is submersible up to 3 meters, with maintained submersion capabilities in both fresh water and saltwater. Above water, the device is able to stay cool without reliance on surrounding water, allowing it to hold up to hurricanes, intense storms, land-to-sea vehicles and more. To ensure operation in versatile environments, the LEDXUL-32E-1227 is constructed of stainless steel hardware (including mounting brackets) and a heavy-duty billet aluminum CNC machined housing. The lens is made out of shatter resistant polycarbonate with a one-piece front lens cover and o-ring lens gasket. To prevent moisture from entering the power cable, the wiring of the light uses a potted power connector.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.


Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42V DC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on commercial boats, heavy equipment and vehicles where power systems

don`t always operate with 12 volts and external generators, transformers or inverters are impractical.

LEDXUL-32E-122735° Flood Beam



LEDXUL-32E-122710° Spot Beam



Durability: The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the `E` part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three feet and resist ingress of dust, dirt and humidity. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.
Mounting: This light bar is equipped with stainless steel mounting brackets which slide within the aluminum housing to allow users to adjust their positioning to match existing or user drilled mounting holes. Each stainless steel bracket has an integrated rubber bushing to absorb vibrations and shocks. To secure the lights in place users simply slide the mounting bolts through the aluminum mounting block and rubber isolator, through the mounting surface, then secure the bolt with a locking nut on the opposite side of the mounting surface. This mounting system enables mounting to flat or round surfaces and allows for minimal 7 degrees of flexibility of angle placement of the light. We also offer a BC-2 bar clamp mounting system you can view here for even greater mounting versatility.
Suggested Applications: Military, security, freshwater, saltwater, above water, extreme weather environments, marine settings, boats, docks, monitoring systems, rugged locations and more.
Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors. You can review the Deutsch connector technical details here.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.


Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364


Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDXUL-32E-1227
Product ID: 257611

Warranty: 36 Months

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
LEDXUL-32E-1227-Beam Pattern-Housing Color-Color Temperature
Example: LEDXUL-32E-1227-SP-BLK-60K

Beam Pattern	
SPOT	-SP
FLOOD	-FL

Housing Color	
BLACK	-BLK
WHITE	-WHT

Color Temperature	
6000K	-60K
5600K	-56K
5000K	-50K
4500K	-45K
4000K	-40K
3500K	-35K
3000K	-30K
2700K	-27K

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**