

ATEX-EPL-TL-2X10W-C

20W Explosion Proof Traffic Light - Dual Stack LED Light - Wire Guard - ATEX/IECEX

Product ID: 261135

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-EPL-TL-2X10W-C Explosion Proof LED Stack Light

Listing: NRTL Listed for ATEX/IECEX Rated Locations

Lamp Technology: LED

Lamp Quantity: (2)

Dimensions: 11.17"-H 8.97" -D (Lamp Only)

Weight: -

Voltage: 120-277V AC, 24V DC, 12V DC, 24V AC or 12V AC

Total Watts: 20W

Single-lamp Watts: 10W

Total Lumens: -

Single-lamp Lumens: -

Luminous Efficiency: -

Expected Lamp Life: 50,000+ Hours

LED Colors: Red/Green, Red/White, Red/Blue, Red/Amber, Red/Purple, White/Blue, White/Green, White/Amber, White/Purple, Blue/Green, Blue/Amber, Blue/Purple, Amber/Green, Amber/Purple, Green/Purple or Red/Red

Color Rendering Index: -

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Beam Configuration: Steady Burn, Strobe or Strobe/Steady

Lighting Configuration: -

Power Efficiency: -

LED Drive: -

Amp Draw: -

Ratings/Approvals

IECEX PTB 12.0017

Ex d e op IIC T4, T6

Ex tb IIIC T4

PTB 11 ATEX 1045

Ex II 2 G Ex d e opis IIC T4

Ex II 2 D Ex tb IIIC T4

ATEX Zones 1 & 2, 21 & 22

IP66

Special Orders - Special Requirements

Ambient Temperature Range: -40°C to +55°C

Materials: Aluminum Housing, Temperature-resistant Pressed Glass Lens, Stainless Steel Wire Guard

Mounting: Pre-drilled Aluminum Flat Surface Mounting Bracket

Wiring: 10` SOOW Cable w/ Flying Leads

Hub: (2) 3/4" NPT

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The ATEX-EPL-TL-2X10W-C Explosion Proof Traffic Light from Larson Electronics is designed for use in ATEX Zones 1 & 2 and 21 & 22 industrial facilities. This 20-watt explosion proof LED stack light supports red, green, blue, white, purple and amber colors, as well as two lamps. This LED stack light is suitable for routing traffic and signaling, and visual indications in industrial refueling stations and process status indication in manufacturing facilities.

The ATEX-EPL-TL-2X10W-C is a dual indicator lighting solution for industrial refueling stations and manufacturing facilities. This ATEX-rated unit features red, green, blue, white, purple and amber colors (one lamp each color) with exceptional lumen output. The LED fixture is available in 120-277V AC, 24V DC, 12V DC, 24V AC or 12V AC. Lighting configuration options include the following: steady burn, strobe or strobe/steady. The LED luminary consumes up to 20 watts during operation (10 watts per lamp) and is approved for ATEX Zone 1 & 2 and 21 & 22 work sites.

This explosion proof LED traffic light is constructed of high-grade aluminum with temperature-resistant pressed glass lenses. Stainless steel wire guards protect each LED fixture from rugged handling and environments. The IP66-rated LED lamps in this traffic light offer cool operation and clean bright output that surpasses that of 100-watt incandescent indicator lamps. This stack light can also be configured with audible horns.

Commonly used color codes for indicators:

- Red: Stop / Failure conditions, such as an emergency stop or machine fault
- Yellow: Caution / Warnings, such as over-temperature or over-pressure conditions
- Green: Go / Normal machine or process operation
- Blue: External help request / Operator/Supervisor required / Maintenance personnel assistance required
- White: User-defined conditions specific to application and environment

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on

and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Wiring/Mounting: The ATEX-EPL-TL-2X10W-C comes with 10 feet of SOOW cord with flying leads for completing electrical connections. Individual leads per lamp allow independent operation, making this unit ideal for fuel depots and manufacturing facilities where status indicators are necessary. The individual leads can be connected to user provided terminal blocks or existing indicator systems. Two, 3/4" NPT hubs are also available during installation. Mounting is provided by a heavy gauge aluminum back plate fabricated from copper free aluminum with four predrilled holes designed to be bolted to walls, ceilings and flat surfaces for permanent and secure attachment.


Note on Lights: *Color choices and light configuration of this unit can be customized to your requirements. We offer steady burn or strobing LED lamps, as well as high or low voltage configurations. Please contact us for special color configurations.*

Applications: Manufacturing plants, oil refineries, wastewater treatment facilities, confined spaces, agricultural sites, grain storage centers, gas stations, food production buildings, chemical processing, flammable work sites and more. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)









ATEX-EPL-TL-2X10W-C

Product ID: 261135

Export Control Classification Number (ECCN): EAR99

Options:

ATEX-EPL-TL-2X10W-C-Voltage-Colors-Beam Config

Example: ATEX-EPL-TL-2X10W-C-1227VAC-RG-STB

Voltage	
120-277VAC	-1227VAC
12VDC	-12VDC
24VDC	-24VDC
12VAC	-12VAC
24VAC	-24VAC

Colors	
RED/GREEN	-RG
RED/WHITE	-RW
RED/BLUE	-RB
RED/AMBER	-RA
RED/PURPLE	-RP
WHITE/BLUE	-WB
WHITE/GREEN	-WG
WHITE/AMBER	-WA
WHITE/PURPLE	-WP
BLUE/GREEN	-BG
BLUE/AMBER	-BA
BLUE/PURPLE	-BP
AMBER/GREEN	-AG
AMBER/PURPLE	-PA
GREEN/PURPLE	-GP
RED/RED	-RR

Beam Config	
STEADY BURN	-STB
STROBE	-STROBE
STROBE/STEADY	-STROBE-STB

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)