Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671


www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ATEX-EPL-SL-5-LED-447-EPP.CE16A

55W Explosion Proof LED String Light - (5) Lamps - Wire Guard - 15M 16/3 SOOW w/ Cord Cap - ATEX/IECEx

Product ID: 261154

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-EPL-SL-5-LED-447-EPP.CE16A Flameproof LED String Light
Listing: NRTL Listed for International; ATEX/IECEx Rated
Lamp Technology: LED
Lamp Quantity: (5)
Dimensions: 17.59"-L x 3.36 -OD
Weight: 75 Lbs
Voltage: 120V AC, 250V AC or 12-24V DC
Total Watts: 55W
Watts: 11W
Lumens: -
Luminous Efficiency: -
Life Expectancy: 50,000+ hours
Light Color: White
Color Rendering Index: -
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Beam Type: Full
Lighting Configuration: Flood
Efficiency: -
Power Factor: -
Protection: Wire Guard
Amp Draw: 0.45A @ 120V, 0.20A @ 250V
Ambient Operating Temp Range: -40C to +40C/+55C
Housing Material: Alloy Plastic
Mounting: Handheld, Rotating Hook

Ratings/Approval
Approved for Zone 1 & Zone 2
Approved for Zone 21 and Zone 22
Ex db eb II C T5 Gb
Ex tb IIIC T95 Db (Ta55)
NRTL Certified to IEC 60079
NRTL Certified to EN 60079

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

The Larson Electronics ATEX-EPL-SL-5-LED-447-EPP.CE16A Explosion Proof LED String Light enables operators in ATEX/IECEx rated environments to closely illuminate hazardous areas effectively. The solid-state LED system features five, 11-watt lamps protected by stainless steel mesh wire guards for added durability. This alloy plastic unit comes with 15 meters of 16/3 SOOW cord with a 16-amp explosion proof pin/sleeve plug.

The ATEX-EPL-SL-5-LED-447-EPP.CE16A is a powerful string light solution for Zone 1/Zone 2 and Zone 21/Zone 22 rated work sites. This unit is equipped with a total of five, 11-watt LED lamps that take on a slim, cylindrical form factor and protected by stainless steel wire guards. A full, 360-degree lighting configuration ensures comprehensive illumination during use. This ATEX/IECEx rated string light is constructed of alloy plastic. Applications for this light includes: repair lighting in hazardous locations, mobile or temporary illumination, task lighting, inspections and more.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Voltage: The ATEX-EPL-SL-5-LED-447-EPP.CE16A operates on 120V AC, 250V AC or 12-24V DC.

Wiring & Plug: This flameproof string lamp is equipped with a 15-meter 16/3 SOOW cord and a 16-amp explosion proof pin/sleeve cord cap (HLP-EX-16A-2P3W).

Mounting: Each LED lamp contains a top-located rotating hook, which allows operators to mount the unit on bars, chains, poles, pipes and small openings.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ATEX-EPL-SL-5-LED-447-EPP.CE16A

Product ID: 261154

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

ATEX-EPL-SL-5-LED-447-EPP.CE16A-Voltage

Example: ATEX-EPL-SL-5-LED-447-EPP.CE16A-125V

Voltage	
120V	-125V
250V	-250V
12-24V	-1224

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**