

HAJ-CB-TLB-ALU-4IN

Hazardous Location Conduit Body - C1D2/C1Z2 - Type LB - 324 cu. in. - (2) 4" Hubs

Product ID: 263775

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAJ-CB-TLB-ALU-4IN Conduit Body for Hazardous Locations

Listing: United States, Canada

Unit Type: Hazardous Location Conduit Body

Dimensions: 16-7/8" x 7-13/16" x 5-1/2"

Weight: 4.82 lbs

Volume: 324 cu. in.

Configuration: Type LB

Material: Copper-free Aluminum

Finish: Electrostatically-applied Powder Coating

Mount: Conduit

Hub Qty: (2)

Hub Size: (2) 4" NPT Tapered Threaded

Approvals/Ratings

Class I, Division 2 Groups A,B,C,D

Class I, Zone 2

Suitable for Wet Locations (w/ Gasketed Covers)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The HAJ-CB-TLB-ALU-4IN Hazardous Location Conduit Body from Larson Electronics ensures reliable access to conductors and electrical components in combustible environments. This Type LB conduit body is made out of copper-free aluminum and finished with an electrostatically-applied powder coating. Operators are provided with two, 4" NPT tapered threaded hubs for completing installations.

The HAJ-CB-TLB-ALU-4IN facilitates tight and secure conduit connections in Class I, Division 2 and Class I, Zone 2 rated work sites. This hazardous location conduit body features a Type LB configuration and offers 324 cubic inches of volume. Constructed of

copper-free aluminum with an electrostatically-applied powder coating for durability, the unit is suitable for wet locations/raintight when used with gasketed covers.

Hubs: The HAJ-CB-TLB-ALU-4IN contains two, 4" NPT tapered threaded hubs.

Applications: Hazardous locations, conduit connections, electrical systems, wiring access, oil and gas, food processing facilities, chemical plants, manufacturing, combustible sites and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



HAJ-CB-TLB-ALU-4IN

Product ID: 263775

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)