

EPCS-PL.R-2PSW.KS

Explosion Proof 2-Position Selector Switch w/ LED Pilot Light - Class I, II, III - Key Operated - NEMA

Product ID: 263798

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPCS-PL.R-2PSW.KS

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPCS-PL.R-2PSW.KS Explosion Proof 2-Position Selector Switch

Listing: NRTL Listed for United States, Canada

Unit Type: Explosion Proof Key Operated Switch w/ Pilot Light

Dimensions: -

Weight: -

Voltage: 240V, 120V or 24V

Selector Switch Type: 2-Position, Maintained

Selector Switch Action: Key Operated, Rotary

Pilot Light: LED

Rated Current: 10 Amps

Material: Copper Free Aluminum Alloy

Mount: Surface

Configuration: Feed Thru or Dead End

Hub Size: 1/2" or 3/4"

Ratings/Approvals

Class I, Divisions 1 & 2, Groups C, D

Class II, Division 1, Groups E, F & G

Class III

NEMA 7 (C, D), 9 (E, F, G)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The Larson Electronics EPCS-PL.R-2PSW.KS Explosion Proof 2-Position Selector Switch is suitable for use in Class I, II and III rated combustible sites. This weatherproof unit features an LED pilot light. The NEMA-rated device is constructed of copper-free

aluminum and can be mounted on flat surfaces.

The EPCS-PL.R-2PSW.KS is recommended for motor or equipment control in flammable facilities. The 10-amp rated unit supports one 2-position switch with maintained operation. Compatible with 240V, 120V or 24V, this rotary device is key operated and features an LED pilot light. The NEMA-rated device is constructed of copper-free aluminum alloy. The EPCS-PL.R-2PSW.KS comes with stainless steel captive screws for the cover assembly.

Hubs: The explosion proof switch is offered with a feed thru or dead end configuration for completing wiring connections. Hub size options include: 1/2" NPT or 3/4" NPT.

Mount: The EPCS-PL.R-2PSW.KS is compatible with surface mounting applications.

Applications: Starters, remote control of motors, chemical processing plants, food processing facilities, oil refineries and other hazardous locations applicable to the unit's classified ratings.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



EPCS-PL.R-2PSW.KS

Product ID: 263798

Export Control Classification Number (ECCN): EAR99

Options:

EPCS-PL.R-2PSW.KS-**Hub Config**-**Hub Config**-**Voltage**

Example: EPCS-PL.R-2PSW.KS-**.50-FT-120V**

Hub Config	
1/2	-.50
3/4	-.75

Hub Config	
FEED THRU	-FT
DEAD END	-DE

Voltage	
120V	-120V
240V	-240V
24V	-24V



Links (Click on the below items to view):

- **Wiring Diagram** (<https://www.larsonelectronics.com/images/product/WiringDiagram/263798.PDF>)
- **HigResPic1** (<https://www.larsonelectronics.com/images/product/HigResPic1/263798.JPG>)
- **ISO 9001 Certification** (<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate** (<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map** (<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)