

HLO-AE.EX-32A-3P4W-380V

Flameproof Receptacle - 380V -32 Amps - 3-pole, 4-wire - IECEX/ATEX Rated

Product ID: 263864

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLO-AE.EX-32A-3P4W-380V IECEX/ATEX Rated Receptacle

Listing: NRTL Listed for European, International Locations

Unit Type: Flameproof Receptacle

Dimensions: -

Weight: -

Max Voltage Rating: 380V AC, 3PH

Amps: 32A

Poles: 3-pole

Wires: 4-wire

Configuration: 3P4W (3P+E)

Clock Hour: 6H

Ambient Operating Temp Rating: -40 Ta +55

Materials: Polyamide

Terminal Capacity: -

Hubs: -

Ratings/Approvals

ATEX/IECEX Rated

Approved for Zone 1 and 2

Approved for Zone 21 and 22

Ex II 2 GD Ex db eb IIC T6

Ex II 2 Gb Ex tb IIIC T80 DbTa +45

Ex II 2 GD EX db eb IIC T5

Ex II 2 Gb EX tb IIIC T95C DbTa +55)

NRTL Certified to IEC 60079

NRTL Certified to EN 60079

CE Certified

IP66 Weatherproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics HLO-AE.EX-32A-3P4W-380V Flameproof Receptacle is recommended for use in IECEX/ATEX rated work sites. This

32-amp rated outlet comes in a 3-pole, 4-wire configuration with 380V AC compatibility. Constructed of polyamide, the unit features IP66 protection.

The HLO-AE.EX-32A-3P4W-380V is designed for secure electrical connections in hazardous locations. This 3-pole, 4-wire receptacle is rated at 32 amps and is compatible with three-phase 380V AC. The IECEx/ATEX rated unit features non-metallic, polyamide construction and IP66-rated protection. Specially designed color coding and pin reduces the possibility of making incorrect power connections. The flameproof receptacle contains a clock hour 6 configuration.

Applications: Manufacturing, industrial, warehouse, lighting, motor-generator sets, compressors, wet areas or locations where combustible dusts, fibers or flying are present or where explosive gases or vapors may be present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



HLO-AE.EX-32A-3P4W-380V

Product ID: 263864

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)