Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**EPRB-ALU-2-0.75**

# Explosion Proof Conduit Reducer Bushing, 2" NPT to 3/4" NPT, Aluminum, C1D1, Rigid/IMC Adaptor

**Product ID: 263998**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**EPRB-ALU-2-0.75 Explosion Proof Reducer Bushing**
**Type: Explosion Proof Conduit Reducer Bushing**
**Dimensions: 13/16" (21mm) - Body Length**
**Hub Size: 2" NPT Male to 3/4" NPT Female**
**Configuration: Male to Female**
**Material: Aluminum, Copper Free (less than 4/10 of 1%)**
**Finish: Natural**
**Color: Silver**
**Weight: < 1 lb**

**Ratings**
Class I, Divisions 1 & 2, Groups A, B, C, & D
Class I, Zones 1 & 2, Groups IIC, IIB, & IIA
Class II, Divisions 1 & 2, Groups E, F, & G

**Special Orders - Special Requirements**
Contact us for special requirements
**Toll Free: 1-800-369-6671**
**Intl: 1-903-270-1187**
**Fax: 1-903-498-3364**
**E-mail: sales@larsonelectronics.com**

**The EPRB-ALU-2-0.75 from Larson Electronics is an Explosion Proof Conduit Reducer Bushing that is for use in Class I, Divisions 1 & 2, Groups A, B, C, & D and Class II, Divisions 1 & 2, Groups E, F, & G hazardous locations. This male to female NPT threaded reducer bushing can be used to reduce the s tapped hole or hub.**
**Features:** The EPRB-ALU-2-0.75 is constructed from copper free aluminum. This explosion proof reducer bushi reduces a 2" NPT threaded hole or hub down to a 3/4" NPT threaded hole or hub. The EPRB-ALU-2-0.75 is silve color and features a natural finish. This explosion prood conduit reducer bushing is designed to be used with rig or IMC conduit. The machined smooth finish interior bushing protects conductors as they are fed through this a The EPRB-ALU-2-0.75 is suitable for use in hazardous locations.
**Applications:** To reduce the trade size NPT of a taped hole or huib. Situations that require an existing tapped h hub to be reduced to a smaller size for conduit runs, or attaching a smaller NPT device to an existing larger NPT

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver cust ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us 800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

# Frequently Asked Questions (FAQ)

**EPRB-ALU-2-0.75**

**Product ID: 263998**

**Warranty:** 6 Months

**Export Control Classification Number (ECCN):** EAR99

Links (Click on the below items to view):

- **CE Certificate**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**