Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C

IEC 60309 Waterproof Connector, 16 Amps 2P+E, 220V 1PH 2P3W, Pin & Sleeve, IP67

Product ID: 264498

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C Water Tight Pin and Sleeve Connector	Certifications - Compliance
Device Series: IEC 60309 (International Standard)	Certified for United States & Canada
Device Type: Connector	NRTL Certified to UL 1682, UL 1686
Dimensions: -	NRTL Certified to CAN/CSA C22.2 No 182.1
Weight: -	CE Certified, Low Voltage Directive 73/23/EEC
Amperage Rating: 16A	CE Certified, Low Voltage Directive 93/68/EEC
Voltage: 220V	NRTL Certified to 60309-1, 60309-2
Frequency: 50/60 Hz	RoHS Certified
Phase: 1-Phase	Compatible with IEC 60309 Compliant Products
Configuration: 2P3W (3P+N+E)	IP67/IP69K Rated Weatherproof
# of Poles: 2-Pole	IK07 Rated Drop Resistant
# of Wires: 3-Wire	Flame Retardant (UL94 V2)
Max Voltage Rating: 250V 3PH	Certified for Full Load Interrupting
Clock Hour: 6H	**Current Interrupting: Certified for current interrupting at full rated current**
Cord Range: .350 - .860	**Corrosion Resistance: Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min**
Dielectric Voltage: 2000V for 1 min	**Flammability: Rated V-2 per UL 94**
# of Operations: > 5000 connects/disconnects under load, at full rated current and voltage	**Ingress Protection Rating: IP67/IP69K**
Minimum Withdrawal Force: 5lbs	**Moisture Resistance: Immersed for 24 hours in 5cm of 25°C water per UL 1682**
Temperature Rise: Max +30°C at full-rated current after 50 cycles of OL at 150% rated current	**Crush Test: 250lbs for 1 min after -25°C for 6 hrs**
Operating Temperature Range: -25°C to +65°C	**Impact Resistance: Drop from 30" 8 times after conditioning to -25°C for 6 hrs**
Waterproof Rating: IP67, IP69K, NEMA 4X	**Cross Compatible: 316C6W**

Shock Resistance: IK09

Flammability: V-2 Rated

Insulation Resistance: 500V for 1 min; >= 5M

Cable Secureness: "Force: 30lb; Torque: 0.4 ft-lb; Max Disp: <= 3/32""""

Seals: Neoprene
Material, Housing Body: Toughened PVC
Material, Housing Cover: Toughened PVC
Material, Contacts: Brass
Material, Contact Carrier: Nylon
Material, External Screws: Acid-Proof Stainless Steel
Material, Internal Screws: Zinc-plated steel
Material, Phase/Ground Sleeves: Brass
Material, Sleeve Spring: Stainless Steel
Material, Terminal Screws: Steel
Color: Blue
Shipping Dimensions: -
Shipping Weight: -

Mating Plug: XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-P
Mating Receptacle: XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-B
Mating Connector: XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C
Mating Inlet: XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-R

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The Larson Electronics XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C is an IEC 60309 international standard industrial use waterproof Connector for industrial work sites. The 16-amp pin/sleeve Connector is configured to operate on 1-Phase 220V AC power and features an IP67 waterproof rating. Designed for rugged facilities, the Pole-pole Wire-wire unit can be disconnected under load up to 5000? times.
The XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C is an industrial grade Connector with waterproof properties. This pin/sleeve unit is compatible with 1-Phase 220V and holds a 16-amp rating. The IP67-rated Connector is constructed of toughened PVC, reinforced thermoplastic polyester and stainless steel.
The XLE-PA-IP67-309.NA series from Larson Electronics complies with the IEC 60309 standard for international equipment (not North American standard), is a direct cross for 316C6W, and is cross compatible with other equipment designed to the same standard. The XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C is a Blue Connector with a grounding pin located at clock hour 6.
For North American standard configurations, please see XLE-PA-IP67-309.NA series product line.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)



Warranty: 6 Months.
Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**