

LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS

**14-25' Stationary 3-Stage Explosion Proof Light Tower - 360° Rotating Boom - EXP Junction Box
- Fixed Mount**

Product ID: 264597

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS - 25` Three Stage Telescoping Non-sparking Light Tower

Explosion Proof Tower Specs

Length: Telescoping from 14` to 25`

Weight: -

Capacity: 100 lbs

Materials: Non-sparking Aluminum Mast w/ Stainless Steel and Galvanized Hardware

Finish: Anodized Finish

Color Options: Blue or Black

Operation: (1) 1,000lbs Manual Winch, Electric Optional

Cable: 3/16" Galvanized Aircraft Cable

Anchor Bolts: (6) 9/16" Bolts

Explosion Proof Junction Box Specs

Listing: NRTL Listed for United States and Canada

External Dimensions: 16.38" x 10.69" x 16.38"

Internal Dimensions: 12"-L x 12"-W x 8"-H

Pan Dimensions: 10.5" x 10.5"

Available Dimensions for Devices: 11.37" x 11.37" x 8"

Weight: 83 lbs

Maximum Conduit Size: 5"

Maximum Operators on Lid: 4 Rows of 4 = 16

Mounting Leg Height: 0.25"

Summary/Ratings

14` to 25` Foot Light Mast

Non-sparking Aluminum Construction

Anodized Finish

Removable Mast Head

125 MPH Wind Resistance

Manual or Optional Electric Operation

Class I, Divisions 1&2 Groups B,C,D

Class I, Zones 1&2 Groups IIB+H2,IIA

Class II, Divisions 1&2 Groups E,F,G

Class III

NEMA 3, 4, 4X

CENELEC/ATEX/IEC Ex

Ex d IIB + H2 T5 or T6

Ex tD A21 IP66

Tamb = + 60°C

Mounting Dimensions (Horizontal) Height: 14.94"
Mounting Dimensions (Horizontal) Width: 6.94"
Mounting Dimensions (Vertical) Height: 6.94"
Mounting Dimensions (Vertical) Width: 14.94"
Cover Type: Bolted
Materials: Copper-free Aluminum
Mounting: Surface Mount
Backplate: Internal, Aluminum
Hinges: N/A
Hubs: (1) 3/4" NPT @ North Side and (1) 3/4" NPT @ South Side
Color: Grey

Shipping: Common Freight
Shipping Dimensions: 16.5`-L x 4`-W x 5`-H
Shipping Weight: +-200 lbs
Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS from Larson Electronics is a fixed mount 3-stage non-sparking aluminum light mast that provides a safe and effective way for operators to quickly deploy lights, security cameras and other equipment to elevations of up to twenty-five feet in combustible locations. This light tower features a rotating boom that allows for 360° of rotation, an explosion proof junction box and a removable mast head for storing mounted equipment when not in use.

This telescoping three stage explosion proof light mast from Larson Electronics is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in hazardous locations where this equipment must be elevated to heights up to 25` for effective coverage. This explosion proof light boom can be extended to 25` for maximum area coverage and collapsed to 14` for applications where a smaller footprint is required. This lightweight tower is constructed of non-sparking aluminum (with stainless steel and galvanized hardware) with a lower section 12` in length and 4" by 4" by 1/8" thick, middle section 11` in length and 3" by 3" by 1/8" thick, and an upper section 10` and 2" by 2" by 1/8" thick. Each section has a 1` overlap. The mast is extended to its full height using an included 1,000 lbs hand winch with 3/16" galvanized cable.



[Click Image to Enlarge](#)



The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics (this model takes on an anodized finish in blue or black). These light masts are typically mounted to trailers or other stable surfaces via a 15" by 13" by 1/4" thick mounting base-plate which has been drilled to accept six 9/16" anchor bolts. A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for light fixtures and equipment.

The LM family of telescoping towers feature a proprietary mast guidance system, which provides increased stability during high winds. When lowered to 14', the mast can withstand winds up to 125 mph. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with ease in either direction. The mast can be positioned in one of four different directions and locked back in place by re-tightening the T-handle. The mast itself spins freely and can typically be rotated with a single hand.

This explosion proof light tower can easily support and lift 100 lbs fixtures. The entire tower assembly is shipped via common freight carrier and when shipped measures approximately 16.5' long, 4' wide, 5' tall and weighs approximately 1400 lbs. Larson Electronics can custom tailor these units to the customer's requirements with longer sections and larger mounting plates. We also offer a choice of either the manual 1,000 lb hand winch included standard or optional electric winch.

Explosion Proof Junction Box: The explosion proof enclosure is made of copper-free aluminum and includes a watertight gasket for a NEMA 4X protection rating. The internal cavity of this flameproof enclosure measures 12" in length by 12" in width by 8" in height. This unit caters to a maximum of 16 operators on the lid (4 rows of 4 = 16) and a maximum conduit size of 5". Operators may access one, 3/4" NPT hub at the north side and one, 3/4" NPT hub at the south side of the unit.

Operators may access an aluminum back plate inside the enclosure for mounting customer-provided equipment. Equipped with a bolted cover, the grey explosion proof enclosure is compatible with surface-mount applications. The NEMA 4X rating makes the unit suitable for both indoor and outdoor applications, as well as ensures protection from water, dust, moisture, dirt and external ice formation. The explosion proof light tower is designed for Class I, Divisions 1 & 2 (Groups B,C,D); Class I, Zones 1 & 2 (Groups IIB+H2,IIA); Class II, Divisions 1 & 2 (Groups E,F,G) and Class III rated combustible sites.

Suggested Applications: Temporary lighting in hazardous locations and explosive facilities, construction sites, and security camera deployment. We can equip this mast with 1000W or 1500W Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the [LED10WSA-160](#), [LEDLB-200X2E](#), [LEDLB-160X2E](#) or [LEDLB-80x2E](#).

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS

Product ID: 264597

Export Control Classification Number (ECCN): EAR99

Options:

LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS-**Finish**

Example: LM.EP-25-3S-FM-ALU-AEB-12.12.8-BP-2X0.75NS-**BLU**

Finish	
BLUE	-BLU
BLACK	-BLK

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)