

EPL-48-2L-LED-50C-EPP

Explosion Proof LED Paint Spray Booth Light - C1D1 - 50 Foot SOOW Cable - Explosion Proof Plug

Product ID: 264629

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPL-48-2L-LED-50C-EPP

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-48-2L-LED-50C-EPP Explosion Proof LED Light

Listing: NRTL Listed for United States and Canada

Lamp Technology: LED

Lamp Qty: (2)

Dimensions: W-11.25" x L-52" x H-8.5"

Weight: -

Voltage: Universal 120-277V AC 50/60 Hz or 12-24V AC/DC

Total Watts: 56W

Single-lamp Watts: 28W

Total Lumens: 7,000 lms

Single-lamp Lumens: 3,500 lms

Luminous Efficacy: 125 Lm/W

Lamp Life: 50,000+ Hours

Color Temp: 5600K or 4100K

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Color Rendering Index: -

Beam Angle: 150°

Lighting Configuration: -

Power Efficiency: -

Ratings

Class I, Division 1, Groups C and D

Class I, Division 2, Group A,B,C,D

Class II, Division 1 & 2, Groups E,F,G

NRTL Certified to UL 595 Marine Type (Saltwater)

NRTL Certified to UL 844, 924

NRTL Certified to UL 1598 Marine Type

Certified to Canadian Standards

Listed for Paint Spray Booths

California Title 24 Compliant

IP67 Rated - Waterproof

NEMA 4X

Power Factor: -
Amperage: 0.47A @ 120V
Operating Temp Rating: T6 Rated
Ambient Operating Temp Range: -30° C to +85°C
Minimum Operating Temp: -30°C
Maximum Case Temp: +90°C
Housing Material: Non-sparking
Housing Finish: -
Lens Material: -
Mounting: Surface Standard - Pendant Optional
Wiring: EYM w/ 50' 16/3 SOOW Cable
EXP Cord Cap: 5-15P, 5-20P or 6-20P

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The Larson Electronics EPL-48-2L-LED-50C-EPP Explosion Proof LED Light Fixture is NRTL Listed for United States and Canada, rated Class I, Division 1 & 2 and Class II, Division 1 and 2 for areas where flammable chemical/petrochemical vapors exist or have the potential to exist. This explosion proof LED light has a T6 temperature rating and carries a paint spray booth light certification as well, making it ideal for applications such as paint booths, oil rigs, offshore applications, petrochemical, manufacturing, chemical storage, water treatment centers, and food processing plants.

This four foot, two lamp LED fixture is ideal for operators seeking a top quality explosion proof light that will reduce operating costs, improve lighting quality and reduce downtime incurred from frequent servicing intervals. The EPL-48-2L-LED-50C-EPP is equipped with Larson Electronics' specially designed LED T-series bulbs which produce 7,000 lumens, resulting in 30% more foot candles of illumination at 8 feet as compared to standard T8 lamps when measured with an Extech light meter. Our LED-T series bulbs are visibly brighter than standard T8s and have consistently surprised many of our customers with their unexpectedly high light output levels. We have replaced two 8 foot dual lamp T8 fixtures in our own facility with our LED T series lamps and produced more illumination in the work area with only one 2 lamp 4 foot long LED fixture.



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)



SURFACE MOUNT (STANDARD)



SURFACE



PENDANT



PENDANT MOUNT (OPTIONAL)

This two lamp explosion proof LED linear fixture is lighter in weight, has a slimmer profile, and produces more light than traditional explosion proof fluorescent fixtures. The four foot long LED tube design bulbs included with this unit are rated at 50,000 hours of service life, which is over twice as long as standard T8 bulbs.

This fixture carries a T6 temperature rating and is Class 1 Division 1, Groups C and D, Class 1 Division 2, Group A, B, C and D, and Class II, Division 1 and 2, Groups E, F and G. [Click here to read the NEC description for explosion proof and hazardous locations.](#)

We have eliminated the ballast box normally associated with fluorescent fixtures which reduces overall weight and creates a slimmer unit profile. There is no ballast in this unit and the included [LEDT8-28W-V1](#) LED lamps have a 50,000+ hour service life, both of which result in extreme efficiency and greatly reduced maintenance costs. The solid state design of the LED lamps give this fixture superior resistance to damage from vibration, extremes in temperature and a lamp service life over twice that of standard fluorescent bulbs.

The 28 watt LED lamps produce 30% more illumination than standard T8 bulbs while offering lower amp draw and increased reliability. Each lamp produces 3,500 lumens at 125 lumens per watt, for a combined 7,000 total lumen light output. An EPL-48-2L-T8 explosion proof fluorescent light, with a combined total of 64 watts, draws 0.54 amps at 120 volts AC. This LED version of the same light, with a total of 56 watts, draws only 0.47 amps at 120 volts AC. The EPL-48-2L-LED-50C-EPP is universal voltage, not multi-tap, and operates on any voltage from 120V to 277V AC 50/60hz without any modifications. We also make a 12/24V AC/DC version for low voltage applications for AC or DC power.

Energy Consumption Comparison

	<u>T5HO</u>	<u>T8</u>	<u>LED</u>
Wattage	108 watts	64 watts	56 watts
Amp Draw @ 120V AC	0.90 amps	0.54 amps	0.47 amps
Amp Draw @ 220V AC	0.49 amps	0.29 amps	0.25 amps
Amp Draw @ 240V AC	0.45 amps	0.27 amps	0.23 amps
Amp Draw @ 277V AC	0.39 amps	0.24 amps	0.20 amps
Amp Draw @ 12V DC	9 amps	5.34 amps	4.67 amps
Amp Draw @ 24V DC	4.5 amps	2.67 amps	2.34 amps
Lamp Life Expectancy	20,000 hours	24,000 hours	50,000 hours
Color Temperature	5000K / 4100K	4100K	5600K
Operation cost per year (12hs/day @ 12c/kWh)	\$56.77	\$33.64	\$29.43

Our EPL-48-2L-LED-50C-EPP LED light fixture is NRTL Listed for United States and Canada for use in paint spray booths. This fixture is equipped with a seal off and 50' of 16/3 SOOW cable with blunt cut end.

Mounting Options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.

Adjustable Surface Mount Brackets: Each bracket is cinched to the bracket mounting peg on

each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg.

[Click Photos to Enlarge](#)



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring & Plug: This explosion proof lighting system is equipped with an EYM and 50 foot of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-15 15 amp straight blade plug for use with 120V explosion proof outlets, a 5-20 20 amp straight blade plug for use with 120V explosion proof outlets, or a 6-20 20 amp straight blade plug for use with 220-240V explosion proof outlets.

Suggested Applications: Paint spray booths, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: EPL-48-2L-LED-50C-EPP



Image: EPL-48-2L-LED-50C-EPP



Image: EPL-48-2L-LED-50C-EPP




Image: EPL-48-2L-LED-50C-EPP

EPL-48-2L-LED-50C-EPP

Product ID: 264629

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPL-48-2L-LED-50C-EPP-Voltage-Cord Cap

Example: EPL-48-2L-LED-50C-EPP-1227-1523

Voltage	
120-277V AC	-1227
11-25V AC/DC	-1224

Cord Cap	
5-15P	-1523
5-20P	-2023-125V
6-20P	-2023-250V

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(<https://www.larsonelectronics.com/images/product/CECCert/264629.PDF>)
- **MSDS (Material Safety Data Sheet)**(<https://www.larsonelectronics.com/images/product/Msds/264629.PDF>)
- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/264629.PDF>)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(<https://www.larsonelectronics.com/images/product/NECCert/264629.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/264629.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/264629.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/264629.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/264629.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/264629.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/264629.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/264629.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/264629.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/264629.JPG>)
- **HigResPic10**(<https://www.larsonelectronics.com/images/product/HigResPic10/264629.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=ZseBiwS7iMI>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)