Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPSLED-EMG-80-C-AM-50C-EPP-120V

7W Explosion Proof LED Emergency Light - Class I, II, III - 120V AC - Magnetic Mount - 50' 16/3 SOOW Cord

Product ID: 264706

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPSLED-EMG-80-C-AM-50C-EPP-120V Explosion Proof Emergency Strobe Light

Listing: NRTL Listed for United States and Canada
Lamp Technology: LED Emergency Light
Lamp Dimensions: 7.25"-Wide, 21" Height
Lamp Weight: 9 lbs
Voltage: 120V AC
Total Watts: 7W
Total Lumens: -
Luminous Efficacy: -
Lamp Life: 50,000+ Hours
Color Options: Red, Blue, Green, Amber or White
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Color Rendering Index: -
Beam Angle: 360°
Lighting Configuration: Strobing Flash (4 Strobes per Second) or Steady Burn
Emergency Battery Type: Maintenance-Free Sealed Lead Acid
Emergency Runtime: 90 Minutes
Amperage: 0.058A @ 120V
Operating Temp Rating: T3C Rated

Ratings

Class I, Groups C and D
Class II, Groups E and F
Class III
IP67 (Waterproof)
Suitable for Paint Spray Booths
T3C Temperature Rating

Ambient Operating Temp Range: -
Housing Material: Heavy Cast Aluminum w/ Polyester Powder Coating
Lens Material: -
Mounting: Magnetic Mount - (4) 200-lb Grip Magnets
Wiring: 50` 16/3 SOOW Cable
Cord Cap Options: 5-15P or 5-20P

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPSLED-EMG-80-C-AM-50C-EPP-120V
Product ID: 264706

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:
EPSLED-EMG-80-C-AM-50C-EPP-120V-Light Color-Light Config-Cord Cap
Example: EPSLED-EMG-80-C-AM-50C-EPP-120V-RED-STB-1523

Light Color	
RED	-RED
GREEN	-GRN
BLUE	-BLU
AMBER	-AMB
WHITE	-WHT

Light Config	
STEADY BURN	-STB
STROBE	-STROBE

Cord Cap	
5-15P	-1523
5-20P	-2023-125V

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map