Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**EPEXC-2X-50-10.3-30A**

# Explosion Proof Extension Cord - Double Gang - 30 Amp Continuous Service - 50' 12/3 SOOW Cord

**Product ID: 264827**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**EPEXC-2X-50-10.3-30A Explosion Proof Extension Cord**
**Amp Rating:** 30 Amp Continuous Service
**Cord Length:** 50 Feet 10/3 SOOW
**Configuration:** 2 Pole 3 Wire
**Receptacles:** (2) 20 Amp Receptacles
**Configuration: 2 Pole 3 Wire**
**Voltage: 125V or 250V**
**Materials:** Copper Free Aluminum
**Mating Plugs:** ****EPP-15A, EPP-20-A***
**Finish: Epoxy Powder Coat**
**Cord Cap:** 30 Amp Pin/Sleeve Cord Cap
NRTL Certified to U.L. Standards

**Plug / Outlet Certifications**
Class I Division 1 Groups C & D
Class II Division 1 Groups F & G
30A Pin/Sleeve Cord Cap

**Special Orders - Special Requirements**
Contact us for special requirements

**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**Fax:** 1-903-498-3364
**E-mail:** sales@larsonelectronics.com

## Made in the USA

**The Larson Electronics EPEXC-2X-50-10.3-30A Explosion Proof Extension Cord allows operators to safely extend the range of their explosion proof light or equipment cords within the boundaries of the hazardous work area. These units are constructed of 50 feet of 10/3 SOOW explosion proof cord rated at 30 amps of continuous service. The cord is chemical and abrasion resistant and comes with two 20 amp explosion proof receptacles installed on one end and a general area use 30 amp pin/sleeve cord cap installed on the other end.**

The two 20 amp power receptacles are constructed of non sparking aluminum and finished with an epoxy powder coating while the housing is constructed of triple coated malleable iron for durability and added corrosion resistance. The internal receptacle plug contacts are constructed of brass and designed to maintain constant pressure along their entire length for superior connectivity. The plug receptacles are deeply recessed to prevent accidental contacts and designed for twist lock plug insertion to provide secure connections. A neoprene seal fitted inside the connector receptacle seals against the plug when inserted to provide positive sealing against water ingress. A spring loaded receptacle door provides an automatic weather-tight seal when the plug is removed. In standard installations within the hazardous location area, threaded rigid pipe is brought to the outlet and the outlet is affixes to a mounting surface.

The receptacles on these units are of a twist lock design. In order for a secure and working connection to take place, the operator must insert the plug and twist until it locks into place. This ensures a safe seal is made before any sparks from electrical contact can take place. To ensure the highest safety, operators should make connections outside of the hazardous area.

These explosion proof extension cords are preconfigured in 125 V (left) or 250 V (right). Each unit is equipped with a 30 amp explosion proof pin/sleeve cord cap and rated for 30 amps of continual service. The outlets are a twistlock design. The deep recessed contacts in the receptacle housing prevents ordinary and wet location plugs from activating the explosion proof outlets.

**Inter-Compatibility:** The included explosion proof plug and receptacles are cross-interchangeable with Crouse Hind™ part# ENPENP5151 plugs and receptacles and Hubble-Killiark part# UGP-15231 ACCEPTOR® plugs and receptacles. Any equipment requiring these C-H or H-B plugs should work with these cords. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

**Wiring and Plug:** This explosion proof extension cord is equipped with 50 feet of 10/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade 30 amp pin/sleeve cord cap.

**Suggested Applications:** Manufacturing, Industrial, Warehouse, Lighting, Explosion Proof Light Fixtures, Grinders, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**EPEXC-2X-50-10.3-30A**

**Product ID: 264827**

**Export Control Classification Number (ECCN):** EAR99

**Options:**

**EPEXC-2X-50-10.3-30A-Voltage**

**Example: EPEXC-2X-50-10.3-30A-2023-125V**

| Voltage | |
|---|---|
| 125V | -2023-125V |
| 250V | -2020-250V |

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**
- **CE Certificate**
- **Certificate 1, Misc**
- **Certificate 2, Misc**
- **Certificate 3, Misc**
- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **USA NEC Certificate (Commonly referred to as UL Certificate)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**