

EPEXC-2X-50-10.3-30A-250V

**Explosion Proof Extension Cord - Double Gang - 30 Amp Continuous Service - 50' 12/3 SOOW
Cord - Pin/Sleeve Receptacles**

Product ID: 264828

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPEXC-2X-50-10.3-30A-250V Explosion Proof Extension Cord

Amp Rating: 30 Amp Continuous Service
Cord Length: 50 Feet 10/3 SOOW
Configuration: 2 Pole 3 Wire
Receptacles: (2) 20 Amp Pin/Sleeve Receptacles
Configuration: 2 Pole 3 Wire
Voltage: 125V or 250V
Materials: Copper Free Aluminum
Mating Plug: ****[EPP-250-1P-20A](#)
Finish: Epoxy Powder Coat
Cord Cap: 30 Amp Pin/Sleeve Cord Cap
[NRTL Certified to U.L. Standards](#)

Plug / Outlet Certifications

Class I Division 1 Groups C & D
Class II Division 1 Groups F & G
30A Pin/Sleeve Cord Cap

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPEXC-2X-50-10.3-30A-250V Explosion Proof Extension Cord allows operators to safely extend the range of their explosion proof light or equipment cords within the boundaries of the hazardous work area. These units are constructed of 50 feet of 10/3 SOOW explosion proof cord rated at 30 amps of continuous service. The cord is chemical and abrasion resistant and comes with two 20 amp explosion proof pin/sleeve receptacles installed on one end and a general area use 30 amp pin/sleeve cord cap installed on the other end.

The two 20 amp pin/sleeve power receptacles are constructed of non sparking aluminum and finished with an epoxy powder coating while the housing is constructed of triple coated malleable iron for durability and added corrosion resistance. The internal receptacle plug contacts are constructed of brass and designed to maintain constant pressure along their entire length for superior connectivity. The pin/sleeve plug receptacles are deeply recessed to prevent accidental contacts and designed for pin/sleeve plug insertion to provide secure connections. A neoprene seal fitted inside the connector receptacle seals against the plug when inserted to provide positive sealing against water ingress. A spring loaded receptacle door provides an automatic weather-tight seal when the plug is removed. In standard installations within the hazardous location area, threaded rigid pipe is brought to the outlet and the outlet is affixed to a mounting surface. The receptacles on these units are of a pin/sleeve design. In order for a secure and working connection to take place, the operator must insert the plug and twist until it engages into place. This ensures a safe seal is made before any sparks from electrical contact can take place. To ensure the highest safety, operators should make connections outside of the hazardous area.

These explosion proof extension cords are preconfigured in 125 V (left) or 250 V (right). Each unit is equipped with a 30 amp explosion proof pin/sleeve cord cap and rated for 30 amps of continual service. The outlets are a pin/sleeve design. The deep recessed contacts in the receptacle housing prevents ordinary and wet location plugs from activating the explosion proof outlets.

Inter-Compatibility: The included explosion proof plug and receptacles are cross-interchangeable with explosion proof rated UL 1686 series 20A pin/sleeve plugs including Cooper Crouse Hinds Arktite, Appleton Powertite, and Killark Versamate Plugs.

Wiring and Plug: This explosion proof extension cord is equipped with 50 feet of 10/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade 30 amp pin/sleeve cord cap.

Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Explosion Proof Light Fixtures, Grinders, Wet areas or Locations Where Combustible Dust is Present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)





EPEXC-2X-50-10.3-30A-250V

Product ID: 264828

Export Control Classification Number (ECCN): EAR99

Options:

EPEXC-2X-50-10.3-30A-250V-Voltage

Example: EPEXC-2X-50-10.3-30A-250V-2023-125V

Voltage	
125V	-2023-125V
250V	-2020-250V

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)