

EPCO-15A

Explosion Proof Connector Outlet - 15 Amp Rated - Locking Cap - 120V

Product ID: 265083

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPCO-15A Explosion Proof Power Outlet

Unit Dimensions: 3.69"D X 8.25"L

Receptacle Current Rating: 15 Amp

Configuration: 3 Pole 2 Wire

Voltage Rating: 120 V

NEMA Config: 5-15C w/ T-Slots

Number of Poles: 3

Suitable Cable: 14 AWG to 12 AWG SOOW

Mating Plugs: ****[EPP-15A](#),

Unit Materials: Copper Free Aluminum (4/10 of 1% max.)

Finish: Epoxy Powder Coat

Certifications - Compliance

Class I, Div 1 & 2, Groups B, C, D

Class I, Zone 1 & 2, Groups IIB+H2, IIA

Class II, Div 1 & 2, Groups F, G

Class III

NEMA 3, NEMA 4X

NRTL Listed for United States and Canada

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPCO-15A explosion proof power connector outlet provides durable and secure weatherproof power connection for portable or stationary electrical devices and equipment in locations where equipment is susceptible to wet and corrosive environments.

This 15 amp rated power receptacle is ideal for operators seeking a high quality, wet area rated power receptacle suitable for use in industrial and manufacturing applications. This unit's power receptacle is constructed of copper free aluminum. The unit is factory sealed and any arcing is safely contained with the interior of the outlet. The receptacle contacts are deep recessed to avoid accidental contact and will not be energized by non explosion proof plugs to preserve explosion proof

protection in hazardous environments. Ordinary location plugs will NOT activate this explosion proof receptacle.

The aluminum housing is finished in an epoxy powder coat. This unit is designed to withstand wet and corrosive conditions such as those found in docks and shipyards and comes with a spring loaded receptacle door to prevent ingress of water and contaminants when the unit is not in use.

The EPCO-15A power connector is constructed of non sparking aluminum and finished with an epoxy powder coating for durability and added corrosion resistance. The internal receptacle plug contacts are constructed of brass and designed to maintain constant pressure along their entire length for superior connectivity. The plug receptacle is deeply recessed to prevent accidental contacts and designed for twist lock plug insertion to provide secure connections. A neoprene seal fitted inside the connector receptacle seals against the plug when inserted to provide positive sealing against water ingress.

A spring loaded receptacle door provides an automatic weather-tight seal when the plug is removed. This flip-style lid features a special notch, allowing operators to lock the door in the open position while plugging or unplugging devices. With no devices plugged into the connector, the lid will screw shut, providing a NEMA 4X seal. When a plug is installed in this connector, the internal seals provide a NEMA 3 seal.

This explosion proof connector is a mate for the Larson Electronics [EPP-15A](#) explosion proof plugs and is compatible with all the Larson Electronics explosion proof lights we make with an explosion proof plug.

Options: This unit accepts 14 or 12 gauge SOOW or similar diameter cable.

Circuit breaking protection: This unit's receptacle is designed to safely contain any arcs between the internal contacts that may be created within the receptacle housing.

Inter-Compatibility: These units are compatible with Crouse Hind™ plugs under catalogue number "ENP5151" and Hubble-Killark Acceptor® plugs under catalogue number "UGP-20231,UGP-20232." Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.

Suggested Applications: Areas where flammable or ignitable vapors or gases may be present or stand the potential to exist, including manufacturing, industrial, commercial, docks, shipyards, shipping ports and other similar ship to shore applications as well as any application requiring a wet area suitable and highly durable source of secure power connection.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)