

GLR-GT-ALB

Adjustable Locking Base Compatible with Golight Radioray GT Lights - Permanent or Magnetic Mount

Product ID: 265719

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: GLR-GT-ALB

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

Made in the USA

Adjustable locking base for Golight Radioray GT Remote Controlled Spotlight. A spring loaded Pem stud snaps into one of the numerous index holes, controlling the rotation and tilt angles. Although the angle is easy to change, no amount of vibration will change the settings, once established. Obviously, the remote control lights can change rotation and angle, but often times the remote control light needs to be elevated in order to have full range. Sometimes, the remote control light cannot be mounted at the very edge of the surface or it is mounted behind some type of rail. In these cases, elevating the light 6 inches and creating new angles will improve the performance of the light.

For people wanting to mount the Golights on an angled surface, this adjustable, locking base seems to be working well. It gets the Golight up about 6 inches from the mounting surface and gives them the ability to set the mount angle and rotation at any angle they like. You just pull

back on the pem studs, rotate or tilt the unit and then drop the stud into an index hole. This makes it a snap to change the position of the base, but once it is locked into place it will stay there no matter how much vibration. It's made from 10 gauge steel, powder coated black. Boaters are asking for this in stainless, so that is available on demand. These can be permanently or magnetically mounted. The steeper the mounting surface, the more useful this is. You can mount the light on a 45 degree downward slope, and then use the base to bring it level. You can even mount the light facing down and then use the base to bring it level.

Available in permanent mount or magnetic mount versions. Excellent solution for mounting on garages and buildings. When combined with the [GL-1204 Ac/DC Converter](#), any Golight remote controlled spotlight can be used with common house wiring (110 VAC). Thus, this becomes an excellent security light for driveways, walkways, etc. where people can use the handheld remote to activate and control the light as they approach and use the driveway, walkway, parking lot, etc.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: GLR-GT-ALB



Image: GLR-GT-ALB



Image: GLR-GT-ALB



Image: GLR-GT-ALB

GLR-GT-ALB

Product ID: 265719

Export Control Classification Number (ECCN): EAR99

Options:

GLR-GT-ALB-Base-Color

Example: GLR-GT-ALB-Perm-Blk

Base	
PERMANENT	-Perm
MAGNETIC	-Mag

Color	
BLACK	-Blk
WHITE	-Wht



Links (Click on the below items to view):

- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/265719.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/265719.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/265719.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/265719.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/265719.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/265719.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/265719.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/265719.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/265719.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/265719.JPG>)
- **HigResPic10**(<https://www.larsonelectronics.com/images/product/HigResPic10/265719.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)