Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

SPLT-1.06K-LM30-6XWP600E-AT-BC

1.06 kW Solar Light Tower - 30' Light Tower - 7.5' Trailer - (6) 60W LED Lamps - (4) 250aH 4D Batteries

Product ID: 265973

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

SPLT-1.06K-LM30-6XWP600E-AT-BC Trailer Mounted 3-Stage Light Tower

Light Mast Specs
Tower Length: 13.5` to 30`
Mast Head Length: 44"
Materials: Steel
Finish: Powder Coated - Gloss Blue
Operation: (1) 1,000lbs Hand Winch
Cable: 3/16" Galvanized Aircraft Cable

Solar Specs
Panes: (4) 265 Watt panels
Method of Deployment: Slider
System Voltage: 24 Volts
Battery Bank: (4) 12V 250aH 4D batteries
Battery Capacity: 1,000aH Total / 500aH Usable

LED Lamp Specs
Lamp Qty: (6)
Lamp Type: CREE LED
Total Watts: 360W
Single-lamp Watts: 60W
Total Lumens: 32,400 lms
Single-lamp Lumens: 5,400 lms
Luminous Efficacy: 90 lm/w
LED Life Expectancy: 50,000+ hours

Quick Summary
13.5` to 30` Light Mast
Steel Construction
Powder Coated Finish
Removable Mast Head
(4) 1,000lb Outriggers
125 mph Wind Resistance
Manual or Optional Electric Operation
(4) 265 Watt Solar Panels w/ Sliders
Fully Solar, No Fuel Needed
Waterproof/Vapor Proof Lamps
50,000+ Hour LED Life
Lamps ETL Approved for Wet Locations
IP68 Waterproof Lamps
Battery Charger
Auto Timer for Lights

Color Temp: 5600K, 4000K, or 3000K
Color Rendering Index: 80
Beam Angle: 60° Vertical, 75° Horizontal
Lighting Configuration: Flood Beam
Ambient Temp Range: -25°C to +60°
Lamp Housing Material: Cast Aluminum
Lamp Lens Material: Polycarbonate

Trailer Specs
Materials: Steel
Trailer Dimensions: 7.5`L` x 7`W trailer bed - 10.75` total length
Hitch: 2" Ball Coupler
Wiring: 7-Pin Flat
Axle: 3,500lb
Suspension: 3,500 Lb 4-Leaf Double Eye Springs
Outriggers: (4) 1,000 Manual Crack Leveling Jacks
Wheels: (2) 15" 5x4.5 Steel Rims
Tires: ST205/75/D15 H188
Weight: +-600 lbs
Shipping: Common Freight
Shipping Dimensions: 8`-L x 8`-W x 12`-H
Shipping Weight: +-600 lbs
Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA
The Larson Electronics SPLT-1.06K-LM30-6XWP600E-AT-BC solar powered LED light tower provides a safe and effective way for operators to quickly deploy 360 watts of intense LED illumination to elevations up to thirty feet. This solar light plant features a telescoping light tower that folds over for easy transportation, a rotating boom that allows for 360° rotation and a removable mast head for storing the six LED light fixtures when not in use. The unit features four 265-watt solar panels and a 1,000 aH capacity battery bank. The entire assembly is mounted onto a 7.5` single axle trailer, allowing operators to transport this solar light tower from location to location.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS
Solar Powered Light Tower: This solar light tower includes four solar panels, solar charging system, battery bank, battery charger, six LED lamps and manual crank up mast mounted on trailer with outriggers. The 1.06 kW solar generator system replenishes amp hours of usable battery capacity per day, assuming 5.5 hours of peak charging sunlight. This system delivers 24 volts for lighting mounted atop the 30` telescoping light mast.
The SPLT-1.06K-LM30-6XWP600E-AT-BC is supported by four 250aH 4D 12V batteries, equating to 1,000aH battery capacity (500aH usable). A battery charger provides flexibility during deployment, which allows operators to supply power to the batteries using an external power source. This feature is useful for fast turnaround projects, sustaining extended periods of illumination and remote sites that lack adequate exposure to sunlight.
Light Mast: This telescoping three stage steel light mast from Larson Electronics' is designed to allow operators to quickly and safely deploy the six LED light heads in locations where this equipment must be elevated to heights up to 30` for effective coverage. This light boom can be extended to 30` above the trailer floor for maximum area coverage, and collapsed to 13.5` for applications where a footprint smaller is required. The tower is constructed of square steel tubing with a base section 6.6` in length and 6" by 6" by 3/16" thick, lower section 6.78` in length and 5" by 5" by 3/16" thick, middle section 6.93` in length and 4" by 4" by 1/8" thick, upper section 7.08` in length and 3" by 3" by 1/8" thick, and top section 7.58` in length and 2" by 2" by 1/8" thick. Each section has a 1`+ overlap. The mast is extended to its full height using an

included 1,000lb rated hand winch with 3/16" galvanized steel cable.
A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for the equipped LED light fixtures. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with easy in either direction. The mast can be positioned in one of four different positions, and locked back in place by re-tightening the T-handle. The mast itself spins freely with easy, and can typically be rotated with a single hand. The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics.
The LM family of telescoping towers feature a proprietary mast guidance system, which provide increased stability during high winds. Four 1,000 lbs hand crank leveling jacks are used for leveling. The jacks can be leveled by hand crank or attachment provided for power drills. These outriggers can be extended 2` out from the side of the trailer for added stability. When lowered to 13.5`, the mast can withstand winds up to 125 mph. Custom builds can be provided for higher wind speed resistance when fully raised.



44" Mast Head for mounting lights and equipment
Click Image to Enlarge



Mast folds over for transportation and when not in use
Click Image to Enlarge

LED Light Fixtures: This solar light plant is equipped with six Larson Electronics LEDWP-600E high output LED light fixtures. The LEDWP-600E consists of six 10-watt LEDs housed within a waterproof aluminum housing that is powder coated for added durability and resistance to corrosion. The housing incorporates integral cooling fins for efficient heat dissipation and increased LED longevity. The LED lamp assembly is protected by a shatterproof polycarbonate lens which is secured to the housing with a waterproof seal. Mounting hardware for the LEDWP-600E consists of a stainless steel coated bracket and stainless steel screws to provide secure mounting and resistance to rust and corrosion. The mounting assembly provides for 360/180 degrees of rotation and tilt to allow the user to position the unit as desired once mounted.
LED Technology: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than traditional lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional lighting.
Lamp Control: Each lamp can be powered on individually, allowing operators to power one lamp or all six lamps at a single time to fit the required illumination requirements. An equipped dusk-to-dawn day/night sensor allows for automated operation of the light configuration set within the control center. Operators may also set a time/duration for light activation using the built-in auto timer feature.

Images Below Show Light Tower Lowered and Raised to 30ft.



Click Images to Enlarge

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Lamps Off (Ambient Light)







(4) 60 Watt LED Lamps Turned On Illuminating Wall 200ft. Away (20,000+sq.ft. area)



Area from Above

Solar Panel Assembly: This unit is comprised of four 265-watt solar panels, generating a total maximum output of 1.06 kW. The panels are mounted securely on a sliding assembly. During deployment, the top solar panels slide out to form a four-panel array for maximum exposure to sunlight. The panels are wired to the solar charger control box which manages the charging system. When in use, the four solar panels are angled at 45° to capture the intensity of the sun for optimized light intake.
Component Control Center: All the electrical components are encapsulated in a NEMA 3R job box that is bolted to the trailer. Since most of these components are not rated for high heat, our component cooling system circulates air within the job box at 1400 CFM when the ambient temperature exceeds 90 degrees Fahrenheit. The job box that contains the component control system includes locks for security purposes.
Trailer Assembly: The entire assembly is mounted to a 7.5` by 7`, single axle trailer via six 1/2" anchor bolts. The two wheel trailer is equipped with 3,500 lbs axle and leaf springs with 15" trailer tires. A standard 2" ball coupling, two standard safety chains, and 7-pin flat trailer plug allow for easy hookup and towing. The trailer tongue can be removed for long term deployment. A rugged and waterproof job box is included, safely secured to the trailer. Four outriggers mounted to the corners of the trailer allow operators to level the trailer, and provide stabilization during deployment. All trailer lighting complies with DOT/FMVSS regulations.
Applications: Remote work locations, construction sites, military bases, camping sites, outdoor events, security applications, emergency services, outdoor lighting, portable lighting and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



SPLT-1.06K-LM30-6XWP600E-AT-BC

Product ID: 265973

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic4**
- **HigResPic5**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**