Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3

Flameproof Double Push Button w/ Pilot Lights - 250V AC/110V DC - Red/Green, Momentary - ATEX/IECEx

Product ID: 266615

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3 Flameproof Double Push Button w/ Pilot Lights

Listing: NRTL Listed for ATEX/IECEx Locations
Unit Type: Explosion Proof Double Push Button w/ Pilot Lights
Dimensions: 3.74" x 3.38" x 2.99" (95mm x 86mm x 76mm)
Weight: -
Rated Voltage: 250V AC or 110V DC
Rated Frequency: -
Amperage Rating: 16A (250V AC), 1A (110V DC)
Mechanical Life: 100,000+ Operations
Push Button Type: Double Momentary
Push Button Color: Red/Green
Contact Configuration: (1) NO, (1) NC
Pilot Lights: (1) Red - Right, (1) Green - Left
Pilot Light Voltage: 100-250V AC or 12-24V DC
Label/Marking: -
Operating Temp: -40°C to +50°C
Materials: Static Resistant Plastic Alloy (Housing)
Mounting: Pendant
Terminals: 2.5mm
Cable Entry: (2) M20 Molded Plastic Hubs @ Bottom
Maximum Cable OD: 5.5mm-13mm

Ratings

Approved for Zone 1 and 2
Approved for Zone 21 and 22
ATEX EX II 2 GD
IEC Ex d e IIC T6 Gd IP66
IEC Ex tb IIC T80°C Db
Temp Rating -40Ta50
NRTL Certified to IEC 60079
NRTL Certified to EN 60079
CE Certified
Conforms to CE 0575
IP66 Weatherproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

PLEASE NOTE: The HLSW-AE.EX series of explosion proof switches, operators, buttons, lights, and dials are certified to European Union (ATEX) and International (IEC Ex) standards and are approved for installing in these locations. This unit IS NOT certified to United States (NEC) or Canadian (CEC) standards for hazardous location. This unit DOES NOT carry UL or CSA ratings. Please contact Larson Electronics for NEC/CEC equivalent version of this product if you intend to install the product in United States, Canada, or any country that followed NEC or CEC electrical standards.

The Larson Electronics HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3 Explosion Proof Double Push Button with Pilot Lights is a compact solution for controlling industrial machinery or equipment in flammable environments. This device is compatible with 250V AC/110V DC and contains NO and NC contacts. Equipped with two pilot lights, the IP66-rated unit is protected by a static resistant plastic alloy housing.

PLEASE NOTE: The HLSW-AE.EX series of explosion proof switches, operators, buttons, lights, and dials are certified to European Union (ATEX) and International (IEC Ex) standards and are approved for installing in these locations. This unit IS NOT certified to United States (NEC) or Canadian (CEC) standards for hazardous location. This unit DOES NOT carry UL or CSA ratings. Please contact Larson Electronics for NEC/CEC equivalent version of this product if you intend to install the product in United States, Canada, or any country that followed NEC or CEC electrical standards.

The HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3 is designed for use in Zones 1/2 and Zones 21/22 rated combustible locations. This double-push button unit is rated for 250V AC at 16 amps and 110V DC at 1 amp. Featuring more than 100,000 operating cycles, the device operates with momentary action for both red and green push buttons (maintained action is available at an additional cost). One red (right) and one green (left) pilot light are available on the device, which operate on 100-250V AC or 12-24V DC. This push button can be added to custom control station builds that contain pilot lights, other push buttons, emergency stop, selector switches, sensors and more.

The explosion proof device is constructed of static resistant plastic alloy (housing). The IP66-rated device is suitable for ATEX/IECEx rated work sites with operating temperatures ranging between -40°C and +50°C. There are no labels or marking on this push button. We offer both custom labels (upon request) and the following selection of markings at an additional cost: On, Off, Start, Stop, I, O, Forward, Reverse and directional arrows.

The weatherproof unit contains (1) normally open and (1) normally closed contacts. We offer a variety of contact configurations, such as: (2) normally open, (2) normally closed, (2) normally open and (2) normally closed, (4) normally open, (4) normally closed, (3) normally open and (1) normally closed, as well as (1) normally open and (3) normally closed.

Wiring: This non-illuminated device is equipped with 2.5mm terminals. Cable entry is facilitated by two M20 molded plastic hubs located at the bottom of the unit. To cater to other system or project requirements, we can offer this push button in M25, as well as in nickel-plated brass or stainless. Maximum outer cable diameter range for the hub is 5.5mm to 13mm.

Mounting: The HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3 is compatible with pendant mounting applications.

Applications: Petroleum refineries, chemical and petrochemical plants, paint spray booths, food manufacturing buildings, agricultural operations, grain storage centers, industrial equipment and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3

Product ID: 266615

Export Control Classification Number (ECCN): EAR99

Options:

HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3-Pilot Light Voltage

Example: HLSW-AE.EX-FG-PB.PL-16A-MS-2X.RG-C3-N-W1-G3-1227

Pilot Light Voltage	
100-250V AC	-1227
12-24V DC	-1224

Links (Click on the below items to view):

- **CE Certificate**
- **Certificate 1, Misc**
- **IEC Ex Certificate (International Explosion Proof)**
- **MSDS (Material Safety Data Sheet**
- **RoHS Certificate (Restriction of Hazardous Substances)**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**