

GAU-UTP-5X1000W-LED-480V

5000 Watt High Intensity LED Utility Pole Mount Light - 550,000 Lumens - 347-480V AC - Utility Pole Lighting

Product ID: 266791

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-UTP-5X1000W-LED-480V High Mast LED Light

Lamp Type: Cree® XTE LEDs
Lamp Dimensions: 17.17" H x 21.02"W x 19.57"D (Per Lamp)
Weight: 396.25 lb (Total Weight); 66.25 lb (Per Lamp)
Total Watts: 5000W (Total); 1000W (Per Lamp)
Total Lumens: 550,000 (Total); 110,000 (Per Lamp)
LED Chip: CRE XPE
LED Qty: 2,200 (Total); 440 (Per Lamp)
Luminous Efficiency: 110 Lm/W
Beam Configurations: 10° Spot or 60° Flood
LED Color Temperature: Cool White - 5500K
LED Life Expectancy: 50,000 hours
Led Drive %: 90%
Voltage: 347-480 V AC
Amp Draw: 3.00 A @ 347 V, 2.17 A @ 480 V (Per Lamp)
Wiring: Junction Box w/ 3/4" NPT Hub (Disconnects to Each Lamp from Box)
Mounting: Utility Pole Mount
Materials: Die Cast Aluminum Housing, High Specular Reflector
Finish: Powder Coated or Galvanized
Ambient Temperature Range: -40°C to +80°C
Waterproof Rating: IP65

Quick Summary

Metal Halide Replacement
Ambient Op Temp -40°C to +80°C
Ideal for Utility Poles
High Specular Reflectors
110 Lumens Per Watt Efficiency
IP65 Rated Waterproof
RoHS Compliant
70% Lumen Retention after 50,000 Hours
UL1012 Compliant
UL60950-1 Compliant
CE Certified

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The GAU-UTP-5X1000W-LED-480V from Larson Electronics is a High Intensity Utility Pole Mount LED Light that provides a safe and effective way for operators to quickly deploy 5000 watts of elevated lighting. Each unit on the GAU-UTP-5X1000W-LED-480V produces 110,000 lumens for a total of 550,000 lumens of lighting power. Each unit has a 3.00 amp draw at 347 V, 50,000 hour service life, 347-480 V volt compatibility, and a IP65 waterproof rating. This utility pole mount LED flood light system provides operators with a rugged and powerful LED alternative to metal halide lamps that uses little power and can withstand rugged use and abusive conditions.

The GAU-UTP-5X1000W-LED-480V Utility Pole Mount LED light from Larson Electronics is comprised of five 1000 W [GAU-HB-1000W-LED-480V](#) LED fixtures that each produce 110,000 lumens of high intensity light while drawing only 1,000 watts at 3.00 amps from a 347 volt electrical system. High output Cree® XTE LEDs are paired with a high purity polished aluminum reflector to produce a well focused 10° spot beam that is ideal for providing far reaching concentrated illumination. We also offer optional reflector a 60° flood beam spreads for covering wide areas. The spot beams are tightly focused and are designed for high elevation mounting to achieve distance, making spot versions ideal for high mast and spots lighting. The flood beams are designed to provide more light over a larger area nearer the fixture, making flood versions ideal for use as dedicated work and area lights.

GAU-HB-1000W-LED-480V lights are ideal replacements for fragile and hot running 2500 watt metal halide lamps. They offer low power requirements, high durability and a versatile mounting system that makes these LED light emitters a superior lighting solution for demanding applications where power and reliability is critical. The heavy duty design and high power of these LED lights also makes them suitable for a wide array of applications including but not limited to: high mast lighting, light towers, light plant LED retrofits, military, mining, industrial manufacturing, machine visioning, security and law enforcement, commercial structure illumination, sport complexes, billboards, race tracks, and parking lots to name a few.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units features a cast aluminum heat sink with copper heatpipes behind the reflector assembly to control heat buildup along with gear-slotting fin technology to dissipate heat. This heat sink is designed to allow ample air flow through the fixture, cooling the unit during operation. This allows for more thorough cooling of the LEDs for extended operating periods and allows the LEDs to be driven at up to 90% capacity without overheating or visible loss of light output. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

Durability: As well as unparalleled heat control, the GAU-HB-1000W-LED-480V series of LED lights from Larson Electronics also offer IP65 rated construction that is designed to withstand extremes of environmental and operating conditions.

These units can withstand rapid temperature changes of -40° Celsius to +50° Celsius, are waterproof, and resist ingress of dust, dirt and humidity. The housings are formed from die cast aluminum lens is constructed of impact and shatter resistant polycarbonate. The Cree® XTE LEDs help these units achieve resistance to vibrations and are rated at 70% lumen maintenance after 50,000 hours of use. We recommend these LED lights for use in applications where a lot of vibration, dust, dirt, dampness and abusive working conditions are encountered.

Voltage: This light is universal voltage capable and can be operated with 347-480 V AC without modifications. 347 V is common in Western Canada, while 480 V is common in the United States and Eastern Canada. The drivers in this unit provide the ability to automatically monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These lights can operate on current ranging from 347V to 480V 50/60Hz without any modifications necessary as a result. This ability to sense and adjust input current also provides protection against voltage spikes and drops that can occur in electrical systems which would otherwise result in burning up or premature LED failure without it.

Mounting: The GAU-UTP-5X1000W-LED-480V is equipped with a utility pole mounting system that allows it to be securely mounted to existing utility poles for wide area coverage.

Wiring: Each light fixture on the GAU-UTP-5X1000W-LED-480V is wired into a junction box with disconnects leading to each fixture. This design allows operators to wire directly into the junction box via a 3/4" NPT hub.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

GAU-UTP-5X1000W-LED-480V

Product ID: 266791

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GAU-UTP-5X1000W-LED-480V-**Finish**-**Beam Config**

Example: GAU-UTP-5X1000W-LED-480V-**PWDC**-**10SP**

Finish	
POWDER COATED	-PWDC
GALVANIZED	-GLVD

Beam Config	
10° SPOT	-10SP
60° FLOOD	-60F

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)