

LED10W-10R-EB

100 Watt LED Light - 9000 lumens - 9-48 Volts DC - Chain / Strap Mount

Product ID: 267071

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LED10W-10R-EB LED Light Bar

LEDs: Seoul Z-Power 10 Watt LEDs

Dimensions: 20"-L 2.75"-H 2.5"-D

Watts: 100

Voltage: 9-48 VDC

Spot Beam: 1100°L x 185°W

Weight: 4.5 Lbs

Lighting Configuration: 10° Spot or 35° Flood

Mounting: (2) Eye Bolts for Inverted Chain Mounting

Wiring: 2 pin Deutsch plug

Amps: 8.3 (on 12 volts) 4.2 (on 24 volts)

Lumens: 9,000

LED Light Color: 6300K

LED Life Expectancy: 50,000 hours

Optics Efficiency: 80%

Materials: Aluminum Housing, Polycarbonate Lens

Housing Colors: Black or White

Lux At The Lens: 198,800

Lux At 1 Meter: 24,800

CRI: 70

CE Certified
EN55015 EMI
EN61547 EMS

LED10W LED Features

Seoul Z-Power 10 Watt LEDs

LEDs Driven At 80%

-40 C~ +80C Operating Temp Range

900 Lumens per LED

70% Lumen Retention @50,000 hours

IP67 Rated Waterproof to 1 meter

[Download Spot and Flood Beam Specs](#)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187


E-mail: sales@larsonelectronics.com

EN62471 Photobiological Safety

Buy American Compliant

The Larson Electronics LED10W-10R-EB LED Light Bar offers high light output from a light weight/low profile, durable and water tight fixture. This IP67 rated LED light bar is designed with low profile hinge mounts that allow 180 degrees of angle adjustment and produces 9,000 lumens of LED light while drawing only 8.3 amps on 12 volts. This light can run on any voltage from 9 to 48 volts and provides a durable and powerful lighting solution ideal for use industrial and commercial applications such as machine vision system lighting, security illumination, law enforcement and vehicle lighting.

The LED10W-10R-EB LED light bar from Larson Electronics produces a 9,000 lumens of bright light while drawing only 100 watts @8.3amps from a 12 volt electrical system. Ten Seoul Z-Power, 10 watt LEDs producing a maximum of 900 lumens each are arranged in rows and paired with 10 degree optics to produce a well focused spot beam measuring 1100` long by 185` in width.. We also offer optional floodlight versions with 35 degree optics to produce a much shorter and wider beam with more light concentrated closer to the fixture. These LED light bars are IP67 rated and waterproof to 1 meter, sealed against intrusion by dust and dirt and constructed to withstand the demanding conditions found in marine environments.



Dark street without any illumination but distant street lights

Same street illuminated by the LED10W-10R, easily reaching the street lights 1100` away

[Click Photo to Enlarge](#)


[Click Photo to Enlarge](#)

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Seoul Z-Power 10 watt LEDs. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

Voltage Control: These units contain an internal voltage regulator which allows them to adjust input current to provide the correct LED voltage levels regardless of input levels from 9 to 50 VDC. These LED10W series light bars can operate on current ranging from 9 to 50VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on boats and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

LED10W-10R 35° Flood Beam
(Std)

LED10W-10R 10° Spot Beam
(Opt)



Durability: The LED10W series of LED light bars from Larson Electronics offer IP67 rated construction that is designed to withstand demanding marine operating conditions. These LED lights are designed for low profile mounting options, allowing them to be used in spaces where room is at a premium. They offer extruded aluminum housings and polycarbonate lenses that provide good durability yet are slimmer and lighter than extreme duty LEDLB-E series lights. These units can operate in temperatures ranging from -40 degrees Celsius to 80 degrees Celsius, are waterproof to 1 meter and are sealed against the ingress of dust, dirt and humidity. The Seoul P7 10 LEDs offer inherent LED resistance to shocks and vibrations, contributing to these unit's 8.6G rating of vibration tolerance.

Mounting: The LED10W-10R-EB is equipped with a pair of eye bolts that allows operators to invert mount the light from chains or straps.

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

On this particular unit there is a one foot pigtail attached to the LED light terminating in a 2 pin Deutsch plug. A wiring harness attaches to the Deutsch socket on the back of the LED light. The harness is terminated in a 2 pin Deutsch plug and includes 20 feet of cable, a relay and a toggle switch that will operate on 12 or 24 volts. The wiring harness is not necessary to installation. Operators can use existing wiring and switches, assuming they are rated for the amperage listed below.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

LED10W-10R-EB

Product ID: 267071

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LED10W-10R-EB-Finish-Beam Type

Example: LED10W-10R-EB-BLK-SP

Finish	
BLACK	-BLK
WHITE	-WHT

Beam Type	
SPOT	-SP
FLOOD	-FL

Links (Click on the below items to view):

- [CE Certificate](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [HigResPic1](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)