

MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ

6 kVA Isolation Transformer - 115V Delta Primary - 200Y/115 Wye Secondary - NEMA 3R - Fully Potted / Encapsulated

Product ID: 267127

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ Fully Potted Isolation Transformer Ratings

Phase: Three Phase	NRTL Listed for United States and Canada
Frequency: 400 Hz	ANN Cooling
kVA: 6	IP14 Rated
Primary Voltage: 115 V Delta	Fully Potted / Encapsulated
Taps: 2 x 5% FCBN, 2 x 5% FCAN	Isolation Transformer
Secondary Voltage: 200Y/115 V Wye	
Winding Material: Aluminum	
Efficiency Regulation: DOE 16	
Insulation: 180°C	
Temperature Rise: 115°C	
Impedance (Std): -	
Seismic: Yes	
Sound Level: Meets NEMA ST-20 Standards	
Primary Termination: -	
Secondary Termination: -	
Enclosure Material: NEMA Type 3R Heavy Duty - Resin Encapsulated	<u>Special Orders - Special Requirements</u>
Finish: ANSI 61 Grey Finish	Contact us for special requirements
Dimensions: 11.83"H x 14.17"W x 8.82"D	Toll Free: 1-800-369-6671
Weight: 140 lb	Intl: 1-903-270-1187

Mounting: Wall Mount

E-mail: sales@larsonelectronics.com

The MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R 115 V Delta 3 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 6 kVA, the MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R fully potted isolation transformer is a three phase unit with a primary voltage of 115 V Delta. It also provides a secondary voltage of 200Y/115 V Wye. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP14.

Benefits: The MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall brackets make installation fast and easy and the offset outward facing wall installation holes allow for easy power tool access.

Safety: The MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R is an encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ



Image: MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ




Image: MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ



Image: MT-DOE16-FP-3P-115D-6KVA-200Y.115-N3R-400HZ



Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/267127.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/267127.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/267127.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/267127.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/267127.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/267127.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/267127.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)