Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C

Industrial Portable UV Sanitation Cart - Kills 99% of Viruses - 3500 sq. ft. Area - 304 Stainless Steel/50' Cord - Public Transit - Adj. Height - Remote - Motion Sensor

Product ID: 267407

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C Adjustable Height UV Sanitation Light Cart

Lamp Technology: UV-C Fluorescent
Lamp Qty: (8)
Dimensions: 68.5" x 14.5" x 14.5" (20" of Vertical Adjustment)
Weight: 76 lb
Voltage: 120V AC, 50/60Hz
Total Watts: 320W
Single-lamp Watts: 40W
Total UV Output: 114.4W
Single-lamp UV Output: 14.3W
Effective UV Radiation (at 1 Meter) Per Lamp: 117.0 uW/cm2 @ 1M
Total Effective UV Radiation (at 1 Meter): 936.0 uW/cm2 @ 1M
Expected Lifespan: 8,000+ Hours
UV Wavelength: UV-C, 200nm - 280nm (254 nm)
Lamp Type: T8
Lamp Base: G13 (Medium Bi-pin)
Replacement Lamp: FRL-48-1X-T8-40W-UV-C
Beam Angle: 360°
Light Configuration: Flood
Delay: 1 Minute and 30 Seconds at Startup

Ratings/Features

Short-wave Germicidal Light
Kills 99% of Viruses and Other Germs
Cooling Fans
Safety Kit Included
Public Transit, Fleets
Wireless Remote
360° Auto Shut-Off Motion Sensor
Made in USA - Manufactured in Texas
EPA Reg. No 98409-1
EPA Est. No. 98409-TX-1

Maximum Treatment Time: 24 Hours
Safety Kit: (2) Safety Goggles, (4) Safety Signs
Wireless Remote: Yes - Included
Motion Sensor: Yes - 360° Auto Shut-Off Motion Sensor
Amps: 16 A
Ambient Operating Temp: 80°F
Materials: 304 Stainless Steel
Lamp Protection: Wire Guard and Center Rail
Mounting: Portable - (4) Wheels w/ (4) Adjustable Trailer Jacks with Hand Cranks
Wiring: 50' 16/3 SOOW Cord w/ Cord Cap
Cord Cap: 5-15 Straight, L5-15 Twist, or Pigtail

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas

The Larson Electronics IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C is an Adjustable Height Industrial Portable UV Sanitation Cart which can disinfect 99% of viruses, bacteria, mold, and spores in public transit, such as buses, trains, and large fleets. This unit offers UV-C output at a range of 200nm - 280nm (254nm) and comes equipped with eight UVC fluorescent lamps. Capable of passing through standard regulation public transit aisles, the 304 stainless steel UV system comes with 50` of 16/3 SOOW cord and a safety kit (two goggles and four safety signs). The IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C allows for twenty inches of vertical adjustment in order to sanitize over objects and other obstacles. This adjustable height industrial portable UV sanitation cart features a wireless remote and a motion sensor that automatically shuts the unit down when motion is detected.

Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores and bacteria. Click here to learn more about UVC and the corona virus*

The IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C is a powerful sanitation solution for public transit operations looking for a quick and thorough way to disinfect fleets. Equipped with eight UVC fluorescent lamps, this system offers 114.4 watts of total output, within the 200nm - 280nm UV-C range (254 nm). The lights have an expected lifespan of 8,000+ hours and emit a flood beam pattern. This UV system caters to 3,500 square feet of space with full, 360 degrees of coverage. With twenty inches of adjustable vertical travel, the IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C can be easily adjusted to the ideal height for various vehicles. Cooling fans below the lamps keep the unit running optimally. There is a delay of 1 minute and 30 seconds at startup for clearing the area after activation. Alternatively, an included wireless remote can be used to activate the device outside of the room.

Measuring 68.5" x 14.5" x 14.5", the slim cart can pass through standard regulation public transit aisles in buses, planes, trains and fleets, without needing to lift or elevate the unit (other disinfection devices on the market are bulky and are unable to fit through aisles). One UV sanitation cart covers 5-6 rows of 2x2 seats per session. Operators may move the cart around after exposure time to disinfect several sections.

This unit is made out of 304 stainless steel and features spring-loaded lamp sockets, which makes it easier to switch out lamps. A wire guard protects the UV lamps from tampering or accidental bumping. Two safety goggles (not full face masks) and four safety signs (to warn individuals about ongoing UV sanitation) are included with the light. With a recommended 20-25 minute exposure time for

viruses, multiple carts can be purchased to cover larger areas quicker. The UV light can disinfect over 99% of bacteria, viruses, mold, and spores.
Motion Sensor: The IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C is equipped with a motion sensor for an additional layer of safety while the unit is in use. Due to the potential harm UVC light can cause to a person`s skin and vision, it is unsafe to be near the light while it is powered on. To avoid accidental exposure to the UV light produced by this sanitation cart, it is equipped with a 360° motion sensor. When the motion sensor detects movement, it will power off the light. When no motion has been detected for at least 5 minutes, the unit will power back on.

Click Photos to Enlarge



5-15 Straight Blade Plug
15 Amp / 125V Rated



L5-15 Twist Lock Plug
15 Amp / 125V Rated



Flying Leads / Pigtail Wires

Wiring/Plug: This unit is equipped with 50 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to common wall outlets. Plug options include standard 5-15 15 amp straight blade plug for 110V wall outlets with ground or NEMA L5-15 15 amp twist lock plug for 125V twist lock outlets. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.
Cart: Operators can easily move the UV lighting system around facilities via four wheels at the bottom. A center rail enables seamless guidance and positioning of the unit. For best results, the light should be setup in the middle of the area. The IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C is equipped with four adjustable trailer jacks (two per side) with platform feet. The jacks allow for twenty inches of vertical adjustment. Operators simply set the unit in place and use the hand cranks to raise the cart to the ideal height for the specific area.
Note on Environment: Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.
Suggested Applications: Sanitation, disinfection, public transportation hubs, buses, fleets, vehicles, airplanes, trains, mass transit and more; kills 99% of viruses, bacteria, mold, and spores.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Q. Does this product kill COVID-19?

A. COVID-19 is the disease created from the SARS-CoV-2 coronavirus. Please see below link for effectiveness against viruses, including the 2019 SARS-CoV-2 coronavirus:
https://www.larsonelectronics.com/images/product/LightingFacts/266985.PDF

Q. Does this product kill he SARS-CoV-2 coronavirus?

A. Please see below link for effectiveness against viruses, including the 2019 SARS-CoV-2 coronavirus:
https://www.larsonelectronics.com/images/product/LightingFacts/266985.PDF

Q. Does this product generate ozone?

A. No. UV lights can be made as ozone-producing or non-ozone producing. Ozone producing lamps leaves radiation in the atmosphere and require a 20-30 minute time after lamps are turned off before the radiation levels dissipate to a safe level before you can re-enter the room/area. The products that Larson Electronics manufactures DO NOT use ozone-producing lamps. This means that the radiation stops the second the light turns off. Once the light is turned off, it is safe to return to the area being disinfected by the light. Please read manual for UV safety requirements.

Q. Is this product skin safe or eye safe?

A. No. UV radiation is not safe for the eyes or skin. Please read manual for UV safety requirements.

Q. Do I need to wear protective gear?

A. Yes. UV radiation is NOT safe for your skin or eyes. Please read manual for UV safety requirements.

Q. Is this unit safe to use in occupied areas?

A. No. This unit produces UV radiation. UV radiation is NOT safe for your skin or eyes. Please read manual for UV safety requirements.

Q. Does this product come with UV lamps

A. Yes. This product will ship with UV lamps. The required UV lamps are included with your purchase.

Q. What if obstacles are in the way of the UV light while it is disinfecting?

A. You will need to move objects around and disinfect again for another 30 minutes. If the cart does not have direct line of sight, it will not disinfect. This is a non-ozone UV generating product so it does not penetrate through solid surfaces and will not reflect and clean the underside of objects or behind objects. If you do not have direct line of sight from the light, you will need to move it around or move the obstacles to create proper exposure.

Q. What if I want to disinfect a larger area than the square footage that is listed in the specifications of this product?

A. You can move the product and cover other areas. Each time the unit is moved, the exposure time starts again.

Q. How long does the fixture need to operate to kill viruses?

A. 30 minute exposure time is required for killing viruses

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C

Product ID: 267407

Export Control Classification Number (ECCN): EAR99

Options:

IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C-Cord Cap

Example: IND-UC.360-SP-AH-48-8L-UVC-V1-AT.WR-KT-50C-5.15

Cord Cap	
5-15 STRAIGHT	-5.15
L5-15 TWIST	-L5.15
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- Catalog Page - Product Series
- Certificate 1, Misc
- Certificate 4, Misc
- Eye Safety Information/Certificate
- Lighting Facts & Information
- MSDS (Material Safety Data Sheet
- Operations Manual
- Spectrum Curve (Wavelength Graph)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- Video1
- Video2
- Video3
- Video4
- Video5
- Video6
- Video7
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map