Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C

Industrial Portable UV Sanitation Cart - Kills 99% of Viruses - 8000 sq. ft. Area - 304 Stainless Steel - 50' Cord - Dolly Style Cart

Product ID: 267546

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C UV Sanitation Light Cart

Lamp Technology: UV-C Fluorescent
Lamp Qty: (8)
Dimensions: 19"-W x 19"-D x 68"-H
Weight: 65 lb
Voltage: 120 V AC, 50/60 Hz
Total Watts: 960W
Single-lamp Watts: 120 W
Total UV Output: 212.8W
Single-lamp UV Output: 26.6W
Expected Lifespan: 8,000+ Hours
UV Wavelength: UV-C, 200nm - 280nm (254 nm)
Lamp Type: T8HO
Lamp Base: G13
Replacement Lamp: FRL-48-1X-T8HO-120W-UV-C
Beam Angle: 360º
Light Configuration: Flood
Delay: 1 Minute and 30 Seconds at Startup
Maximum Treatment Time: 24 Hours
Safety Kit: (2) Safety Goggles, (4) Safety Signs

Ratings/Features

NRTL Listed to UL 508A
NRTL Listed to CSA C22.2 No. 14
Short-wave Germicidal Light
Kills 99% of Viruses and Other Germs
Cooling Fans
Safety Kit Included
Dolly Style Cart
Made in USA - Manufactured in Texas
EPA Reg. No 98409-1
EPA Est. No. 98409-TX-1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Amps: -

Ambient Operating Temp: 80°F

Materials: 304 Stainless Steel

Lamp Protection: Wire Guard and Center Rail

Mounting: Portable - (2) Stationary Caster Wheels, (2) Support Legs, and (1) Handle

Wiring: 50' 16/3 SOOW Cord w/ Cord Cap

Cord Cap: 5-15 Straight, L5-15 Twist or Pigtail

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas


The Larson Electronics IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C is an Industrial Portable UV Sanitation Cart which can 99% of viruses, bacteria, mold, and spores in large facilities. This unit offers UV-C output at a range of 200nm - 280nm (254nm) and comes equipped with eight UVC fluorescent lamps. Capable of disinfecting an entire room, the 304 Stainless Steel UV system comes with 50` of 16/3 SOOW cord and a safety kit (two goggles and four safety signs). The dolly style cart on the IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C makes repositioning the unit very easy.

Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores, and bacteria. Click here to learn more about UVC and the corona virus*

The IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C is a powerful sanitation solution for industrial sites and commercial facilities. Equipped with eight UVC fluorescent lamps, this system offers output within the 200nm - 280nm UV-C range (254 nm). The lights have an expected lifespan of 8,000+ hours and emits a flood beam pattern. This UV system caters to 8,000 square feet of space with full, 360 degrees of coverage. Cooling fans below the lamps keep the unit running optimally. There is a delay of 1 minute and 30 seconds at startup for clearing the area after activation. Operators may move the cart around after exposure time to disinfect several sections.

This unit is made out of 304 Stainless Steel and features spring-loaded lamp sockets, which makes it easier to switch out lamps. A wire guard protects the UV lamps from tampering or accidental bumping. Two safety goggles (not full face masks) and four safety signs (to warn individuals about ongoing UV sanitation) are included with the light. With a recommended 20-25 minute exposure time for viruses, multiple carts can be purchased to cover larger areas quicker. The UV light can disinfect over 99% of bacteria, viruses, mold, and spores.

Click Photos to Enlarge



5-15 Straight Blade Plug
15 Amp / 125V Rated



L5-15 Twist Lock Plug
15 Amp / 125V Rated



Flying Leads / Pigtail Wires

Wiring/Plug: This unit is equipped with 50 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy

connection to common wall outlets. Plug options include standard 5-15 15 amp straight blade plug for 110V wall outlets with ground or NEMA L5-15 15 amp twist lock plug for 125V twist lock outlets. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.
Cart: Operators can easily move the UV lighting system around facilities via two stationary caster wheels at the rear of the unit, two support legs at the front, and a rear-mounted handle. Operators simply use the handle to tilt the unit onto the back wheels, roll the sanitation light into the desired position, and allow the unit to rest on the front support legs for use. For best results, the light should be setup in the middle of the area.
Suggested Applications: Sanitation, disinfection, killing 99% of viruses, bacteria, mold, and spores, retail spaces, lobbies, commercial locations, industrial parks, schools, public transportation hubs, airports, office buildings, medical centers and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Q. How long does the fixture need to operate to kill viruses?

A. 30 minute exposure time is required for killing viruses

Q. What if I want to disinfect a larger area than the square footage that is listed in the specifications of this product?

A. You can move the product and cover other areas. Each time the unit is moved, the exposure time starts again.

Q. What if obstacles are in the way of the UV light while it is disinfecting?

A. You will need to move objects around and disinfect again for another 30 minutes. If the cart does not have direct line of sight, it will not disinfect. This is a non-ozone UV generating product so it does not penetrate through solid surfaces and will not reflect and clean the underside of objects or behind objects. If you do not have direct line of sight from the light, you will need to move it around or move the obstacles to create proper exposure.

Q. Does this product come with UV lamps

A. Yes. This product will ship with UV lamps. The required UV lamps are included with your purchase.

Q. Is this unit safe to use in occupied areas?

A. No. This unit produces UV radiation. UV radiation is NOT safe for your skin or eyes. Please read manual for UV safety requirements.

Q. Do I need to wear protective gear?

A. Yes. UV radiation is NOT safe for your skin or eyes. Please read manual for UV safety requirements.

Q. Is this product skin safe or eye safe?

A. No. UV radiation is not safe for the eyes or skin. Please read manual for UV safety requirements.

Q. Does this product generate ozone?

A. No. UV lights can be made as ozone-producing or non-ozone producing. Ozone producing lamps leaves radiation in the atmosphere and require a 20-30 minute time after lamps are turned off before the radiation levels dissipate to a safe level before you can re-enter the room/area. The products that Larson Electronics manufactures DO NOT use ozone-producing lamps. This means that the radiation stops the second the light turns off. Once the light is turned off, it is safe to return to the area being disinfected by the light. Please read manual for UV safety requirements.

Q. Does this product kill he SARS-CoV-2 coronavirus?

A. Please see below link for effectiveness against viruses, including the 2019 SARS-CoV-2 coronavirus:
https://www.larsonelectronics.com/images/product/LightingFacts/266985.PDF

Q. Does this product kill COVID-19?

A. COVID-19 is the disease created from the SARS-CoV-2 coronavirus. Please see below link for effectiveness against viruses, including the 2019 SARS-CoV-2 coronavirus:
https://www.larsonelectronics.com/images/product/LightingFacts/266985.PDF

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C

Product ID: 267546

Export Control Classification Number (ECCN): EAR99

Options:

IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C-Cord Cap

Example: IND-UC.360-DH-48-8L-UVC-V2-AT-KT-50C-5.15

Cord Cap	
5-15 STRAIGHT	-5.15
L5-15 TWIST	-L5.15
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- Beam Information (Coverage, Datafile)
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- Catalog Page - Product Series
- Certificate 1, Misc
- Certificate 4, Misc
- Eye Safety Information/Certificate
- Lighting Facts & Information
- MSDS (Material Safety Data Sheet
- Operations Manual
- Spectrum Curve (Wavelength Graph)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- Video1
- Video2
- Video3
- Video4
- Video5
- Video6
- Video7
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map