


IND-CVL-IDC-300W-UVC-SFC

300W UVC Induction Conveyor Sanitation Light - 120-277V - Surface Mount

Product ID: 267813

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-CVL-IDC-300W-UVC-SFC UVC Sanitation Fixture

Listing: -

Lamp Technology: UVC Induction

Dimensions: -

Weight: -

Voltage: 120-277V AC

Total Watts: 300W

Total UV Output (Watts): -

Total Radiant Intensity: -

Luminous Efficacy: -

Lamp Life: 100,000+ Hours

UV Band: UVC 254nm (200nm - 280nm)

Peak Wavelength: 280nm

Color Temperature: -

Color Rendering Index: -

Lamp Type: Induction

Lamp Base: -

Replacement Lamp: -

Beam Angle: 120°

Lighting Configuration: Flood Pattern

Ratings/Approvals

Germicidal Applications

Risk Group 3 UV product

EPA Reg. No 98409-1

EPA Est. No. 98409-TX-1

Power Efficiency: -
Power Factor: -
Amps: 2.5A @ 120V, 125A @ 240V, 1.08A @ 277V
Operating Temp Range: -
Housing Material: -
Hardware/Hub Material: -
Mounting: Surface Mount
Hub Quantity: -
Wiring Hub Size: -

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

This unit is Made In USA - Manufactured in Texas

The IND-CVL-IDC-300W-UVC-SFC from Larson Electronics is a UVC Induction Conveyor Sanitation Light that serves as a disinfection solution in industrial facilities. This 300-watt unit features a UVC induction lamp with a 120° beam angle configuration. Powered via an electromagnet to reduce the risk of gas leaks associated with fluorescent lights, the surface-mount luminary operates on 120-277V AC.

***PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores and bacteria. [Click here to learn more about UVC and the corona virus*](#)

The IND-CVL-IDC-300W-UVC-SFC is a powerful induction sanitation lamp that is suitable for germicidal illumination along conveyor systems. This 300-watt fixture provides UVC output within the 200nm - 280nm range. During use, the unit emits UV light with a 120° beam angle in a flood beam configuration. This mercury-based germicidal lamp operates on 120-277V AC and does not contain electrodes. The lamp has a 100,000-hour useful lifespan, making the unit a long-lasting solution in work sites.

Operation: The IND-CVL-IDC-300W-UVC-SFC should only be used in non-occupied areas. The UVC radiation produced by this fixture is not safe for skin or eyes. These fixtures should also be set up on a separate circuit from other lighting. It is advised to use a control circuit that incorporates a motion sensor with groupings of fixtures. This adds a level of safety because the lights will turn off if someone enters the area while the lights are on.

This UV fixture is a Risk Group 3 UV product. UV radiation from the unit can damage the skin and eyes without proper protection. Operators should avoid exposure to the eyes and skin when the unit is unshielded (for use in enclosed environments only). In the event of lamp breakage, it is recommended to ventilate the room for 30 minutes and clean the area with gloves (not a vacuum cleaner). Contents should be stored in a sealed plastic bag and brought to a waste/recycling facility.

Mounting Height	Irradiance/Second	Exposure Time Required*	Beam Length	Beam Width
10 ft	166.92 uW/cm2	1.2 minutes	6.3 ft	6.3 ft
12 ft	121.34 uW/cm2	1.65 minutes	7.6 ft	7.6 ft
15 ft	82.86 uW/cm2	2.5 minutes	9.5 ft	9.5 ft

18 ft	61.15 uW/cm2	3.3 minutes	11.46	11.46
20 ft	51.48 uW/cm2	3.9 minutes	12.74 ft	12.74 ft
22.5 ft	42.61 uW/cm2	4.7 minutes	14.34 ft	14.34 ft
25 ft	36.06 uW/cm2	5.6 minutes	15.92 ft	15.92 ft
28 ft	30.25 uW/cm2	6.7 minutes	17.84 ft	17.84 ft
30 ft	27.21 uW/cm2	7.4 minutes	19.11 ft	19.11 ft
32.5 ft	24.11 uW/cm2	8.3 minutes	20.7 ft	20.7 ft
35 ft	21.59 uW/cm2	9.3 minutes	22.3 ft	22.3 ft
40 ft	17.75 uW/cm2	11.3 minutes	25.5 ft	25.5 ft

*Exposure time is based off of total irradiance. The above calculations are based on 12mJ total exposure. This level of exposure deactivates most organisms.

Note on Lamps: Induction lamps are similar to high-intensity discharge lamps. There is a glass bulb filled with gases, and an external ballast. The difference in the technology is, unlike metal halide or high pressure sodium that create an arc between two electrodes to ignite gases, induction lamps generate light from an electromagnetic interaction with the gases. This magnetic reaction with the gases provides a more energy efficient product and a longer lifespan over traditional high intensity discharge lamps. Additionally, there is no warm-up time generally associated with high intensity discharge lamps. Induction lamps provide instant-on light output similar to LED technology. The combination of induction lamp technology and UVC output provides the high output from high intensity discharge lamps with the instant-on, long life span, and energy efficiency of LED technology.

Mounting: The IND-CVL-IDC-300W-UVC-SFC is suitable for surface mount installations (see chart for mounting height and UV exposure recommendations).

Note on Environment: Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.

Applications: Germicidal, water purification, disinfection, food processing, air disinfection, pharmaceuticals, biotechnology and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



IND-CVL-IDC-300W-UVC-SFC

Product ID: 267813

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Certificate 4, Misc](#)
- [Eye Safety Information/Certificate](#)
- [Spectrum Curve \(Wavelength Graph\)](#)
- [HigResPic1](#)
- [Video4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)