

EXPCMR-WIP-OZ-2MP-IM.128G-M-1523

Explosion Proof Outdoor Security Camera - 120V - Wireless Video Output - 128GB Memory

Product ID: 269363

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 Explosion Proof Camera w/ Wireless Video Output

Listing: NRTL Listed for United States, Canada and International ATEX/IECEx Rated

Unit Type: Explosion Proof Wireless Camera

Dimensions: 18"W x 8"D x 6"H

Weight: -

Voltage: 120V AC

Watts: 5W

Image Sensor: CMOS

Display Resolution: 1920 x 1080

Video Resolutions: 1080p (1920 x 1080), 720p (1280 x 720), VGA (640 x 480), QVGA (320 x 240)

Lens: 2.8-4mm Focal Length

Angle of View: Horizontal: 106°, Diagonal: 118° @ f = 2.8mm; Horizontal: 70°, Diagonal: 78° @ f = 4mm

Video Framerate: 30fps (60Hz), 25fps (50Hz), Downward Adjustable

Video Output: Wireless

Wireless Standard: IEEE802.11b / g / n

Data Rate: IEEE802.11b - 11Mbps (Max); IEEE802.11g - 54Mbps (Max); IEEE802.11n - 150Mbps (Max)

Frequency Bands: 2412 - 2472 MHz

Remote Access: Supports P2P & DDNS

Wireless Security: Supports WEP, WPA & WPA2

Maximum Power: 18dBm

Internal Memory: 128 GB Solid State

Memory Recording Time: 16 Hours @ 1080p Resolution or 24 Hours @ 720p Resolution

Housing Material: Aluminum

Ratings/Approvals

Class I, Divisions 1 & 2 Groups B,C,D
Class I, Zones 1 & 2 Groups IIB+H2, IIA
Class II, Divisions 1 & 2 Groups E,F,G
Class III, Divisions 1 & 2
IECEx db IIC Gb
IECEx tb IIC Db IP66
ATEX Ex II 2 G / D
NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)
30' Max Distance

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Mounting: Magnetic Mount

Cord: -

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 from Larson Electronics is an Explosion Proof Outdoor Security Camera for flammable work sites, harsh environments and outdoor locations. This IP66-rated device offers wireless video output and connection to other devices. Capable of producing clear, 1080p HD images, the 5-watt unit supports magnetic mounting, which does not require tools, screws or additional accessories. 128 GB internal solid state memory allows the camera to record up to 16 hours of footage at 1080p or 24 hours at 720p.

Camera Features: The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 security camera provides operators in hazardous areas with crisp 1080p HD images. Equipped with a 2 MP lens, up to 6x digital zoom is possible with the fixed-focus device. A cutting-edge chipset facilitates image compression and video processing with superior quality. Video output and connection to other devices is wireless (no cords). An example of such device is our [Class I, Division 1 explosion proof tablet \(EXP-TBLT-10I-W10-128G-4G\)](#), which operators can use to view images transmitted wirelessly from the explosion proof security camera. 128 GB of internal solid state memory allows this camera to record up to 16 hours of footage in 1080p resolution or 24 hours at 20p resolution. Lower resolutions will allow for longer recording times.

Durability: The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining lightweight and easy to use. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate.

The explosion proof security device is designed to perform under harsh and rugged conditions. This IP66 rated waterproof unit resists the corrosive effects of weather, dust, dirt, and humidity. This Class I Divisions 1 & 2, Class II Divisions 1 & 2, Class III Divisions 1 & 2 rated camera provides property and product security while protecting operators with its safe and reliable explosion proof and weatherproof design.

Security & Remote Access: The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 supports several forms of security. The supported forms include WEP Encryption, WPA Encryption and WPA2 Encryption. This explosion proof outdoor security camera also features remote access capability. It supports both P2P and DDNS remote access.

Wi-Fi: The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 is Wi-Fi compliant with wireless standards IEEE 802.11 b/g/n. On IEEE802.11b, this camera transfers data at a maximum rate of 15Mbps. On IEEE802.11g, the max data transfer rate is 54Mbps. The max data transfer rate on IEEE802.11n is 150Mbps.

Wireless Network: The explosion proof camera allows operators to create their own 2.4 Ghz and 5 Ghz wireless network. This feature makes networks for cameras easier to setup in outdoor sites. A QR code on the unit can be scanned for seamless wireless network configuration. The network facilitates the connection of various devices. During use, footage is stored via internal memory.

Voltage: This unit operates on 120V AC.

Mounting: The EXPCMR-WIP-OZ-2MP-IM.128G-M-1523 can be mounted on magnetic surfaces via a magnetic mounting system on the explosion proof camera. This seamless feature allows operators with gloved hands to position the unit instantly, without tools, screws or additional accessories.

Applications: Explosion proof forklifts, tank cleaning, tank/reactor monitoring, remote observation of external facilities, offshore and land based rigs, indoor and outdoor security, commercial buildings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to

honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.




Frequently Asked Questions (FAQ)











EXPCMR-WIP-OZ-2MP-IM.128G-M-1523

Product ID: 269363

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)