Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2

10 kVA Rack Mounted Isolation Transformer - 400V Delta - 208Y/120 Wye-N - 15 Amp Circuit Breaker - 50/60Hz - Pin & Sleeve Inlet Plug/Twistlock Receptacle

Product ID: 271600

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 Isolation Rack Mounted Transformer

Transformer Type: Isolation
Phase: Three Phase
Frequency: 50/60 Hz
Primary Voltage: 400 V Delta
Primary Configuration: Delta
kVA: 10
Secondary Voltage: 208Y/120 V Wye-N
Secondary Connection: Wye-N
Circuit Breaker: 15-Amp C-Curve Circuit Breaker Protects Primary Side
Short Circuit Capacity: 10 kA
Maximum Switching Frequency: 360 Per Hour
Winding Material: Aluminum
Inlet Plug: 16-Amp 416B6W Inlet Pin and Sleeve Connector
Outlet Receptacle: 30-Amp 530R9W Female Twistlock Receptacle
Cooling: Air / Dry Type
Insulation: 220°C
Temperature Rise: 150°C
Sound Level: 36 dB
Enclosure Rating: NEMA 1
Enclosure Material: Steel - Ventilated
Finish: Powder Coated - Black
Mounting: At Least 20U Tall Server Rack (20U Unit)
Dimensions: 19"-W x 31"-D x 35"-H

Ratings

NRTL Listed for United States
NRTL Certified for Canada
Black Powder Coated Steel Enclosure
NEMA 1 Rated
Low Profile Front Mounted Handles
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Weight: 295 lb

The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 from Larson Electronics is a Three Phase Rack Mounted Isolation Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for server rack applications, the MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 provides increased reliability, higher efficiency, protection against critical equipment failures, and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 is a 20 rack unit (20U).

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 isolation transformer is a three phase unit with a 10 kVA rating and a primary voltage of 400 V Delta. It also provides a secondary voltage of 208Y/120 V Wye-N. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.
This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The powder coated steel enclosure is black in color, rated NEMA 1, and is suitable for mounting in a server rack mount of at least 20U. Four low profile handles on the front of the enclosure make installation and removal a simple task while still allowing server rack doors to close. The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 features a 220°C insulation with a 150°C temperature rise.

Benefits: The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.
This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Protection: The primary side of the MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 is protected by a 15 amp C-curve circuit breaker. This thermal magnetic three pole circuit breaker provides a layer of protection against power surges and start-up amp draw. It has a short circuit capacity of 10 kA and a maximum switching frequency of 360 per hour.

Safety: The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 achieves these safety features by seperating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Mounting: This rack mounted transformer is designed to be mounted inside server racks. The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 is a 20U unit which allows it to fit in a server rack mount at least 20U tall. The front located handles assist in inserting and removing the transformer while having a low enough profile to allow server rack doors to close.

Wiring/Connections: The MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2 features a 16-amp 416B6W inlet pin and sleeve connector for making 400 V Delta primary connections. The output side is equipped with a 30-amp 530R9W female pin/sleeve receptacle to allow for 208Y/120 Wye output connections.

Applications: Server rack isolation transformer applications.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

MPD-MT-RMU-20U-ISX-400D-10KVA-208Y.120-M2

Product ID: 271600

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**