Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C

280W UV Disinfection Conveyor Oven - 220V, 50Hz - (4) 48" UVC Lamps, UV Shield - Single Speed/25' Cord

Product ID: 271656

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C UV Sanitation Conveyor System

Lamp Technology: UV-C Fluorescent

Lamp Qty: (4) 48" (2 On Top; 2 On Bottom)

Overall Dimensions: 86.263"-L x 17.00"-W x 32.00"H

Conveyor Length: 52"-L

Maximum Package Dimensions: 12"W x 12"H

Weight: -

Voltage: 220 V AC, 50 Hz

Phase: 1-Phase

Total Watts: 280W

Single-lamp Watts: 40W

Total UV Output: 57.2W

Single-lamp UV Output: 14.3W

Effective UV Radiation (at 1 Meter) Per Lamp: 117.0 uW/cm2 @ 1M

Total Effective UV Radiation (at 1 Meter): 468.0 uW/cm2 @ 1M

Expected Lifespan: 8,000+ Hours

UV Wavelength: UV-C, 200nm - 280nm (254 nm)

Lamp Type: T8

Ratings/Features

UV Oven

Short-wave Germicidal Light

Kills 99% of Viruses and Other Germs

Made in USA - Manufactured in Texas

EPA Reg. No 98409-1

EPA Est. No. 98409-TX-1

Lamp Base: G13 (Medium Bi-pin)
Replacement Lamp: FRL-48-1X-T8-40W-UV-C
Beam Angle: 360°
Light Configuration: Flood
Sanitation Duration: 60 Seconds
Conveyor Belt Speed: Single

Activation: On/Off Switch for Lamps and Motor

Safety: Adjustable UV Shields

Amps: 1.33 A @ 220 V

Ambient Operating Temp Range: -

Materials: 304 Stainless Steel

Lens Material: -

Mounting: Rubber Feet

Wiring: 25' Cord w/ Cord Cap

Cord Cap: NEMA 6-15, NEMA 6-20, NEMA L6-15, NEMA L6-20, BS1363 (Type G), Schuko (Type F, CEE 7/4), BS546 (Type M), or Pigtail

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas

The Larson Electronics IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C UV Disinfection Conveyor Oven sanitizes products, packages, equipment, and more. It is ideal for putting into use at package processing areas, receiving stations, warehouses, and more. Equipped with four UV lamps, the unit offers UV-C output at a range of 200nm - 280nm (254nm). This system sanitizes packages up to 12" tall by 12" wide in 60 seconds. Protected by a 304 stainless steel housing, the UV oven operates on single-phase 220 V, 50 Hz and comes with a 25` cord terminated in a 220 V cord cap.

Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores, and bacteria. Click here to learn more about UVC and the coronavirus*

The IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C is a powerful sanitation solution for handling large amounts of products, packages, equipment, catalogs, mail, and other items that are 12" x 12" or less in size. Equipped with four UVC fluorescent lamps, this system offers UV output within the 200nm - 280nm UV-C range (254 nm). The lights have an expected lifespan of 8,000+ hours and emit a flood beam pattern with 360 degrees of coverage. Inside the UV oven, the lamps take on the following configuration: (2) 48" UV bulbs on the top and (2) 48" UV bulbs on the bottom. Models with side lamps are available (at an additional cost) for cleaning large packages.

Adjustable UV shields located at both ends are available for UV protection. The components are designed to reduce stray UV light during treatment. We offer bolt-on plastic strip door curtains for variable height processing at an additional cost. The single-speed system is protected by a 304 stainless steel housing.

Operation: Start the UV sanitation system by pressing the on/off button for the lamps and motors. Next, load "dirty" products, packages, equipment, mail, or other items into the entrance of the unit (the UV oven accepts packages up to 12" tall by 12" wide - we offer longer and wider units with larger size capacities at an additional cost). The "dirty" packages are cleaned by the UV lamps. The entire disinfection process takes 60 seconds to complete. Sanitized packages exit through an opening after UV treatment. To ease processing, we offer different types of end caps for catching into a collection box and an optional automatic grabber from a hopper (not included) at additional costs. We can also integrate

this UV disinfection unit with existing mail/package processing equipment at an additional cost.
Voltage: The IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C operates on single-phase 220 V AC, 50 Hz.

Click Photos to Enlarge



L6-15 Twist Lock Plug
15 Amp / 250V Rated



UK BS1363 Straight Blade Plug
13 Amp / 250V Rated / Internal Fuse



Intl Schuko 2-Pin Plug
16 Amp / 250V Rated / Grounded



Flying Leads / Pigtail Wires

Wiring/Plug: This unit is equipped with 25 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to outlets. Plug options include standard NEMA 6-15 15 amp straight blade plug, standard NEMA 6-20 20 amp straight blade plug, NEMA L6-15 15 amp twist lock plug, NEMA L6-20 20 amp twist lock plug, British BS1363 (Type G plug) 13 amp fused 3-blade plug for United Kingdom outlets, a two pin 16 amp rated Schuko plug (Type F, CEE 7/4 plug) with ground contact and socket for European outlets up to 250V, or a BS546 (Type M, CEE 3-pin 15 amp rated plug for Indian and South African outlets. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.
Mount: This UV sanitation system is a stand alone unit that can be deployed in work sites. Rubber feet at the bottom ensures stability and prevents scratching surfaces during use.
Note on Environment: Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.
Suggested Applications: Sanitation, disinfection, warehouses, mail, package processing, products, equipment, and more; kills 99% of viruses, bacteria, mold, and spores.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364






DANGER

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C

Product ID: 271656

Export Control Classification Number (ECCN): EAR99

Options:

IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C-Cord Cap

Example: IND-CBE-UVC-60-12X12-R2-220V.50HZ-25C-6.15

Cord Cap	
6-15	-6.15
6-20	-6.20
L6-15	-L6.15
L6-20	-L6.20
BS1363	-BS1363
SCHUKO	-Schuko
BS546	-BS546
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- **Beam Information (Coverage, Datafile)**
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**
- **Certificate 1, Misc**
- **Certificate 4, Misc**
- **Dimensional Drawing 2D**
- **Eye Safety Information/Certificate**
- **Lighting Facts & Information**
- **MSDS (Material Safety Data Sheet**
- **Spectrum Curve (Wavelength Graph)**
- **USA NEC Certificate (Commonly referred to as UL Certificate)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**