Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPSW-20A-DRW-1P-3W

Explosion Proof 0-10V Rotary Dimmer w/ 3-Way On/Off Switch - Single Pole Double Throw - Class I, II, III/Group B Rated - Copper-free Aluminum - N4X

Product ID: 272095

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPSW-20A-DRW-1P-3W Explosion Proof 0-10V Rotary Dimmer 3-Way Switch

Listing: NRTL Listed for United States, Canada
Switch Type: 0-10V Rotary Dimmer 3-Way Switch
Dimensions: -
Weight: -
Operation Voltage: 600 V AC
Dimmer Switch Type: Front Mounted Rotary Switch
Max Lamps per Switch: 25
On/Off Switch Type: 1-pole, Double Throw, 3-Way Rotary Switch
On/Off Switch Action: Maintained
Contacts: (1) Normally Open/Normally Closed
Contact Block Amp Rating: 20A
Grounding: Single Internal Housing Ground Screw
Ambient Temp Rating: -20°C to +60°C
Unit Materials: Copper-free Aluminum
Mounting: External Mounting Lugs on Body
Hub Quantity: (2) Feed Through or (1) Dead End
Hub Size: 1/2" or 3/4"
Color: Gray

Ratings/Approvals

Class I, Divisions 1 & 2 Groups B, C, D
Class II, Divisions 1 & 2 Groups E, F, G
Class III
NEMA 4X
NEMA 4X

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in Texas

The Larson Electronics EPSW-20A-DRW-1P-3W Explosion Proof 0-10V Rotary Dimmer w/ 3-Way On/Off Switch is suitable for Class I, II and III rated combustible work sites. This 0-10V dimmable explosion proof switch, which can be used in Group B rated locations and carries a NEMA 4X rating, provides a reliable method for operators to adjust the brightness of explosion proof lights connected to the switch in order to best accommodate the situation or workplace while maintaining safety within hazardous environments. Constructed of copper-free aluminum, the device features a rotary, maintained on/off switch below the dimmer as well as one normally open/normally closed contact.

The EPSW-20A-DRW-1P-3W is ideal for operators seeking a high quality explosion proof dimmer switch rated for use in hazardous areas designated Class, I, II and III environments, including Group B rated sites. This NEMA 4X rated dimmer with on/off switch is easily wall mounted via integral mounting tabs at two corners of the housing. Operators can choose between two hub sizes of either 1/2" or 3/4" and either a feed through or dead end configuration.

The explosion proof switch cover and housing box is constructed of copper free aluminum for superior performance and durability. A NEMA 4X waterproof rating indicates that the enclosure provides a degree of protection to operators against access to hazardous parts, provides a degree of protection against environmental concerns such as the ingress of water, provides additional protection against corrosion and that the enclosure will not be damaged by the external formation of ice.

This explosion proof dimmable rotary switch offers operators smooth, flicker-free dimming of lights for precise control of brightness level while maintaining the power delivered to the lamp. The EPSW-20A-DRW-1P-3W explosion proof dimmer switch also works to save energy while reducing energy costs and helping to extend the life of the connected lamp. The dimmable rotary switch features surge protection technology, advanced heat sinks to extend the service life of the switch and protection from possible interference from radios and other equipment. The unit is also very user friendly as the position of the rotary dial indicates the perceived light level.

A rotary on/off switch can be found below the dimmer. The 1-pole 3-way switch features a double throw configuration with maintained action. Equipped with two positions, operators may access contact blocks that are rated at 20 amps inside the unit.

3-Way Switch: The EPSW-20A-DRW-1P-3W features a 3-way switch. This switch can be used as a standalone switch, but two switches are required for 3-way function such as operating the same light fixture from the top and bottom of a set of stairs.

Operation Voltage: The EPSW-20A-DRW-1P-3W operates on 600 V AC. This operation voltage covers 120V, 220V, 240V, 277V, 347V, 480V, and 600V.

Note on Dimming Voltage/Amperage: The voltage range is 0-10V, with 0V being completely off and 10V being full power. The max resistance is calculated for up to 25 devices being controlled by this unit. This dimmer is NOT compatible with incandescent lamps or screw-in compact fluorescent lamps. This unit IS compatible with LED, HID, fluorescent, compact fluorescent, induction, and any type of lamp that the power supply or ballast is 0-10V capable and has 0-10V control wires.

Hubs: These dimmer switches are not factory sealed and require external sealing fittings. This explosion proof switch is available with either 1/2" or 3/4" NPT tapped hubs. The conduit openings are provided on the top and bottom of the unit in feed through versions while dead end versions have a single conduit hub, providing easy and secure connection to main power line supplies.

This rotary dimmer switch is compatible with explosion proof dimmable light fixtures with V+ and V- dimming control wires. This dimmer is not compatible with voltage dimming, the driver/ballast must have 0-10V control wires for dimming to be compatible. The EPSW-20A-DRW-1P-3W-N4X is suitable for use in

environments where combustible dusts and particulates may be present as well as any other hazardous locations.
Mounting: External mounting lugs provide simple and secure mounting of the unit to walls and flat surfaces.
Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Lighting, Wet areas or Locations Where Combustible Dust is Present.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPSW-20A-DRW-1P-3W

Product ID: 272095

Export Control Classification Number (ECCN): EAR99

Options:

EPSW-20A-DRW-1P-3W-Hub Config-Configuration

Example: EPSW-20A-DRW-1P-3W-0.5IN-FT

Hub Config	
1/2 INCH	-0.5IN
3/4 INCH	-0.75IN

Configuration	
FEED-THRU	-FT
DEAD-END	-DE

Links (Click on the below items to view):

- **HigResPic1**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**