Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 272743

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

WALSB-50AI-125.250V-2.L09-2.L08-2.N07 Spider Box
Input: 50A CS6375 Inlet
Primary Voltage: 125/250V AC
Output: 50A CS6369 Feed Through
Secondary Voltage: 125V and 250V
Secondary Breakers: (2) 30A 2P [250V], (2) 20A 2P [250V], (2) 20A 1P [125V]
Secondary Receptacles: (2) 30A L6-30R [250V], (2) 20A L6-20R [250V], (2) 20A 5-20R [125V]
Secondary Protection: Ground Fault Circuit Interrupter
GFI Trip Level: 4-6 mA
Housing Material: 16-gauge Steel
Mounting: Portable/Base Stand
Dimensions: 11" x 21" x 14.5"
Weight: 29 lbs
Color: Yellow

Ratings/Approvals
NRTL Certified to UL 1640
NEMA 3R Weatherproof
Overload Protection
Short Circuit Protection

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas

The Larson Electronics WALSB-50AI-125.250V-2.L09-2.L08-2.N07 is a portable spider box for indoor, outdoor and rugged applications. This unit allows operators to use 125/250V power via a CS6375 electrical inlet. The device supports one feed through receptacle for 125/250V equipment, as well as six output receptacles. For robust

protection, the spider box is NEMA 3R rated and protected by impact/flame resistant weatherproof covers.

This portable spider box uses a 50-amp, 125/250V CS6375 inlet for bringing power into the unit, while the outlet is a 50-amp, 125/250V CS6369 feed through for powering 125/250V tools and machines. Operators can access two 30-amp 1-pole 250V breakers protecting two 30-amp L6-30R 250V receptacles, two 20-amp 1-pole 250V breakers protecting two 20-amp L6-20R 250V receptacles and two 20-amp 1-pole 125V breakers protecting two 20-amp 5-20R 125V receptacles on the unit. GFI trip level is set to 4-6 mA with a maximum trip time of 25 mS. The WALSB-50AI-125.250V-2.L09-2.L08-2.N07 spider box features short circuit, overload, open neutral and reverse phasing protection. Should circuit overload occur, the unit will automatically shut down to protect the spider box from damage.

The housing on the WALSB-50AI-125.250V-2.L09-2.L08-2.N07 is constructed of 16-gauge steel with a NEMA 3R enclosure rating. This device is approved for wet locations and features heavy-duty impact/flame resistant weatherproof covers. Two angled legs at the base of the unit and low center of gravity ensures this spider box does not tip over in the field.

Certification: All units are built in accordance to NFPA 70 (National Electric Code). All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 3R and NEMA 4x equipment can be equipped upon request.

Applications: Indoor or outdoor applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits and shipyard operations. These units are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 272743

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **Operations Manual**(https://www.larsonelectronics.com//images/product/Manual/272743.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/272743.JPG)
- **HigResPic2**(https://www.larsonelectronics.com//images/product/HigResPic2/272743.JPG)
- **HigResPic3**(https://www.larsonelectronics.com//images/product/HigResPic3/272743.JPG)
- **HigResPic4**(https://www.larsonelectronics.com//images/product/HigResPic4/272743.JPG)
- **HigResPic5**(https://www.larsonelectronics.com//images/product/HigResPic5/272743.JPG)
- **HigResPic6**(https://www.larsonelectronics.com//images/product/HigResPic6/272743.JPG)
- **HigResPic7**(https://www.larsonelectronics.com//images/product/HigResPic7/272743.JPG)
- **HigResPic8**(https://www.larsonelectronics.com//images/product/HigResPic8/272743.JPG)
- **HigResPic9**(https://www.larsonelectronics.com//images/product/HigResPic9/272743.JPG)
- **HigResPic10**(https://www.larsonelectronics.com//images/product/HigResPic10/272743.JPG)
- **Video1**(https://www.youtube.com/watch?v=1S-T6kqZndQ)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)