Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-AE.EX-STRB-LED-10W-P-24V-R1

10W Explosion Proof LED Strobe Indicator Warning Light - 24V, 50/60 Hz - Purple - Surface Mount - ATEX/IECEx

Product ID: 273022

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-AE.EX-STRB-LED-10W-P-24V-R1 LED Strobe Light

Listing: NRTL Listed for European Union and International
Lamp Technology: LED
Dimensions (w/ Mounting Bracket): 13.62" x 9.84" (346mm x 250mm)
Weight: -
Voltage: 24V AC/DC, 50/60Hz
Total Watts: 10W
Luminous Intensity: -
Luminous Efficacy: -
Lamp Life: 50,000+ Hours
LED Color: Purple
Color Rendering Index: -
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Beam Angle: 360°
Lighting Configuration: Strobe Flashing or Rotating Flash Pattern
Power Efficiency: -
Power Factor: -
Ambient Operating Temp Range: -20° C to +55°C
Operating Temp Rating: T6
Housing Material: Die-cast Aluminum Alloy
Housing Finish: Epoxy Resin Powder
Lens Material: Borosilicate Glass
Hardware Material: Stainless Steel
Mounting: Surface
Terminals: L1, N, PE
Cable Entry: (1) M25 x 1.5 - Molded Plastic w/ Stopping Plug
Cable Entry OD: 8-17mm

Ratings/Approvals

ATEX/IECEx Rated
Zones 1/2 and 21/22
Ex tb C T80 Db
Ex 2 GD Ex de C T6 Gb
IP66 Waterproof
T6 Temperature Rating

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The EPL-AE.EX-STRB-LED-10W-P-24V-R1 Explosion Proof LED Strobe Indicator Warning Light from Larson Electronics is a powerful lamp for ATEX/IECEx rated environments. This 10-watt purple fixture is compatible with 24V AC/DC, 50/60Hz and offers 360 degrees of illumination. Constructed of die-cast aluminum alloy with an epoxy resin powder finish, the IP66 rated light is

compatible with surface mounting applications.
The EPL-AE.EX-STRB-LED-10W-P-24V-R1 is a durable purple warning light for hazardous locations and combustible sites. Equipped with a corrosion-resistant housing, this unit operates on 24V AC/DC, 50/60 Hz. The 10-watt light features an expected lifespan of 50,000+ hours and offers powerful light output. A 360-degree beam angle ensures high visibility during use. Options for strobing patterns include: standard strobe flash or rotating flash. This purple LED luminary is constructed of die-cast aluminum alloy with an epoxy resin powder finish. Protected by a borosilicate toughened glass lens, the unit carries T6 and IP66 waterproof ratings. This LED aviation light is ATEX/IECEx rated for Zones 1, 2, 21 and 22.
LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than traditional lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional lighting.
Wiring: Cable entries are facilitated by one M25 x 1.5 hub (molded plastic cable gland and stopping plug). Terminal connections include: L1, N and PE.
Mounting: The EPL-AE.EX-STRB-LED-10W-P-24V-R1 is compatible with surface mounting installations.
Suggested Applications: Hazardous locations, warnings, outdoor sites, indicator lighting, obstruction lighting, aviation, marking, military lighting systems and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-AE.EX-STRB-LED-10W-P-24V-R1

Product ID: 273022

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPL-AE.EX-STRB-LED-10W-P-24V-R1-Pattern

Example: EPL-AE.EX-STRB-LED-10W-P-24V-R1-FS

Pattern	
FLASH	-FS
ROTATING	-RT

Links (Click on the below items to view):

- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**